

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	30 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

450

64	<i>(146,2)</i>
65	<i>(143,4)</i>
66	<i>(140,7)</i>

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	48 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
78	0	8,8	36,3	63,8	91,3	<i>(108,5)</i>
80	0	7,9	34,7	61,5	88,2	<i>(105)</i>
82	0	7,1	33,2	59,3	85,4	<i>(101,7)</i>

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
90	0	,6	24,5	48,4	72,3	87,2
92	0	0	23,2	46,6	69,9	84,6
94	0	0	22	44,9	67,7	(82)

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t) Radius (m)	80	160	240	320	400	450
94	0	0	19,6	42,6	65,6	79,9
96	0	0	18,4	40,9	63,4	77,4
98	0	0	17,3	39,3	61,3	75,1

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t) Radius (m)	80	160	240	320	400	450
98	0	0	14,7	36,4	58	71,5
100	0	0	13,7	34,9	56,1	69,3
102		0	12,8	33,5	54,3	67,3
104		0	11,9	32,2	52,5	65,3
106		0	10,9	30,9	50,9	63,3

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	160	240	320	400	450
102	0	11,6	32,3	53,1	66,1
104	0	10,7	31	51,4	64,1
106	0	9,8	29,8	49,7	62,2
108	0	9	28,6	48,1	60,4
110	0	8,2	27,4	46,6	58,6

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	160	240	320	400	450
110	0	6	25,2	44,4	56,5
112	0	5,2	24,1	43	54,8
114	0	4,5	23	41,5	53,1
116	0	3,7	22	40,2	51,5
118	0	3	20,9	38,8	50

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

	160	240	320	400	450
114	0	3,1	21,6	40,2	51,8
116	0	2,4	20,6	38,8	50,2
118	0	1,7	19,6	37,5	48,7
120	0	1	18,6	36,2	47,2
122	0	,4	17,7	35	45,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	160	240	320	400	450
118	0	0	17,5	35,4	46,6
120	0	0	16,5	34,2	45,2
122	0	0	15,6	33	43,8
124	0	0	14,7	31,8	42,4
126	0	0	13,9	30,6	41,1
128	0	0	13	29,5	39,8
130	0	0	12,2	28,4	38,5

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	160	240	320	400	450
122	0	0	14,8	32,2	43
124	0	0	13,9	31	41,7
126	0	0	13	29,8	40,3
128	0	0	12,2	28,7	39
130	0	0	11,4	27,6	37,8
132		0	10,6	26,6	36,6
134		0	9,8	25,5	35,4

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

	240	320	400	450
130	0	8,9	25,2	35,4
132	0	8,2	24,2	34,2
134	0	7,4	23,2	33
136	0	6,7	22,2	31,9
138	0	5,9	21,2	30,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
78	0	5,6	33,1	60,6	88,1	105,3
80	0	4,8	31,6	58,3	85,1	101,9
82	0	4	30,1	56,2	82,3	98,6

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	48 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
82	0	1	27,1	53,2	79,3	95,6
84	0	,3	25,8	51,2	76,7	92,6
86	0	0	24,5	49,4	74,2	89,7

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
94	0	0	16,8	39,6	62,5	76,7
96	0	0	15,7	38,1	60,4	74,4
98	0	0	14,7	36,6	58,5	72,2

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
98	0	12,2	34,2	56,2	70
100	0	11,3	32,8	54,4	67,8
102	0	10,4	31,5	52,6	65,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	160	240	320	400	450
102	0	7,8	28,6	49,3	62,3
104	0	7	27,4	47,7	60,4
106	0	6,2	26,2	46,1	58,6
108	0	5,4	25	44,6	56,8
110	0	4,7	23,9	43,1	55,1

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
110	0	3,5	22,7	41,9	53,9
112	0	2,8	21,7	40,5	52,3
114	0	2,1	20,7	39,2	50,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	160	240	320	400	450
114	0	0	18,4	37	48,6
116	0	0	17,5	35,7	47,1
118	0	0	16,5	34,4	45,6
120	0	0	15,6	33,2	44,2
122	0	0	14,8	32	42,9

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					

118	0	0	15,1	33	44,2
120	0	0	14,2	31,8	42,8
122	0	0	13,4	30,7	41,5
124	0	0	12,6	29,6	40,2
126	0	0	11,8	28,5	39

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

	240	320	400	450
122	0	11,2	28,6	39,4
124	0	10,4	27,5	38,1
126	0	9,6	26,4	36,9
128	0	8,8	25,3	35,7
130	0	8,1	24,3	34,5
132	0	7,4	23,3	33,3
134	0	6,6	22,4	32,2

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
126	0	8,8	25,6	36,1
128	0	8	24,5	34,9
130	0	7,2	23,5	33,7
132	0	6,5	22,5	32,5
134	0	5,8	21,6	31,4
136	0	5,1	20,6	30,3
138	0	4,4	19,7	29,3

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

	240	320	400	450
134	0	3,3	19,1	29
136	0	2,7	18,2	27,9
138	0	2	17,3	26,9
140	0	1,4	16,4	25,9
142	0	,7	15,6	24,9

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
82	0	0	23,5	49,6	75,7	92,1
84	0	0	22,3	47,7	73,2	89,1
86	0	0	21,1	46	70,8	86,3

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	48 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
86	0	0	18	42,9	67,7	83,2
88	0	0	17	41,2	65,5	80,7
90	0	0	16	39,7	63,4	78,2

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
94	0	12,3	35	57,7	71,9
96	0	11,4	33,6	55,9	69,8
98	0	10,6	32,4	54,1	67,7

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
98	0	9,1	30,9	52,8	66,5
100	0	8,2	29,7	51,1	64,5
102	0	7,4	28,4	49,4	62,5

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					

102	0	4,9	26	47,1	60,3
104	0	4,1	24,8	45,5	58,4
106	0	3,3	23,6	43,9	56,6

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	160	240	320	400	450
106	0	,9	20,8	40,8	53,3
108	0	,2	19,8	39,4	51,6
110	0	0	18,8	38	50
112	0	0	17,8	36,7	48,5
114	0	0	16,9	35,4	47

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					

114	0	0	15,6	34,2	45,7
116	0	0	14,7	32,9	44,3
118	0	0	13,9	31,8	43

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
118	0	11,6	29,5	40,7
120	0	10,8	28,4	39,4
122	0	10	27,3	38,1
124	0	9,2	26,2	36,9
126	0	8,5	25,2	35,7

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

	240	320	400	450
122	0	8,6	25,9	36,7
124	0	7,8	24,8	35,5
126	0	7,1	23,8	34,3
128	0	6,4	22,9	33,2
130	0	5,7	21,9	32

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
126	0	4,9	21,7	32,2
128	0	4,2	20,7	31
130	0	3,5	19,8	29,9
132	0	2,9	18,9	28,8
134	0	2,2	18	27,8
136	0	1,6	17,1	26,8
138	0	1	16,3	25,8

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

	240	320	400	450
130	0	2,7	19	29,1
132	0	2	18	28
134	0	1,4	17,1	27
136	0	,7	16,3	26
138	0	,1	15,4	25
140	0	0	14,6	24
142	0	0	13,8	23,1

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
138	0	0	12,9	22,5
140	0	0	12,1	21,5
142	0	0	11,3	20,6
144	0	0	10,6	19,7
146		0	9,8	18,9
148		0	9,1	18
150		0	8,4	17,2

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
86	0	15,1	39,9	64,8	80,3
88	0	14,1	38,3	62,6	77,8
90	0	13,1	36,8	60,6	75,4

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	48 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
90	0	10	33,7	57,4	72,2
92	0	9,1	32,3	55,5	70
94	0	8,4	31	53,7	67,9

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
98	0	5,1	26,8	48,6	62,2
100	0	4,4	25,7	47	60,3
102	0	3,8	24,6	45,5	58,5

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					

102	0	2,2	23,2	44,2	57,3
104	0	1,5	22,1	42,7	55,5
106	0	,9	21,1	41,2	53,8

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					

106	0	0	18,5	38,8	51,5
108	0	0	17,5	37,4	49,9
110	0	0	16,6	36,1	48,3

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	160	240	320	400	450
110	0	0	13,8	33	45,1
112	0	0	12,9	31,8	43,6
114	0	0	12,1	30,6	42,2
116		0	11,3	29,5	40,8
118		0	10,5	28,4	39,5

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)				
118	0	9,2	27,1	38,3
120	0	8,5	26	37
122	0	7,7	25	35,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

	240	320	400	450
122	0	5,4	22,7	33,5
124	0	4,7	21,8	32,4
126	0	4,1	20,8	31,3
128	0	3,4	19,9	30,2
130	0	2,8	19	29,1

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
126	0	2,6	19,3	29,8
128	0	2	18,4	28,7
130	0	1,3	17,6	27,7
132	0	,8	16,7	26,7
134	0	,2	15,9	25,7

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
130	0	0	15,4	25,5
132	0	0	14,5	24,5
134	0	0	13,7	23,5
136	0	0	12,9	22,6
138	0	0	12,1	21,7
140	0	0	11,4	20,8
142	0	0	10,6	19,9

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

320	400	450
-----	-----	-----

138	0	11,3	20,9
140	0	10,5	20
142	0	9,8	19,1
144	0	9,1	18,2
146	0	8,4	17,4

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

142	0	7,2	16,5
144	0	6,5	15,7
146	0	5,8	14,9
148	0	5,2	14,1
150	0	4,5	13,3
154	0	3,3	11,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
90	0	6,4	30,2	53,9	68,7
92	0	5,7	28,9	52	66,5
94	0	5	27,6	50,3	64,5

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
102	0	0	18,5	39,3	52,4
104	0	0	17,5	38	50,8
106	0	0	16,7	36,7	49,3

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
106	0	0	15,2	35,4	48
108	0	0	14,3	34,1	46,5
110	0	0	13,5	32,9	45

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

	240	320	400	450
110	0	10,9	30,4	42,6
112	0	10,1	29,2	41,2
114	0	9,3	28,1	39,8
116	0	8,5	27	38,5
118	0	7,7	25,9	37,2

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

	240	320	400	450
114	0	6,6	25,1	36,7
116	0	5,9	24,1	35,5
118	0	5,2	23,1	34,2
120	0	4,5	22,1	33,1
122	0	3,8	21,1	31,9

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	122	124	126	
	0	2,5	19,8	30,6
	0	1,9	18,9	29,5
	0	1,3	18	28,5

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
126	0	0	15,7	26,2
128	0	0	14,9	25,2
130	0	0	14,1	24,2
132	0	0	13,3	23,3
134	0	0	12,5	22,3

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
130	0	0	12,6	22,7
132	0	0	11,8	21,8
134	0	0	11,1	20,9
136		0	10,3	20
138		0	9,6	19,2

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

134	0	8,8	18,7
136	0	8,1	17,8
138	0	7,4	17
140	0	6,7	16,1
142	0	6,1	15,3
144	0	5,4	14,6
146	0	4,8	13,8

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

142	0	5,2	14,5
144	0	4,5	13,7
146	0	3,9	12,9
148	0	3,3	12,2
150	0	2,7	11,5

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	320	400	450
Radius (m)			

146	0	1,3	10,3
148	0	,7	9,6
150	0	,1	8,9
154	0	0	7,5
158	0	0	6,2

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	160	240	320	400	450
94	0	0	21,3	44	58,2
96	0	0	20,3	42,5	56,3
98	0	0	19,3	41	54,6

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)				
106	0	10,8	30,9	43,5
108	0	10,1	29,8	42,1
110	0	9,4	28,7	40,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)				
110	0	7,9	27,4	39,5
112	0	7,2	26,3	38,2
114	0	6,5	25,2	36,9

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

	240	320	400	450
114	0	3,9	22,8	34,5
116	0	3,3	21,7	33,3
118	0	2,6	20,7	32,1
120	0	2	19,8	30,9
122	0	1,3	18,8	29,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	122	124	126	
	0	0	0	
	16,1	15,3	14,4	
	26,9	25,9	24,9	

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
126	0	0	13,1	23,5
128	0	0	12,3	22,6
130	0	0	11,6	21,7

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

130	0	9,2	19,4
132	0	8,5	18,5
134	0	7,8	17,6
136	0	7,2	16,8
138	0	6,5	16

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

320	400	450
-----	-----	-----

134	0	6,3	16,1
136	0	5,6	15,3
138	0	5	14,5
140	0	4,4	13,8
142	0	3,8	13,1

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

138	0	2,8	12,3
140	0	2,1	11,6
142	0	1,5	10,8
144	0	1	10,1
146	0	,4	9,4
148	0	0	8,7
150	0	0	8,1

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

146	0	0	8,6
148	0	0	7,9
150	0	0	7,2
154	0	0	5,9

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

400	450
-----	-----

150	0	4,6
154	0	3,3
158	0	2,1
162	0	1

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)				
98	0	12,5	34,2	47,8
100	0	11,7	32,9	46,2
102	0	10,9	31,7	44,7

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	110	112	114	
	0	3,1	22,4	34,5
	0	2,5	21,5	33,3
	0	2	20,6	32,2

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	114	116	118	
	0	,6	19,3	31
	0	0	18,4	29,8
	0	0	17,5	28,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

	240	320	400	450
118	0	0	14,9	26,3
120	0	0	14,1	25,2
122	0	0	13,3	24,2
124	0	0	12,5	23,2
126	0	0	11,7	22,3

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

320	400	450
-----	-----	-----

126	0	9	19,4
128	0	8,3	18,6
130	0	7,6	17,7

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

	320	400	450
--	-----	-----	-----

130	0	6,2	16,3
132	0	5,6	15,6
134	0	5	14,8
136	0	4,4	14
138	0	3,8	13,3

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

134	0	2,6	12,4
136	0	2	11,7
138	0	1,4	10,9
140	0	,8	10,2
142	0	,3	9,6

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

320	400	450
-----	-----	-----

138	0	0	9,4
140	0	0	8,7
142	0	0	8
144	0	0	7,4
146	0	0	6,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

400	450
-----	-----

142	0	5,8
144	0	5,1
146	0	4,5
148	0	3,9
150	0	3,3
154	0	2,2

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

400	450
-----	-----

150	0	2,4
154	0	1,3
158	0	,2

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

400	450
-----	-----

154	0	0
158	0	0
162	0	0
166	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	102	104	106	
	0	4,4	25,3	38,3
	0	3,8	24,2	37
	0	3,2	23,2	35,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
114	0	0	14,6	26,3
116	0	0	13,9	25,3
118	0	0	13,1	24,4

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	320	400	450
Radius (m)			
118	0	11,8	23,1
120	0	11,1	22,1
122	0	10,3	21,2

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	320	400	450
Radius (m)			

122	0	7,8	18,7
124	0	7,1	17,9
126	0	6,4	17
128	0	5,7	16,1
130	0	5,1	15,3

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

130	0	2,4	12,5
132	0	1,8	11,8
134	0	1,3	11,1

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

	320	400	450
--	-----	-----	-----

134	0	0	9,7
136	0	0	9
138	0	0	8,3
140	0	0	7,7
142	0	0	7,1

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

400	450
-----	-----

138	0	5,9
140	0	5,3
142	0	4,7
144	0	4,1
146	0	3,5

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

 Superlift Counterweight (t)
 Radius (m)

400	450
-----	-----

142	0	3,1
144	0	2,5
146	0	2
148	0	1,4
150	0	,9
154	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	400	450
Radius (m)		

150	0	0
154	0	0
158	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	400	450
Radius (m)		

154	0	0
158	0	0
162	0	0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

158	0
162	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	36 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	102	104	106	
	0	0	0	0
	20	19	18,1	33
	31,8	30,6		

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

118	0	6,7	18
120	0	6,1	17,2
122	0	5,6	16,4

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

122	0	4,2	15,1
124	0	3,6	14,4
126	0	3,1	13,6

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	320	400	450
Radius (m)			

126	0	,5	11,1
128	0	0	10,3
130	0	0	9,6
132	0	0	8,9
134	0	0	8,2

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	400	450
Radius (m)		

134	0	5,5
136	0	4,9
138	0	4,3

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

400	450
-----	-----

138	0	2,8
140	0	2,3
142	0	1,7
144	0	1,2
146	0	,7

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

400	450
-----	-----

142	0	0
144	0	0
146	0	0
148	0	0
150	0	0

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)
Radius (m)

400	450
-----	-----

146	0	0
148	0	0
150	0	0
154	0	0
158	0	0

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	24,5 m
Superlift Radius	24 m

Superlift Counterweight (t)	400	450
Radius (m)		

154	0	0
158	0	0
162		0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!