

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	30 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

64	76
65	74,4
66	72,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	48 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
78	0	0	5,4	22,8	40,2	51,2
80	0	0	4,6	21,5	38,5	49,1
82	0	0	3,8	20,3	36,9	47,2

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
90	0	0	12,7	27,9	37,4
92	0	0	11,8	26,6	35,8
94	0	0	10,8	25,3	34,4

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
94	0	0	8,3	22,9	32
96	0	0	7,4	21,7	30,6
98	0	0	6,5	20,5	29,2

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					

98	0	0	4,1	17,8	26,4
100	0	0	3,3	16,8	25,1
102	0	0	2,6	15,7	24
104	0	0	1,8	14,7	22,8
106	0	0	1,1	13,8	21,7

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					

102	0	0	1,4	14,5	22,8
104	0	0	,7	13,6	21,6
106	0	0	0	12,6	20,5
108	0	0	0	11,8	19,5
110	0	0	0	10,9	18,5

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
110	0	0	8,7	16,3
112	0	0	7,9	15,4
114	0	0	7,1	14,4
116	0	0	6,3	13,5
118	0	0	5,6	12,7

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
114	0	0	5,7	13,1
116	0	0	5	12,2
118	0	0	4,2	11,3
120	0	0	3,5	10,5
122	0	0	2,9	9,7

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
118	0	0	2,1	9,2
120	0	0	1,4	8,4
122	0	0	,8	7,6
124	0	0	,1	6,8
126	0	0	0	6,1
128	0	0	0	5,4
130	0	0	0	4,7

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
122	0	0	0	6,8
124	0	0	0	6
126	0	0	0	5,3
128	0	0	0	4,6
130		0	0	3,8
132		0	0	3,2
134		0	0	2,5

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

 Superlift Counterweight (t)
 Radius (m)

320	400	450
-----	-----	-----

130	0	0	1,4
132	0	0	,8
134	0	0	,1
136	0	0	0
138	0	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
78	0	0	2,2	19,7	37,2	48,1
80	0	0	1,5	18,5	35,5	46,1
82	0	0	,8	17,4	33,9	44,3

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	48 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
82	0	0	14,3	30,9	41,3
84	0	0	13,3	29,5	39,6
86	0	0	12,4	28,1	38

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
94	0	0	5,6	20,1	29,2
96	0	0	4,8	19	27,9
98	0	0	4,1	18	26,6

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
98	0	0	1,5	15,5	24,2
100	0	0	,8	14,4	23
102	0	0	,1	13,4	21,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
102	0	0	10,9	19,1
104	0	0	10	18
106	0	0	9,1	17
108	0	0	8,3	16
110	0	0	7,5	15,1

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)				
110	0	0	6,3	13,9
112	0	0	5,6	13
114	0	0	4,8	12,2

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
114	0	0	2,6	9,9
116	0	0	1,9	9,1
118	0	0	1,2	8,3
120	0	0	,6	7,6
122	0	0	0	6,8

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

 Superlift Counterweight (t)
 Radius (m)

	240	320	400	450
118	0	0	0	6,9
120	0	0	0	6,2
122	0	0	0	5,5
124	0	0	0	4,8
126		0	0	4,1

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

320	400	450
-----	-----	-----

122	0	0	3,3
124	0	0	2,6
126	0	0	2
128	0	0	1,3
130	0	0	,7
132	0	0	0
134	0	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

126	0	0	1,1
128	0	0	,4
130	0	0	0
132	0	0	0
134	0	0	0
136	0	0	0
138	0	0	0

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	320	400	450
Radius (m)			

134	0	0	0
136	0	0	0
138	0	0	0
140	0	0	0
142		0	0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
82	0	0	10,8	27,4	37,8
84	0	0	9,9	26,1	36,2
86	0	0	9	24,8	34,7

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	48 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
86	0	0	5,9	21,7	31,6
88	0	0	5,2	20,6	30,2
90	0	0	4,4	19,5	28,9

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
94	0	0	1,2	15,7	24,7
96	0	0	,6	14,7	23,6
98	0	0	0	13,9	22,5

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
98	0	0	0	12,3	21
100	0	0	0	11,4	19,9
102	0	0	0	10,6	18,9

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)				
102	0	0	8	16,4
104	0	0	7,2	15,4
106	0	0	6,4	14,4

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

 Superlift Counterweight (t)
 Radius (m)

	240	320	400	450
106	0	0	3,8	11,8
108	0	0	3,1	10,9
110	0	0	2,4	10
112	0	0	1,7	9,2
114	0	0	1,1	8,4

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	114	116	118	
	0	0	0	7,2
	0	0	0	6,5
	0	0	0	5,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

 Superlift Counterweight (t)
 Radius (m)

	320	400	450
--	-----	-----	-----

118	0	0	3,5
120	0	0	2,8
122	0	0	2,1
124	0	0	1,5
126	0	0	,9

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	320	400	450
Radius (m)			

122	0	0	,7
124	0	0	,1
126	0	0	0
128	0	0	0
130	0	0	0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	320	400	450	
Radius (m)				

126	0	0	0
128	0	0	0
130	0	0	0
132	0	0	0
134	0	0	0
136	0	0	0
138	0	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

320	400	450
-----	-----	-----

130	0	0	0
132	0	0	0
134	0	0	0
136	0	0	0
138		0	0
140		0	0
142		0	0

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450
Radius (m)		

138	0	0
140	0	0
142	0	0
144	0	0
146	0	0
148	0	0
150	0	0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
86	0	0	3	18,8	28,7
88	0	0	2,3	17,8	27,4
90	0	0	1,7	16,7	26,2

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	48 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
90	0	0	0	13,6	23
92	0	0	0	12,7	21,9
94	0	0	0	11,8	20,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)				
98	0	0	8,4	17
100	0	0	7,6	16,1
102	0	0	6,9	15,2

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)				
102	0	0	5,4	13,7
104	0	0	4,6	12,8
106	0	0	3,9	11,9

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	106	108	110	
	0	0	1,3	9,4
	0	0	,7	8,6
	0	0	0	7,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

110	0	0	5,2
112	0	0	4,4
114	0	0	3,7
116	0	0	3
118	0	0	2,4

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

118	0	0	1,1
120	0	0	,5
122	0	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

 Superlift Counterweight (t)
 Radius (m)

320	400	450
-----	-----	-----

122	0	0	0
124	0	0	0
126	0	0	0
128	0	0	0
130	0	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	320	400	450
Radius (m)			

126	0	0	0
128	0	0	0
130	0	0	0
132	0	0	0
134		0	0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450
Radius (m)		

130	0	0
132	0	0
134	0	0
136	0	0
138	0	0
140	0	0
142	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450	
Radius (m)			

138	0	0	
140	0	0	
142	0	0	
144	0	0	
146	0	0	

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450
Radius (m)		

142	0	0
144	0	0
146	0	0
148		0
150		0
154		0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)				
90	0	0	10,1	19,5
92	0	0	9,2	18,5
94	0	0	8,4	17,5

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	102	104	106	
	0	0	,8	9,1
	0	0	,2	8,4
	0	0	0	7,7

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	106	108	110	
	0	0	0	6,2
	0	0	0	5,4
	0	0	0	4,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

110	0	0	2,2
112	0	0	1,5
114	0	0	,8
116	0	0	,2
118	0	0	0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

320	400	450
-----	-----	-----

114	0	0	0
116	0	0	0
118	0	0	0
120	0	0	0
122	0	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
122	0	0	0
124	0	0	0
126	0	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450	
Radius (m)			

126	0	0	
128	0	0	
130	0	0	
132	0	0	
134	0	0	

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450	
Radius (m)			

130	0	0	
132	0	0	
134	0	0	
136	0	0	
138	0	0	

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450
Radius (m)		

134	0	0
136	0	0
138	0	0
140	0	0
142	0	0
144	0	0
146		0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

142	0
144	0
146	0
148	0
150	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

 Superlift Counterweight (t)
 Radius (m)

450

146	0
148	0
150	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)				
94	0	0	2,2	11,2
96	0	0	1,5	10,4
98	0	0	,9	9,6

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

106	0	0	1,9
108	0	0	1,3
110	0	0	,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
110	0	0	0
112	0	0	0
114	0	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	320	400	450
Radius (m)			

114	0	0	0
116	0	0	0
118	0	0	0
120	0	0	0
122	0	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450	
Radius (m)			

122	0	0	
124	0	0	
126	0	0	

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450
Radius (m)		

126	0	0
128	0	0
130	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450	
Radius (m)			

130	0	0	
132	0	0	
134	0	0	
136	0	0	
138	0	0	

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

134	0
136	0
138	0
140	0
142	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

138	0
140	0
142	0
144	0
146	0
148	0
150	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
98	0	0	2,8
100	0	0	2,2
102	0	0	1,6

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	320	400	450
Radius (m)			
110	0	0	0
112	0	0	0
114	0	0	0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
 "Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450	
Radius (m)			

114	0	0	
116	0	0	
118	0	0	

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450	
Radius (m)			

118	0	0	
120	0	0	
122	0	0	
124	0	0	
126	0	0	

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
 "Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450	
Radius (m)			

126	0	0	
128	0	0	
130	0	0	

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

130	0
132	0
134	0
136	0
138	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

 Superlift Counterweight (t)
 Radius (m)

450

134	0
136	0
138	0
140	0
142	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	320	400	450
Radius (m)			
102	0	0	0
104	0	0	0
106	0	0	0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450	
Radius (m)			

114	0	0	
116	0	0	
118	0	0	

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450
Radius (m)		

118	0	0
120	0	0
122	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450	
Radius (m)			

122	0	0	
124	0	0	
126	0	0	
128	0	0	
130		0	

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

130	0
132	0
134	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
Radius (m)

134	0
136	0
138	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	36 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450
Radius (m)		

102	0	0
104	0	0
106	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)	400	450
Radius (m)		

118	0	0
120	0	0
122	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

Superlift Counterweight (t)
 Radius (m)

122	0
124	0
126	0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
 "Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	15,5 m
Superlift Radius	15 m

 Superlift Counterweight (t)
 Radius (m)

126	0
128	0
130	0
132	0
134	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!