

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 48 m |
| Jib Length | 30 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|-----|------|------|-------|-------|-------|
| 42 | 0 | 8,4 | 48 | 87,7 | 127,3 | 167 | 191,8 |
| 43 | 0 | 7,5 | 46,2 | 84,9 | 123,5 | 162,2 | 186,4 |
| 44 | 0 | 6,7 | 44,4 | 82,2 | 119,9 | 157,7 | 181,3 |
| 45 | 0 | 5,9 | 42,8 | 79,6 | 116,5 | 153,3 | 176,4 |
| 46 | 0 | 5,2 | 41,2 | 77,2 | 113,2 | 149,2 | 171,7 |
| 47 | 0 | 4,5 | 39,7 | 74,9 | 110,1 | 145,2 | 167,2 |
| 48 | 0 | 3,8 | 38,2 | 72,6 | 107 | 141,5 | 163 |
| 49 | 0 | 3,1 | 36,8 | 70,5 | 104,2 | 137,8 | 158,9 |
| 50 | 0 | 2,5 | 35,4 | 68,4 | 101,4 | 134,4 | 154,9 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 48 m |
| Jib Length | 36 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|-----|------|------|-------|-------|-------|
| 46 | 0 | 3,7 | 39,8 | 76 | 112,1 | 148,3 | 170,9 |
| 47 | 0 | 3 | 38,3 | 73,7 | 109 | 144,3 | 166,4 |
| 48 | 0 | 2,3 | 36,9 | 71,4 | 106 | 140,5 | 162,1 |
| 49 | 0 | 1,7 | 35,5 | 69,3 | 103,1 | 136,9 | 158,1 |
| 50 | 0 | 1,1 | 34,2 | 67,3 | 100,4 | 133,5 | 154,1 |
| 51 | 0 | ,6 | 33 | 65,3 | 97,8 | 130,1 | 150,4 |
| 52 | 0 | 0 | 31,7 | 63,5 | 95,2 | 127 | 146,8 |
| 53 | 0 | 0 | 30,6 | 61,7 | 92,8 | 123,9 | 143,4 |
| 54 | 0 | 0 | 29,5 | 60 | 90,5 | 121 | 140 |
| 55 | 0 | 0 | 28,4 | 58,3 | 88,2 | 118,1 | 136,8 |
| 56 | 0 | 0 | 27,3 | 56,7 | 86 | 115,4 | 133,7 |
| 57 | 0 | 0 | 26,3 | 55,1 | 83,9 | 112,8 | 130,8 |
| 58 | 0 | 0 | 25,3 | 53,6 | 81,9 | 110,2 | 127,9 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 48 m |
| Jib Length | 42 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|------|------|------|-------|-------|
| 50 | 0 | 0 | 32,7 | 65,9 | 99,1 | 132,2 | 153 |
| 51 | 0 | 0 | 31,5 | 64 | 96,5 | 128,9 | 149,2 |
| 52 | 0 | 0 | 30,3 | 62,1 | 93,9 | 125,8 | 145,7 |
| 53 | 0 | 0 | 29,2 | 60,3 | 91,5 | 122,7 | 142,2 |
| 54 | 0 | 0 | 28,1 | 58,6 | 89,2 | 119,8 | 138,9 |
| 55 | 0 | 0 | 27 | 57 | 87 | 117 | 135,7 |
| 56 | 0 | 0 | 26 | 55,4 | 84,8 | 114,3 | 132,6 |
| 57 | 0 | 0 | 25 | 53,9 | 82,8 | 111,7 | 129,7 |
| 58 | 0 | 0 | 24,1 | 52,4 | 80,8 | 109,1 | 126,9 |
| 59 | 0 | 0 | 23,1 | 51 | 78,8 | 106,7 | 124,1 |
| 60 | 0 | 0 | 22,3 | 49,6 | 77 | 104,4 | 121,5 |
| 62 | 0 | 0 | 20,6 | 47 | 73,5 | 99,9 | 116,4 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 48 m |
| Jib Length | 48 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|------|------|------|-------|-------|
| 54 | 0 | 0 | 25,1 | 55,7 | 86,3 | 116,9 | 136 |
| 55 | 0 | 0 | 24,1 | 54,1 | 84,1 | 114,1 | 132,8 |
| 56 | 0 | 0 | 23,1 | 52,5 | 82 | 111,4 | 129,8 |
| 57 | 0 | 0 | 22,2 | 51 | 79,9 | 108,8 | 126,9 |
| 58 | 0 | 0 | 21,2 | 49,6 | 78 | 106,3 | 124,1 |
| 59 | 0 | 0 | 20,4 | 48,2 | 76,1 | 103,9 | 121,3 |
| 60 | 0 | 0 | 19,5 | 46,9 | 74,2 | 101,6 | 118,7 |
| 62 | 0 | 0 | 17,9 | 44,3 | 70,8 | 97,2 | 113,8 |
| 64 | 0 | 0 | 16,4 | 42 | 67,6 | 93,1 | 109,1 |
| 66 | 0 | 0 | 15 | 39,8 | 64,5 | 89,3 | 104,8 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 48 m |
| Jib Length | 54 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|------|------|------|-------|-------|
| 58 | 0 | 0 | 19,8 | 48,2 | 76,7 | 105,1 | 122,9 |
| 59 | 0 | 0 | 18,9 | 46,9 | 74,8 | 102,7 | 120,2 |
| 60 | 0 | 0 | 18,1 | 45,5 | 73 | 100,4 | 117,6 |
| 62 | 0 | 0 | 16,5 | 43 | 69,5 | 96 | 112,6 |
| 64 | 0 | 0 | 15 | 40,6 | 66,2 | 91,9 | 107,9 |
| 66 | 0 | 0 | 13,6 | 38,4 | 63,2 | 88 | 103,6 |
| 68 | 0 | 0 | 12,2 | 36,3 | 60,4 | 84,4 | 99,5 |
| 70 | 0 | 0 | 11 | 34,4 | 57,7 | 81,1 | 95,6 |
| 72 | 0 | 0 | 9,9 | 32,5 | 55,2 | 77,9 | 92 |
| 74 | 0 | 0 | 8,8 | 30,8 | 52,8 | 74,9 | 88,6 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 48 m |
| Jib Length | 60 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

| Superlift Counterweight (t) Radius (m) | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|---|---|----|------|------|------|------|-------|
| 62 | 0 | 0 | 15,6 | 42,4 | 69,2 | 95,9 | 112,7 |
| 64 | 0 | 0 | 14,1 | 40 | 65,8 | 91,7 | 107,9 |
| 66 | 0 | 0 | 12,7 | 37,7 | 62,8 | 87,8 | 103,5 |
| 68 | 0 | 0 | 11,3 | 35,6 | 59,9 | 84,1 | 99,3 |
| 70 | 0 | 0 | 10,1 | 33,6 | 57,1 | 80,7 | 95,4 |
| 72 | 0 | 0 | 8,9 | 31,7 | 54,6 | 77,4 | 91,7 |
| 74 | 0 | 0 | 7,7 | 29,9 | 52,2 | 74,3 | 88,2 |
| 76 | 0 | 0 | 6,7 | 28,3 | 49,8 | 71,4 | 84,9 |
| 78 | 0 | 0 | 5,7 | 26,7 | 47,7 | 68,7 | 81,8 |

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 48 m |
| Jib Length | 66 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|------|------|------|------|-------|
| 66 | 0 | 0 | 10,5 | 35,8 | 61 | 86,3 | 102,1 |
| 68 | 0 | 0 | 9,1 | 33,6 | 58,1 | 82,6 | 97,9 |
| 70 | 0 | 0 | 7,9 | 31,6 | 55,3 | 79,1 | 93,9 |
| 72 | 0 | 0 | 6,7 | 29,7 | 52,8 | 75,8 | 90,2 |
| 74 | 0 | 0 | 5,5 | 27,9 | 50,3 | 72,7 | 86,7 |
| 76 | 0 | 0 | 4,5 | 26,2 | 48 | 69,8 | 83,3 |
| 78 | 0 | 0 | 3,5 | 24,6 | 45,8 | 67 | 80,2 |
| 80 | 0 | 0 | 2,5 | 23,1 | 43,7 | 64,3 | 77,2 |
| 82 | 0 | 0 | 1,6 | 21,6 | 41,7 | 61,8 | 74,4 |
| 84 | 0 | 0 | ,7 | 20,2 | 39,8 | 59,4 | 71,7 |
| 86 | 0 | 0 | 0 | 18,9 | 38 | 57,1 | 69,1 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 48 m |
| Jib Length | 72 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|-----|------|------|------|------|
| 66 | 0 | 0 | 7,8 | 32,5 | 57 | 81,6 | 97 |
| 68 | 0 | 0 | 6,6 | 30,4 | 54,3 | 78,1 | 93 |
| 70 | 0 | 0 | 5,4 | 28,5 | 51,7 | 74,8 | 89,3 |
| 72 | 0 | 0 | 4,2 | 26,7 | 49,2 | 71,7 | 85,7 |
| 74 | 0 | 0 | 3,2 | 25 | 46,9 | 68,7 | 82,4 |
| 76 | 0 | 0 | 2,2 | 23,4 | 44,7 | 65,9 | 79,2 |
| 78 | 0 | 0 | 1,2 | 21,9 | 42,6 | 63,3 | 76,2 |
| 80 | 0 | 0 | ,3 | 20,5 | 40,6 | 60,8 | 73,4 |
| 82 | 0 | 0 | 0 | 19,1 | 38,7 | 58,4 | 70,7 |
| 84 | 0 | 0 | 0 | 17,8 | 36,9 | 56,1 | 68,1 |
| 86 | 0 | 0 | 0 | 16,5 | 35,2 | 54 | 65,6 |
| 88 | 0 | 0 | 0 | 15,3 | 33,6 | 51,9 | 63,3 |
| 90 | 0 | 0 | 0 | 14,2 | 32 | 49,9 | 61,1 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 48 m |
| Jib Length | 78 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|----|---|----|-----|------|------|------|------|
| 70 | 0 | 0 | 4,2 | 27,3 | 50,5 | 73,6 | 88,1 |
| 72 | 0 | 0 | 3,1 | 25,5 | 48 | 70,5 | 84,6 |
| 74 | 0 | 0 | 2 | 23,9 | 45,7 | 67,6 | 81,2 |
| 76 | 0 | 0 | 1 | 22,3 | 43,5 | 64,8 | 78,1 |
| 78 | 0 | 0 | ,1 | 20,8 | 41,5 | 62,2 | 75,1 |
| 80 | 0 | 0 | 0 | 19,4 | 39,5 | 59,7 | 72,3 |
| 82 | 0 | 0 | 0 | 18 | 37,7 | 57,3 | 69,6 |
| 84 | 0 | 0 | 0 | 16,7 | 35,9 | 55 | 67 |
| 86 | 0 | 0 | 0 | 15,5 | 34,2 | 52,9 | 64,6 |
| 88 | 0 | 0 | 0 | 14,3 | 32,6 | 50,9 | 62,3 |
| 90 | 0 | 0 | 0 | 13,2 | 31,1 | 48,9 | 60,1 |
| 92 | | 0 | 0 | 12,1 | 29,6 | 47,1 | 58 |
| 94 | | 0 | 0 | 11,1 | 28,2 | 45,3 | 56 |
| 96 | | 0 | 0 | 10,1 | 26,9 | 43,6 | 54 |
| 98 | | 0 | 0 | 9,2 | 25,6 | 41,9 | 52,2 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 48 m |
| Jib Length | 84 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|---|----|-----|------|------|------|------|
| 74 | 0 | 0 | 0 | 21,9 | 43,8 | 65,7 | 79,3 |
| 76 | 0 | 0 | 0 | 20,3 | 41,6 | 62,9 | 76,2 |
| 78 | 0 | 0 | 0 | 18,8 | 39,5 | 60,3 | 73,2 |
| 80 | 0 | 0 | 0 | 17,4 | 37,6 | 57,8 | 70,4 |
| 82 | 0 | 0 | 0 | 16 | 35,7 | 55,4 | 67,7 |
| 84 | 0 | 0 | 0 | 14,8 | 34 | 53,2 | 65,2 |
| 86 | 0 | 0 | 0 | 13,6 | 32,3 | 51 | 62,7 |
| 88 | | 0 | 0 | 12,4 | 30,7 | 49 | 60,4 |
| 90 | | 0 | 0 | 11,3 | 29,1 | 47 | 58,2 |
| 92 | | 0 | 0 | 10,2 | 27,7 | 45,2 | 56,1 |
| 94 | | 0 | 0 | 9,2 | 26,3 | 43,4 | 54,1 |
| 96 | | 0 | 0 | 8,2 | 25 | 41,7 | 52,1 |
| 98 | | 0 | 0 | 7,3 | 23,7 | 40 | 50,3 |
| 100 | | 0 | 0 | 6,4 | 22,4 | 38,5 | 48,5 |
| 102 | | 0 | 0 | 5,5 | 21,2 | 37 | 46,8 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 48 m |
| Jib Length | 90 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|---|----|-----|------|------|------|------|
| 78 | 0 | 0 | 0 | 17,4 | 38,2 | 58,9 | 71,8 |
| 80 | 0 | 0 | 0 | 16 | 36,2 | 56,4 | 69 |
| 82 | 0 | 0 | 0 | 14,7 | 34,4 | 54 | 66,3 |
| 84 | | 0 | 0 | 13,4 | 32,6 | 51,8 | 63,8 |
| 86 | | 0 | 0 | 12,2 | 31 | 49,7 | 61,4 |
| 88 | | 0 | 0 | 11,1 | 29,4 | 47,7 | 59,1 |
| 90 | | 0 | 0 | 10 | 27,8 | 45,7 | 56,9 |
| 92 | | 0 | 0 | 8,9 | 26,4 | 43,9 | 54,8 |
| 94 | | 0 | 0 | 7,9 | 25 | 42,1 | 52,8 |
| 96 | | 0 | 0 | 6,9 | 23,7 | 40,4 | 50,9 |
| 98 | | 0 | 0 | 6 | 22,4 | 38,8 | 49 |
| 100 | | 0 | 0 | 5,2 | 21,2 | 37,2 | 47,3 |
| 102 | | 0 | 0 | 4,3 | 20 | 35,7 | 45,6 |
| 104 | | 0 | 0 | 3,5 | 18,9 | 34,3 | 43,9 |
| 106 | | 0 | 0 | 2,7 | 17,8 | 32,9 | 42,4 |
| 108 | | 0 | 0 | 2 | 16,8 | 31,6 | 40,9 |
| 110 | | 0 | 0 | 1,2 | 15,8 | 30,3 | 39,4 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 48 m |
| Jib Length | 96 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|------|------|------|------|
| 82 | 0 | 0 | 12,9 | 32,6 | 52,3 | 64,6 |
| 84 | 0 | 0 | 11,6 | 30,8 | 50 | 62,1 |
| 86 | 0 | 0 | 10,4 | 29,1 | 47,9 | 59,6 |
| 88 | 0 | 0 | 9,2 | 27,5 | 45,9 | 57,3 |
| 90 | 0 | 0 | 8,1 | 26 | 43,9 | 55,1 |
| 92 | 0 | 0 | 7,1 | 24,6 | 42,1 | 53 |
| 94 | 0 | 0 | 6,1 | 23,2 | 40,3 | 51 |
| 96 | 0 | 0 | 5,1 | 21,9 | 38,6 | 49,1 |
| 98 | 0 | 0 | 4,2 | 20,6 | 37 | 47,2 |
| 100 | 0 | 0 | 3,3 | 19,4 | 35,4 | 45,5 |
| 102 | 0 | 0 | 2,5 | 18,2 | 34 | 43,8 |
| 104 | 0 | 0 | 1,6 | 17,1 | 32,5 | 42,2 |
| 106 | 0 | 0 | ,9 | 16 | 31,1 | 40,6 |
| 108 | 0 | 0 | ,1 | 14,9 | 29,8 | 39,1 |
| 110 | 0 | 0 | 0 | 13,9 | 28,5 | 37,6 |
| 112 | 0 | 0 | 0 | 13 | 27,3 | 36,2 |
| 114 | 0 | 0 | 0 | 12 | 26,1 | 34,9 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 48 m |
| Jib Length | 102 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

 Superlift Counterweight (t)
 Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|-----|------|------|------|
| 86 | 0 | 0 | 9,8 | 28,6 | 47,4 | 59,2 |
| 88 | 0 | 0 | 8,6 | 27 | 45,4 | 56,9 |
| 90 | 0 | 0 | 7,5 | 25,5 | 43,4 | 54,7 |
| 92 | 0 | 0 | 6,4 | 24 | 41,6 | 52,5 |
| 94 | 0 | 0 | 5,4 | 22,6 | 39,8 | 50,5 |
| 96 | 0 | 0 | 4,5 | 21,3 | 38,1 | 48,6 |
| 98 | 0 | 0 | 3,5 | 20 | 36,5 | 46,7 |
| 100 | 0 | 0 | 2,7 | 18,8 | 34,9 | 45 |
| 102 | 0 | 0 | 1,8 | 17,6 | 33,4 | 43,3 |
| 104 | 0 | 0 | 1 | 16,5 | 31,9 | 41,6 |
| 106 | 0 | 0 | ,2 | 15,4 | 30,5 | 40 |
| 108 | 0 | 0 | 0 | 14,3 | 29,2 | 38,5 |
| 110 | 0 | 0 | 0 | 13,3 | 27,9 | 37 |
| 112 | 0 | 0 | 0 | 12,3 | 26,7 | 35,6 |
| 114 | 0 | 0 | 0 | 11,4 | 25,5 | 34,3 |
| 116 | | 0 | 0 | 10,5 | 24,3 | 33 |
| 118 | | 0 | 0 | 9,6 | 23,2 | 31,7 |
| 120 | | 0 | 0 | 8,7 | 22,1 | 30,4 |
| 122 | | 0 | 0 | 7,9 | 21 | 29,2 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 48 m |
| Jib Length | 108 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----|----|-----|-----|------|------|------|
| 90 | 0 | 0 | 5,1 | 23,1 | 41 | 52,3 |
| 92 | 0 | 0 | 4,1 | 21,6 | 39,2 | 50,2 |
| 94 | 0 | 0 | 3,1 | 20,3 | 37,4 | 48,2 |
| 96 | 0 | 0 | 2,1 | 18,9 | 35,7 | 46,2 |
| 98 | 0 | 0 | 1,2 | 17,7 | 34,1 | 44,4 |
| 100 | 0 | 0 | ,3 | 16,5 | 32,6 | 42,6 |
| 102 | 0 | 0 | 0 | 15,3 | 31,1 | 40,9 |
| 104 | 0 | 0 | 0 | 14,2 | 29,6 | 39,3 |
| 106 | 0 | 0 | 0 | 13,1 | 28,3 | 37,8 |
| 108 | 0 | 0 | 0 | 12,1 | 26,9 | 36,2 |
| 110 | | 0 | 0 | 11,1 | 25,7 | 34,8 |
| 112 | | 0 | 0 | 10,1 | 24,4 | 33,4 |
| 114 | | 0 | 0 | 9,2 | 23,2 | 32 |
| 116 | | 0 | 0 | 8,3 | 22,1 | 30,7 |
| 118 | | 0 | 0 | 7,4 | 21 | 29,5 |
| 120 | | 0 | 0 | 6,6 | 19,9 | 28,3 |
| 122 | | 0 | 0 | 5,7 | 18,9 | 27,1 |
| 124 | | 0 | 0 | 4,9 | 17,9 | 25,9 |
| 126 | | 0 | 0 | 4,2 | 16,9 | 24,8 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 54 m |
| Jib Length | 30 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|------|------|-------|-------|-------|
| 46 | 0 | 0 | 35 | 71,1 | 107,1 | 143,2 | 165,7 |
| 47 | 0 | 0 | 33,7 | 68,9 | 104,1 | 139,3 | 161,4 |
| 48 | 0 | 0 | 32,3 | 66,8 | 101,2 | 135,7 | 157,2 |
| 49 | 0 | 0 | 31 | 64,8 | 98,5 | 132,2 | 153,2 |
| 50 | 0 | 0 | 29,8 | 62,8 | 95,8 | 128,8 | 149,4 |
| 51 | 0 | 0 | 28,6 | 61 | 93,3 | 125,6 | 145,8 |
| 52 | 0 | 0 | 27,5 | 59,2 | 90,8 | 122,5 | 142,3 |
| 53 | 0 | 0 | 26,4 | 57,4 | 88,5 | 119,5 | 138,9 |
| 54 | 0 | 0 | 25,3 | 55,8 | 86,2 | 116,6 | 135,6 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 54 m |
| Jib Length | 36 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|------|------|-------|-------|-------|
| 48 | 0 | 0 | 30,9 | 65,5 | 100,1 | 134,7 | 156,3 |
| 49 | 0 | 0 | 29,7 | 63,5 | 97,3 | 131,2 | 152,3 |
| 50 | 0 | 0 | 28,5 | 61,6 | 94,7 | 127,8 | 148,5 |
| 51 | 0 | 0 | 27,3 | 59,8 | 92,2 | 124,6 | 144,9 |
| 52 | 0 | 0 | 26,2 | 58 | 89,8 | 121,6 | 141,4 |
| 53 | 0 | 0 | 25,2 | 56,3 | 87,4 | 118,6 | 138,1 |
| 54 | 0 | 0 | 24,2 | 54,7 | 85,2 | 115,8 | 134,8 |
| 55 | 0 | 0 | 23,2 | 53,1 | 83,1 | 113 | 131,7 |
| 56 | 0 | 0 | 22,2 | 51,6 | 81 | 110,4 | 128,8 |
| 57 | 0 | 0 | 21,3 | 50,2 | 79 | 107,8 | 125,9 |
| 58 | 0 | 0 | 20,4 | 48,8 | 77,1 | 105,4 | 123,1 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 54 m |
| Jib Length | 42 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

 Superlift Counterweight (t)
 Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|------|------|------|-------|-------|
| 54 | 0 | 0 | 22,7 | 53,3 | 83,9 | 114,5 | 133,6 |
| 55 | 0 | 0 | 21,7 | 51,7 | 81,8 | 111,8 | 130,5 |
| 56 | 0 | 0 | 20,8 | 50,2 | 79,7 | 109,2 | 127,6 |
| 57 | 0 | 0 | 19,9 | 48,8 | 77,7 | 106,6 | 124,7 |
| 58 | 0 | 0 | 19 | 47,4 | 75,8 | 104,2 | 121,9 |
| 59 | 0 | 0 | 18,2 | 46,1 | 74 | 101,8 | 119,3 |
| 60 | 0 | 0 | 17,4 | 44,8 | 72,2 | 99,6 | 116,7 |
| 62 | 0 | 0 | 15,9 | 42,4 | 68,8 | 95,3 | 111,8 |
| 64 | 0 | 0 | 14,5 | 40,1 | 65,7 | 91,3 | 107,3 |
| 66 | 0 | 0 | 13,1 | 37,9 | 62,7 | 87,5 | 103 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 54 m |
| Jib Length | 48 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|------|------|------|-------|-------|
| 58 | 0 | 0 | 16,1 | 44,5 | 72,9 | 101,2 | 119 |
| 59 | 0 | 0 | 15,3 | 43,2 | 71,1 | 98,9 | 116,4 |
| 60 | 0 | 0 | 14,5 | 41,9 | 69,3 | 96,7 | 113,8 |
| 62 | 0 | 0 | 13,1 | 39,5 | 66 | 92,5 | 109 |
| 64 | 0 | 0 | 11,7 | 37,3 | 62,9 | 88,5 | 104,5 |
| 66 | 0 | 0 | 10,4 | 35,2 | 60 | 84,8 | 100,3 |
| 68 | 0 | 0 | 9,2 | 33,3 | 57,3 | 81,3 | 96,3 |
| 70 | 0 | 0 | 8,1 | 31,5 | 54,8 | 78,1 | 92,7 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 54 m |
| Jib Length | 54 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

| Superlift Counterweight (t) Radius (m) | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|---|---|----|------|------|------|------|-------|
| 58 | 0 | 0 | 14,6 | 43,1 | 71,6 | 100 | 117,8 |
| 59 | 0 | 0 | 13,8 | 41,8 | 69,8 | 97,7 | 115,2 |
| 60 | 0 | 0 | 13,1 | 40,5 | 68 | 95,5 | 112,6 |
| 62 | 0 | 0 | 11,6 | 38,1 | 64,7 | 91,2 | 107,8 |
| 64 | 0 | 0 | 10,2 | 35,9 | 61,6 | 87,2 | 103,3 |
| 66 | 0 | 0 | 9 | 33,8 | 58,7 | 83,5 | 99,1 |
| 68 | 0 | 0 | 7,8 | 31,9 | 56 | 80,1 | 95,1 |
| 70 | 0 | 0 | 6,7 | 30 | 53,4 | 76,8 | 91,4 |
| 72 | 0 | 0 | 5,6 | 28,3 | 51 | 73,7 | 87,9 |
| 74 | 0 | 0 | 4,7 | 26,7 | 48,8 | 70,8 | 84,6 |
| 76 | 0 | 0 | 3,8 | 25,2 | 46,6 | 68,1 | 81,5 |
| 78 | 0 | 0 | 2,9 | 23,8 | 44,6 | 65,5 | 78,6 |

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 54 m |
| Jib Length | 60 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

| Superlift Counterweight (t) Radius (m) | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|---|---|----|------|------|------|------|-------|
| 62 | 0 | 0 | 10,8 | 37,6 | 64,3 | 91,1 | 107,9 |
| 64 | 0 | 0 | 9,4 | 35,3 | 61,2 | 87,1 | 103,3 |
| 66 | 0 | 0 | 8,1 | 33,2 | 58,2 | 83,3 | 99 |
| 68 | 0 | 0 | 6,9 | 31,2 | 55,5 | 79,8 | 95 |
| 70 | 0 | 0 | 5,8 | 29,3 | 52,9 | 76,4 | 91,2 |
| 72 | 0 | 0 | 4,7 | 27,6 | 50,4 | 73,3 | 87,6 |
| 74 | 0 | 0 | 3,7 | 25,9 | 48,1 | 70,3 | 84,2 |
| 76 | 0 | 0 | 2,7 | 24,3 | 45,9 | 67,6 | 81,1 |
| 78 | 0 | 0 | 1,8 | 22,8 | 43,9 | 64,9 | 78,1 |
| 80 | 0 | 0 | ,9 | 21,4 | 41,9 | 62,4 | 75,2 |
| 82 | 0 | 0 | ,1 | 20,1 | 40 | 60 | 72,5 |

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 54 m |
| Jib Length | 66 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|-----|------|------|------|------|
| 66 | 0 | 0 | 5,9 | 31,2 | 56,5 | 81,8 | 97,6 |
| 68 | 0 | 0 | 4,7 | 29,2 | 53,7 | 78,2 | 93,5 |
| 70 | 0 | 0 | 3,5 | 27,3 | 51,1 | 74,8 | 89,7 |
| 72 | 0 | 0 | 2,5 | 25,5 | 48,6 | 71,7 | 86,1 |
| 74 | 0 | 0 | 1,4 | 23,9 | 46,2 | 68,7 | 82,7 |
| 76 | 0 | 0 | ,5 | 22,3 | 44 | 65,8 | 79,4 |
| 78 | 0 | 0 | 0 | 20,8 | 42 | 63,2 | 76,4 |
| 80 | 0 | 0 | 0 | 19,3 | 40 | 60,6 | 73,5 |
| 82 | 0 | 0 | 0 | 18 | 38,1 | 58,2 | 70,8 |
| 84 | 0 | 0 | 0 | 16,7 | 36,3 | 55,9 | 68,1 |
| 86 | 0 | 0 | 0 | 15,5 | 34,6 | 53,7 | 65,7 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 54 m |
| Jib Length | 72 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|-----|------|------|------|------|
| 70 | 0 | 0 | 1 | 24,2 | 47,4 | 70,5 | 85 |
| 72 | 0 | 0 | 0 | 22,5 | 45 | 67,5 | 81,6 |
| 74 | 0 | 0 | 0 | 21 | 42,8 | 64,7 | 78,3 |
| 76 | 0 | 0 | 0 | 19,5 | 40,7 | 62 | 75,3 |
| 78 | 0 | 0 | 0 | 18 | 38,7 | 59,5 | 72,4 |
| 80 | 0 | 0 | 0 | 16,7 | 36,9 | 57 | 69,6 |
| 82 | 0 | 0 | 0 | 15,4 | 35,1 | 54,7 | 67 |
| 84 | 0 | 0 | 0 | 14,2 | 33,4 | 52,6 | 64,6 |
| 86 | | 0 | 0 | 13 | 31,8 | 50,5 | 62,2 |
| 88 | | 0 | 0 | 11,9 | 30,2 | 48,5 | 59,9 |
| 90 | | 0 | 0 | 10,9 | 28,7 | 46,6 | 57,8 |
| 92 | | 0 | 0 | 9,8 | 27,3 | 44,8 | 55,7 |
| 94 | | 0 | 0 | 8,9 | 25,9 | 43 | 53,7 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 54 m |
| Jib Length | 78 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|-----|------|------|------|------|
| 74 | 0 | 0 | 0 | 19,7 | 41,6 | 63,5 | 77,1 |
| 76 | 0 | 0 | 0 | 18,2 | 39,5 | 60,8 | 74,1 |
| 78 | 0 | 0 | 0 | 16,9 | 37,6 | 58,3 | 71,2 |
| 80 | 0 | 0 | 0 | 15,5 | 35,7 | 55,9 | 68,5 |
| 82 | 0 | 0 | 0 | 14,3 | 33,9 | 53,6 | 65,9 |
| 84 | | 0 | 0 | 13,1 | 32,2 | 51,4 | 63,4 |
| 86 | | 0 | 0 | 11,9 | 30,6 | 49,4 | 61,1 |
| 88 | | 0 | 0 | 10,8 | 29,1 | 47,4 | 58,8 |
| 90 | | 0 | 0 | 9,8 | 27,7 | 45,5 | 56,7 |
| 92 | | 0 | 0 | 8,8 | 26,3 | 43,7 | 54,7 |
| 94 | | 0 | 0 | 7,8 | 24,9 | 42 | 52,7 |
| 96 | | 0 | 0 | 6,9 | 23,7 | 40,4 | 50,8 |
| 98 | | 0 | 0 | 6,1 | 22,5 | 38,8 | 49,1 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 54 m |
| Jib Length | 84 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|------|------|------|------|
| 78 | 0 | 0 | 14,9 | 35,6 | 56,3 | 69,3 |
| 80 | 0 | 0 | 13,5 | 33,7 | 53,9 | 66,6 |
| 82 | 0 | 0 | 12,3 | 32 | 51,7 | 64 |
| 84 | 0 | 0 | 11,1 | 30,3 | 49,5 | 61,5 |
| 86 | 0 | 0 | 9,9 | 28,7 | 47,4 | 59,2 |
| 88 | 0 | 0 | 8,9 | 27,2 | 45,5 | 56,9 |
| 90 | 0 | 0 | 7,8 | 25,7 | 43,6 | 54,8 |
| 92 | 0 | 0 | 6,8 | 24,3 | 41,8 | 52,8 |
| 94 | 0 | 0 | 5,9 | 23 | 40,1 | 50,8 |
| 96 | 0 | 0 | 5 | 21,7 | 38,5 | 48,9 |
| 98 | 0 | 0 | 4,1 | 20,5 | 36,9 | 47,2 |
| 100 | 0 | 0 | 3,3 | 19,3 | 35,4 | 45,4 |
| 102 | 0 | 0 | 2,5 | 18,2 | 34 | 43,8 |
| 104 | 0 | 0 | 1,7 | 17,1 | 32,6 | 42,2 |
| 106 | 0 | 0 | 1 | 16,1 | 31,2 | 40,7 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 54 m |
| Jib Length | 90 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|------|------|------|------|
| 82 | 0 | 0 | 10,9 | 30,6 | 50,3 | 62,6 |
| 84 | 0 | 0 | 9,7 | 28,9 | 48,1 | 60,1 |
| 86 | 0 | 0 | 8,6 | 27,3 | 46,1 | 57,8 |
| 88 | 0 | 0 | 7,5 | 25,8 | 44,1 | 55,6 |
| 90 | 0 | 0 | 6,5 | 24,4 | 42,3 | 53,4 |
| 92 | 0 | 0 | 5,5 | 23 | 40,5 | 51,4 |
| 94 | 0 | 0 | 4,6 | 21,7 | 38,8 | 49,5 |
| 96 | 0 | 0 | 3,7 | 20,4 | 37,2 | 47,6 |
| 98 | 0 | 0 | 2,8 | 19,2 | 35,6 | 45,8 |
| 100 | 0 | 0 | 2 | 18 | 34,1 | 44,2 |
| 102 | 0 | 0 | 1,2 | 16,9 | 32,7 | 42,5 |
| 104 | 0 | 0 | ,4 | 15,9 | 31,3 | 40,9 |
| 106 | 0 | 0 | 0 | 14,9 | 30 | 39,4 |
| 108 | 0 | 0 | 0 | 13,9 | 28,7 | 38 |
| 110 | 0 | 0 | 0 | 12,9 | 27,5 | 36,6 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 54 m |
| Jib Length | 96 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|-----|------|------|------|
| 86 | 0 | 0 | 6,7 | 25,5 | 44,3 | 56 |
| 88 | 0 | 0 | 5,6 | 24 | 42,3 | 53,8 |
| 90 | 0 | 0 | 4,6 | 22,5 | 40,5 | 51,7 |
| 92 | 0 | 0 | 3,6 | 21,1 | 38,7 | 49,6 |
| 94 | 0 | 0 | 2,7 | 19,8 | 37 | 47,7 |
| 96 | 0 | 0 | 1,8 | 18,6 | 35,3 | 45,8 |
| 98 | 0 | 0 | ,9 | 17,4 | 33,8 | 44 |
| 100 | 0 | 0 | ,1 | 16,2 | 32,3 | 42,3 |
| 102 | 0 | 0 | 0 | 15,1 | 30,9 | 40,7 |
| 104 | 0 | 0 | 0 | 14 | 29,5 | 39,1 |
| 106 | 0 | 0 | 0 | 13 | 28,2 | 37,6 |
| 108 | 0 | 0 | 0 | 12 | 26,9 | 36,2 |
| 110 | | 0 | 0 | 11,1 | 25,7 | 34,8 |
| 112 | | 0 | 0 | 10,1 | 24,5 | 33,4 |
| 114 | | 0 | 0 | 9,3 | 23,3 | 32,1 |
| 116 | | 0 | 0 | 8,4 | 22,2 | 30,9 |
| 118 | | 0 | 0 | 7,6 | 21,1 | 29,6 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 54 m |
| Jib Length | 102 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|-----|------|------|------|
| 86 | 0 | 0 | 6,1 | 24,9 | 43,8 | 55,5 |
| 88 | 0 | 0 | 5 | 23,4 | 41,8 | 53,3 |
| 90 | 0 | 0 | 4 | 22 | 39,9 | 51,2 |
| 92 | 0 | 0 | 3 | 20,6 | 38,2 | 49,1 |
| 94 | 0 | 0 | 2,1 | 19,2 | 36,4 | 47,2 |
| 96 | 0 | 0 | 1,2 | 18 | 34,8 | 45,3 |
| 98 | 0 | 0 | ,3 | 16,8 | 33,2 | 43,5 |
| 100 | 0 | 0 | 0 | 15,6 | 31,7 | 41,8 |
| 102 | 0 | 0 | 0 | 14,5 | 30,3 | 40,2 |
| 104 | 0 | 0 | 0 | 13,4 | 28,9 | 38,6 |
| 106 | 0 | 0 | 0 | 12,4 | 27,6 | 37,1 |
| 108 | | 0 | 0 | 11,4 | 26,3 | 35,6 |
| 110 | | 0 | 0 | 10,4 | 25,1 | 34,2 |
| 112 | | 0 | 0 | 9,5 | 23,9 | 32,8 |
| 114 | | 0 | 0 | 8,6 | 22,7 | 31,5 |
| 116 | | 0 | 0 | 7,8 | 21,6 | 30,3 |
| 118 | | 0 | 0 | 6,9 | 20,5 | 29 |
| 120 | | 0 | 0 | 6,1 | 19,5 | 27,8 |
| 122 | | 0 | 0 | 5,3 | 18,5 | 26,7 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 54 m |
| Jib Length | 108 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----|----|-----|-----|------|------|------|
| 90 | 0 | 0 | 1,5 | 19,5 | 37,5 | 48,7 |
| 92 | 0 | 0 | ,6 | 18,1 | 35,7 | 46,7 |
| 94 | 0 | 0 | 0 | 16,8 | 34 | 44,8 |
| 96 | 0 | 0 | 0 | 15,6 | 32,4 | 42,9 |
| 98 | 0 | 0 | 0 | 14,4 | 30,8 | 41,1 |
| 100 | 0 | 0 | 0 | 13,2 | 29,4 | 39,4 |
| 102 | 0 | 0 | 0 | 12,1 | 27,9 | 37,8 |
| 104 | | 0 | 0 | 11,1 | 26,6 | 36,2 |
| 106 | | 0 | 0 | 10,1 | 25,2 | 34,7 |
| 108 | | 0 | 0 | 9,1 | 24 | 33,3 |
| 110 | | 0 | 0 | 8,1 | 22,7 | 31,9 |
| 112 | | 0 | 0 | 7,2 | 21,6 | 30,5 |
| 114 | | 0 | 0 | 6,3 | 20,4 | 29,2 |
| 116 | | 0 | 0 | 5,5 | 19,3 | 28 |
| 118 | | 0 | 0 | 4,7 | 18,3 | 26,8 |
| 120 | | 0 | 0 | 3,9 | 17,2 | 25,6 |
| 122 | | 0 | 0 | 3,1 | 16,2 | 24,5 |
| 124 | | 0 | 0 | 2,4 | 15,3 | 23,4 |
| 126 | | 0 | 0 | 1,6 | 14,4 | 22,3 |
| 128 | | 0 | 0 | ,9 | 13,4 | 21,3 |
| 130 | | 0 | 0 | ,2 | 12,6 | 20,2 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 60 m |
| Jib Length | 30 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|------|------|------|-------|-------|
| 48 | 0 | 0 | 25,6 | 60,1 | 94,6 | 129,1 | 150,6 |
| 49 | 0 | 0 | 24,5 | 58,2 | 92 | 125,7 | 146,8 |
| 50 | 0 | 0 | 23,4 | 56,4 | 89,5 | 122,5 | 143,1 |
| 51 | 0 | 0 | 22,4 | 54,7 | 87 | 119,4 | 139,6 |
| 52 | 0 | 0 | 21,4 | 53 | 84,7 | 116,4 | 136,2 |
| 53 | 0 | 0 | 20,4 | 51,4 | 82,5 | 113,6 | 133 |
| 54 | 0 | 0 | 19,4 | 49,9 | 80,3 | 110,8 | 129,8 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 60 m |
| Jib Length | 36 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|------|------|------|-------|-------|
| 53 | | | | 50,2 | 81,4 | 112,6 | 132 |
| 54 | 0 | 0 | 18,1 | 48,7 | 79,3 | 109,8 | 128,9 |
| 55 | 0 | 0 | 17,3 | 47,2 | 77,2 | 107,2 | 125,9 |
| 56 | 0 | 0 | 16,4 | 45,8 | 75,2 | 104,7 | 123 |
| 57 | 0 | 0 | 15,6 | 44,5 | 73,4 | 102,2 | 120,3 |
| 58 | 0 | 0 | 14,9 | 43,2 | 71,5 | 99,9 | 117,6 |
| 59 | 0 | 0 | 14,1 | 41,9 | 69,8 | 97,6 | 115 |
| 60 | 0 | 0 | 13,4 | 40,7 | 68,1 | 95,4 | 112,5 |
| 62 | 0 | 0 | 11,9 | 38,4 | 64,8 | 91,2 | 107,8 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 60 m |
| Jib Length | 42 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|------|------|------|-------|-------|
| 54 | 0 | 0 | 16,6 | 47,2 | 77,9 | 108,5 | 127,6 |
| 55 | 0 | 0 | 15,8 | 45,8 | 75,8 | 105,9 | 124,7 |
| 56 | 0 | 0 | 14,9 | 44,4 | 73,9 | 103,4 | 121,8 |
| 57 | 0 | 0 | 14,1 | 43,1 | 72 | 100,9 | 119 |
| 58 | 0 | 0 | 13,4 | 41,8 | 70,2 | 98,6 | 116,3 |
| 59 | 0 | 0 | 12,6 | 40,5 | 68,4 | 96,3 | 113,8 |
| 60 | 0 | 0 | 11,9 | 39,3 | 66,8 | 94,2 | 111,3 |
| 62 | 0 | 0 | 10,6 | 37,1 | 63,6 | 90 | 106,6 |
| 64 | 0 | 0 | 9,3 | 35 | 60,6 | 86,2 | 102,2 |
| 66 | 0 | 0 | 8,1 | 33 | 57,8 | 82,6 | 98,1 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 60 m |
| Jib Length | 48 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|------|------|------|------|-------|
| 58 | 0 | 0 | 10,3 | 38,7 | 67,1 | 95,5 | 113,3 |
| 59 | 0 | 0 | 9,6 | 37,5 | 65,4 | 93,3 | 110,7 |
| 60 | 0 | 0 | 8,9 | 36,3 | 63,7 | 91,2 | 108,3 |
| 62 | 0 | 0 | 7,6 | 34,1 | 60,6 | 87,1 | 103,6 |
| 64 | 0 | 0 | 6,4 | 32 | 57,7 | 83,3 | 99,3 |
| 66 | 0 | 0 | 5,3 | 30,1 | 54,9 | 79,7 | 95,2 |
| 68 | 0 | 0 | 4,3 | 28,3 | 52,3 | 76,4 | 91,4 |
| 70 | 0 | 0 | 3,3 | 26,6 | 49,9 | 73,3 | 87,8 |
| 72 | 0 | 0 | 2,4 | 25 | 47,7 | 70,3 | 84,5 |
| 74 | 0 | 0 | 1,5 | 23,5 | 45,5 | 67,6 | 81,3 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 60 m |
| Jib Length | 54 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|-----|------|------|------|-------|
| 62 | 0 | 0 | 6,2 | 32,7 | 59,3 | 85,8 | 102,4 |
| 64 | 0 | 0 | 5 | 30,6 | 56,3 | 82 | 98,1 |
| 66 | 0 | 0 | 3,8 | 28,7 | 53,6 | 78,4 | 94 |
| 68 | 0 | 0 | 2,8 | 26,9 | 51 | 75,1 | 90,2 |
| 70 | 0 | 0 | 1,8 | 25,2 | 48,6 | 72 | 86,6 |
| 72 | 0 | 0 | ,9 | 23,6 | 46,3 | 69 | 83,2 |
| 74 | 0 | 0 | ,1 | 22,1 | 44,2 | 66,2 | 80 |
| 76 | 0 | 0 | 0 | 20,7 | 42,2 | 63,6 | 77 |
| 78 | 0 | 0 | 0 | 19,4 | 40,3 | 61,2 | 74,2 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 60 m |
| Jib Length | 60 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

| Superlift Counterweight (t) Radius (m) | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|---|---|----|-----|------|------|------|------|
| 66 | 0 | 0 | 3 | 28,1 | 53,2 | 78,3 | 93,9 |
| 68 | 0 | 0 | 1,9 | 26,2 | 50,5 | 74,9 | 90,1 |
| 70 | 0 | 0 | ,9 | 24,5 | 48,1 | 71,7 | 86,4 |
| 72 | 0 | 0 | 0 | 22,9 | 45,8 | 68,7 | 83 |
| 74 | 0 | 0 | 0 | 21,4 | 43,6 | 65,8 | 79,7 |
| 76 | 0 | 0 | 0 | 19,9 | 41,5 | 63,2 | 76,7 |
| 78 | 0 | 0 | 0 | 18,5 | 39,6 | 60,6 | 73,8 |
| 80 | 0 | 0 | 0 | 17,2 | 37,7 | 58,2 | 71 |
| 82 | 0 | 0 | 0 | 16 | 36 | 55,9 | 68,4 |
| 84 | 0 | 0 | 0 | 14,8 | 34,3 | 53,8 | 65,9 |
| 86 | 0 | 0 | 0 | 13,7 | 32,7 | 51,7 | 63,5 |

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 60 m |
| Jib Length | 66 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|-----|------|------|------|------|
| 70 | 0 | 0 | 0 | 22,4 | 46,2 | 70 | 84,9 |
| 72 | 0 | 0 | 0 | 20,8 | 43,9 | 67 | 81,4 |
| 74 | 0 | 0 | 0 | 19,3 | 41,7 | 64,1 | 78,1 |
| 76 | 0 | 0 | 0 | 17,8 | 39,6 | 61,4 | 75 |
| 78 | 0 | 0 | 0 | 16,4 | 37,6 | 58,8 | 72,1 |
| 80 | 0 | 0 | 0 | 15,1 | 35,8 | 56,4 | 69,3 |
| 82 | | 0 | 0 | 13,9 | 34 | 54,1 | 66,7 |
| 84 | | 0 | 0 | 12,7 | 32,3 | 51,9 | 64,2 |
| 86 | | 0 | 0 | 11,5 | 30,7 | 49,8 | 61,8 |
| 88 | | 0 | 0 | 10,5 | 29,1 | 47,8 | 59,5 |
| 90 | | 0 | 0 | 9,4 | 27,6 | 45,9 | 57,3 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 60 m |
| Jib Length | 72 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|----|-----|------|------|------|------|
| 74 | 0 | 0 | 16,4 | 38,3 | 60,2 | 73,8 |
| 76 | 0 | 0 | 15 | 36,3 | 57,6 | 70,9 |
| 78 | 0 | 0 | 13,7 | 34,4 | 55,1 | 68,1 |
| 80 | 0 | 0 | 12,4 | 32,6 | 52,8 | 65,4 |
| 82 | 0 | 0 | 11,3 | 31 | 50,6 | 62,9 |
| 84 | 0 | 0 | 10,1 | 29,4 | 48,5 | 60,5 |
| 86 | 0 | 0 | 9,1 | 27,8 | 46,6 | 58,3 |
| 88 | 0 | 0 | 8,1 | 26,4 | 44,7 | 56,1 |
| 90 | 0 | 0 | 7,1 | 25 | 42,9 | 54 |
| 92 | 0 | 0 | 6,2 | 23,6 | 41,1 | 52,1 |
| 94 | 0 | 0 | 5,3 | 22,4 | 39,5 | 50,2 |
| 96 | 0 | 0 | 4,4 | 21,1 | 37,9 | 48,3 |
| 98 | 0 | 0 | 3,6 | 19,9 | 36,3 | 46,6 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 60 m |
| Jib Length | 78 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|------|------|------|------|
| 78 | 0 | 0 | 12,4 | 33,2 | 53,9 | 66,8 |
| 80 | 0 | 0 | 11,2 | 31,4 | 51,6 | 64,2 |
| 82 | 0 | 0 | 10,1 | 29,8 | 49,4 | 61,7 |
| 84 | 0 | 0 | 9 | 28,2 | 47,4 | 59,4 |
| 86 | 0 | 0 | 7,9 | 26,7 | 45,4 | 57,1 |
| 88 | 0 | 0 | 6,9 | 25,2 | 43,5 | 55 |
| 90 | 0 | 0 | 6 | 23,9 | 41,7 | 52,9 |
| 92 | 0 | 0 | 5,1 | 22,5 | 40 | 51 |
| 94 | 0 | 0 | 4,2 | 21,3 | 38,4 | 49,1 |
| 96 | 0 | 0 | 3,3 | 20,1 | 36,8 | 47,3 |
| 98 | 0 | 0 | 2,5 | 18,9 | 35,3 | 45,6 |
| 100 | 0 | 0 | 1,8 | 17,8 | 33,9 | 43,9 |
| 102 | 0 | 0 | 1 | 16,8 | 32,5 | 42,3 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 60 m |
| Jib Length | 84 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|------|------|------|------|
| 78 | 0 | 0 | 10,4 | 31,2 | 51,9 | 64,9 |
| 80 | 0 | 0 | 9,2 | 29,4 | 49,6 | 62,3 |
| 82 | 0 | 0 | 8 | 27,8 | 47,5 | 59,8 |
| 84 | 0 | 0 | 6,9 | 26,2 | 45,4 | 57,4 |
| 86 | 0 | 0 | 5,9 | 24,7 | 43,4 | 55,2 |
| 88 | 0 | 0 | 4,9 | 23,2 | 41,6 | 53 |
| 90 | 0 | 0 | 4 | 21,9 | 39,8 | 51 |
| 92 | 0 | 0 | 3,1 | 20,6 | 38,1 | 49 |
| 94 | 0 | 0 | 2,2 | 19,3 | 36,4 | 47,1 |
| 96 | 0 | 0 | 1,4 | 18,1 | 34,9 | 45,3 |
| 98 | 0 | 0 | ,6 | 17 | 33,4 | 43,6 |
| 100 | 0 | 0 | 0 | 15,9 | 32 | 42 |
| 102 | 0 | 0 | 0 | 14,8 | 30,6 | 40,4 |
| 104 | 0 | 0 | 0 | 13,8 | 29,2 | 38,9 |
| 106 | 0 | 0 | 0 | 12,8 | 28 | 37,4 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 60 m |
| Jib Length | 90 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|-----|------|------|------|
| 82 | 0 | 0 | 6,6 | 26,3 | 46 | 58,3 |
| 84 | 0 | 0 | 5,5 | 24,7 | 44 | 56 |
| 86 | 0 | 0 | 4,5 | 23,2 | 42 | 53,7 |
| 88 | 0 | 0 | 3,5 | 21,8 | 40,2 | 51,6 |
| 90 | 0 | 0 | 2,6 | 20,5 | 38,4 | 49,6 |
| 92 | 0 | 0 | 1,7 | 19,2 | 36,7 | 47,6 |
| 94 | 0 | 0 | ,8 | 18 | 35,1 | 45,8 |
| 96 | 0 | 0 | 0 | 16,8 | 33,5 | 44 |
| 98 | 0 | 0 | 0 | 15,6 | 32 | 42,3 |
| 100 | 0 | 0 | 0 | 14,5 | 30,6 | 40,7 |
| 102 | 0 | 0 | 0 | 13,5 | 29,2 | 39,1 |
| 104 | 0 | 0 | 0 | 12,5 | 27,9 | 37,6 |
| 106 | | 0 | 0 | 11,5 | 26,7 | 36,1 |
| 108 | | 0 | 0 | 10,6 | 25,5 | 34,8 |
| 110 | | 0 | 0 | 9,7 | 24,3 | 33,4 |
| 112 | | 0 | 0 | 8,9 | 23,2 | 32,1 |
| 114 | | 0 | 0 | 8 | 22,1 | 30,9 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 60 m |
| Jib Length | 96 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|-----|------|------|------|
| 86 | 0 | 0 | 2,6 | 21,4 | 40,2 | 51,9 |
| 88 | 0 | 0 | 1,6 | 20 | 38,3 | 49,8 |
| 90 | 0 | 0 | ,7 | 18,6 | 36,5 | 47,8 |
| 92 | 0 | 0 | 0 | 17,3 | 34,8 | 45,8 |
| 94 | 0 | 0 | 0 | 16,1 | 33,2 | 44 |
| 96 | 0 | 0 | 0 | 14,9 | 31,7 | 42,2 |
| 98 | 0 | 0 | 0 | 13,8 | 30,2 | 40,5 |
| 100 | 0 | 0 | 0 | 12,7 | 28,8 | 38,8 |
| 102 | | 0 | 0 | 11,6 | 27,4 | 37,3 |
| 104 | | 0 | 0 | 10,6 | 26,1 | 35,8 |
| 106 | | 0 | 0 | 9,7 | 24,8 | 34,3 |
| 108 | | 0 | 0 | 8,8 | 23,6 | 32,9 |
| 110 | | 0 | 0 | 7,9 | 22,5 | 31,6 |
| 112 | | 0 | 0 | 7 | 21,3 | 30,3 |
| 114 | | 0 | 0 | 6,2 | 20,2 | 29 |
| 116 | | 0 | 0 | 5,4 | 19,2 | 27,8 |
| 118 | | 0 | 0 | 4,6 | 18,2 | 26,7 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 60 m |
| Jib Length | 102 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----|----|-----|-----|------|------|------|
| 90 | 0 | 0 | 0 | 18 | 36 | 47,2 |
| 92 | 0 | 0 | 0 | 16,7 | 34,3 | 45,3 |
| 94 | 0 | 0 | 0 | 15,5 | 32,7 | 43,4 |
| 96 | 0 | 0 | 0 | 14,3 | 31,1 | 41,7 |
| 98 | 0 | 0 | 0 | 13,2 | 29,6 | 39,9 |
| 100 | | 0 | 0 | 12,1 | 28,2 | 38,3 |
| 102 | | 0 | 0 | 11 | 26,8 | 36,7 |
| 104 | | 0 | 0 | 10 | 25,5 | 35,2 |
| 106 | | 0 | 0 | 9,1 | 24,3 | 33,8 |
| 108 | | 0 | 0 | 8,1 | 23 | 32,3 |
| 110 | | 0 | 0 | 7,2 | 21,9 | 31 |
| 112 | | 0 | 0 | 6,4 | 20,7 | 29,7 |
| 114 | | 0 | 0 | 5,5 | 19,6 | 28,5 |
| 116 | | 0 | 0 | 4,7 | 18,6 | 27,2 |
| 118 | | 0 | 0 | 3,9 | 17,5 | 26,1 |
| 120 | | 0 | 0 | 3,2 | 16,6 | 24,9 |
| 122 | | 0 | 0 | 2,4 | 15,6 | 23,8 |
| 124 | | 0 | 0 | 1,7 | 14,7 | 22,8 |
| 126 | | 0 | 0 | 1 | 13,8 | 21,7 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 60 m |
| Jib Length | 108 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|-----|-----|-----|------|------|------|
| 94 | 0 | 0 | 13 | 30,2 | 41 |
| 96 | 0 | 0 | 11,8 | 28,7 | 39,2 |
| 98 | 0 | 0 | 10,7 | 27,2 | 37,5 |
| 100 | 0 | 0 | 9,6 | 25,8 | 35,9 |
| 102 | 0 | 0 | 8,6 | 24,4 | 34,3 |
| 104 | 0 | 0 | 7,6 | 23,1 | 32,8 |
| 106 | 0 | 0 | 6,7 | 21,9 | 31,4 |
| 108 | 0 | 0 | 5,7 | 20,6 | 30 |
| 110 | 0 | 0 | 4,8 | 19,5 | 28,6 |
| 112 | 0 | 0 | 4 | 18,4 | 27,3 |
| 114 | 0 | 0 | 3,2 | 17,3 | 26,1 |
| 116 | 0 | 0 | 2,4 | 16,2 | 24,9 |
| 118 | 0 | 0 | 1,6 | 15,2 | 23,7 |
| 120 | 0 | 0 | ,9 | 14,3 | 22,6 |
| 122 | 0 | 0 | ,2 | 13,3 | 21,5 |
| 124 | 0 | 0 | 0 | 12,4 | 20,5 |
| 126 | 0 | 0 | 0 | 11,5 | 19,5 |
| 128 | 0 | 0 | 0 | 10,7 | 18,5 |
| 130 | | 0 | 0 | 9,8 | 17,5 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 66 m |
| Jib Length | 30 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|------|------|------|-------|-------|
| 50 | 0 | 0 | 17,3 | 50,3 | 83,4 | 116,4 | 137,1 |
| 51 | 0 | 0 | 16,4 | 48,7 | 81,1 | 113,4 | 133,7 |
| 52 | 0 | 0 | 15,5 | 47,2 | 78,9 | 110,6 | 130,4 |
| 53 | 0 | 0 | 14,6 | 45,7 | 76,8 | 107,8 | 127,3 |
| 54 | 0 | 0 | 13,8 | 44,2 | 74,7 | 105,2 | 124,2 |
| 55 | 0 | 0 | 13 | 42,9 | 72,8 | 102,7 | 121,3 |
| 56 | 0 | 0 | 12,2 | 41,5 | 70,9 | 100,2 | 118,5 |
| 57 | 0 | 0 | 11,4 | 40,2 | 69 | 97,8 | 115,8 |
| 58 | 0 | 0 | 10,7 | 39 | 67,3 | 95,5 | 113,2 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 66 m |
| Jib Length | 36 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|------|------|------|-------|-------|
| 54 | 0 | 0 | 12,4 | 43 | 73,6 | 104,1 | 123,2 |
| 55 | 0 | 0 | 11,6 | 41,6 | 71,6 | 101,6 | 120,4 |
| 56 | 0 | 0 | 10,9 | 40,3 | 69,8 | 99,2 | 117,6 |
| 57 | 0 | 0 | 10,2 | 39,1 | 68 | 96,8 | 114,9 |
| 58 | 0 | 0 | 9,5 | 37,9 | 66,2 | 94,6 | 112,3 |
| 59 | 0 | 0 | 8,8 | 36,7 | 64,6 | 92,4 | 109,8 |
| 60 | 0 | 0 | 8,2 | 35,6 | 62,9 | 90,3 | 107,4 |
| 62 | 0 | 0 | 7 | 33,4 | 59,9 | 86,3 | 102,8 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 66 m |
| Jib Length | 42 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|-----|------|------|------|-------|
| 58 | 0 | 0 | 8 | 36,4 | 64,8 | 93,2 | 111 |
| 59 | 0 | 0 | 7,3 | 35,2 | 63,2 | 91,1 | 108,5 |
| 60 | 0 | 0 | 6,7 | 34,1 | 61,6 | 89 | 106,1 |
| 62 | 0 | 0 | 5,5 | 32 | 58,5 | 85 | 101,6 |
| 64 | 0 | 0 | 4,4 | 30,1 | 55,7 | 81,3 | 97,3 |
| 66 | 0 | 0 | 3,4 | 28,2 | 53 | 77,8 | 93,4 |
| 68 | 0 | 0 | 2,4 | 26,5 | 50,5 | 74,6 | 89,6 |
| 70 | 0 | 0 | 1,5 | 24,8 | 48,2 | 71,5 | 86,1 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 66 m |
| Jib Length | 48 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|-----|------|------|------|------|
| 62 | 0 | 0 | 2,4 | 28,9 | 55,4 | 81,9 | 98,5 |
| 64 | 0 | 0 | 1,4 | 27 | 52,7 | 78,3 | 94,3 |
| 66 | 0 | 0 | ,4 | 25,2 | 50 | 74,9 | 90,4 |
| 68 | 0 | 0 | 0 | 23,5 | 47,6 | 71,7 | 86,7 |
| 70 | 0 | 0 | 0 | 22 | 45,3 | 68,7 | 83,3 |
| 72 | 0 | 0 | 0 | 20,5 | 43,2 | 65,8 | 80 |
| 74 | 0 | 0 | 0 | 19,1 | 41,2 | 63,2 | 77 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 66 m |
| Jib Length | 54 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|-----|------|------|------|------|
| 66 | 0 | 0 | 0 | 23,8 | 48,7 | 73,6 | 89,1 |
| 68 | 0 | 0 | 0 | 22,1 | 46,3 | 70,4 | 85,5 |
| 70 | 0 | 0 | 0 | 20,6 | 44 | 67,4 | 82 |
| 72 | 0 | 0 | 0 | 19,1 | 41,8 | 64,5 | 78,7 |
| 74 | 0 | 0 | 0 | 17,7 | 39,8 | 61,9 | 75,7 |
| 76 | 0 | 0 | 0 | 16,4 | 37,9 | 59,4 | 72,8 |
| 78 | 0 | 0 | 0 | 15,2 | 36,1 | 57 | 70 |
| 80 | | 0 | 0 | 14 | 34,4 | 54,7 | 67,5 |
| 82 | | 0 | 0 | 12,9 | 32,8 | 52,6 | 65 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 66 m |
| Jib Length | 60 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|-----|------|------|------|------|
| 70 | 0 | 0 | 0 | 19,9 | 43,5 | 67,1 | 81,8 |
| 72 | 0 | 0 | 0 | 18,4 | 41,3 | 64,2 | 78,5 |
| 74 | 0 | 0 | 0 | 17 | 39,2 | 61,5 | 75,4 |
| 76 | 0 | 0 | 0 | 15,7 | 37,3 | 58,9 | 72,5 |
| 78 | | 0 | 0 | 14,4 | 35,5 | 56,5 | 69,7 |
| 80 | | 0 | 0 | 13,2 | 33,7 | 54,2 | 67 |
| 82 | | 0 | 0 | 12,1 | 32 | 52 | 64,5 |
| 84 | | 0 | 0 | 11 | 30,5 | 50 | 62,1 |
| 86 | | 0 | 0 | 9,9 | 29 | 48 | 59,8 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 66 m |
| Jib Length | 66 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|----|-----|------|------|------|------|
| 70 | 0 | 0 | 17,8 | 41,6 | 65,4 | 80,3 |
| 72 | 0 | 0 | 16,3 | 39,4 | 62,5 | 76,9 |
| 74 | 0 | 0 | 14,9 | 37,3 | 59,7 | 73,8 |
| 76 | 0 | 0 | 13,5 | 35,3 | 57,2 | 70,8 |
| 78 | 0 | 0 | 12,3 | 33,5 | 54,7 | 68 |
| 80 | 0 | 0 | 11,1 | 31,7 | 52,4 | 65,3 |
| 82 | 0 | 0 | 9,9 | 30 | 50,2 | 62,8 |
| 84 | 0 | 0 | 8,8 | 28,5 | 48,1 | 60,3 |
| 86 | 0 | 0 | 7,8 | 26,9 | 46,1 | 58 |
| 88 | 0 | 0 | 6,8 | 25,5 | 44,2 | 55,8 |
| 90 | 0 | 0 | 5,8 | 24,1 | 42,3 | 53,8 |
| 92 | 0 | 0 | 4,9 | 22,8 | 40,6 | 51,7 |
| 94 | 0 | 0 | 4 | 21,5 | 38,9 | 49,8 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 66 m |
| Jib Length | 72 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|----|-----|------|------|------|------|
| 74 | 0 | 0 | 12 | 33,9 | 55,8 | 69,5 |
| 76 | 0 | 0 | 10,7 | 32 | 53,3 | 66,7 |
| 78 | 0 | 0 | 9,5 | 30,3 | 51 | 64 |
| 80 | 0 | 0 | 8,4 | 28,6 | 48,8 | 61,4 |
| 82 | 0 | 0 | 7,3 | 27 | 46,7 | 59 |
| 84 | 0 | 0 | 6,3 | 25,5 | 44,7 | 56,7 |
| 86 | 0 | 0 | 5,3 | 24,1 | 42,8 | 54,5 |
| 88 | 0 | 0 | 4,4 | 22,7 | 41 | 52,5 |
| 90 | 0 | 0 | 3,5 | 21,4 | 39,3 | 50,5 |
| 92 | 0 | 0 | 2,6 | 20,1 | 37,6 | 48,6 |
| 94 | 0 | 0 | 1,8 | 18,9 | 36 | 46,7 |
| 96 | 0 | 0 | 1 | 17,8 | 34,5 | 45 |
| 98 | 0 | 0 | ,3 | 16,7 | 33,1 | 43,3 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 66 m |
| Jib Length | 78 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|-----|------|------|------|
| 78 | 0 | 0 | 8,2 | 29 | 49,7 | 62,7 |
| 80 | 0 | 0 | 7,1 | 27,3 | 47,5 | 60,2 |
| 82 | 0 | 0 | 6,1 | 25,8 | 45,5 | 57,8 |
| 84 | 0 | 0 | 5,1 | 24,3 | 43,5 | 55,5 |
| 86 | 0 | 0 | 4,1 | 22,8 | 41,6 | 53,3 |
| 88 | 0 | 0 | 3,2 | 21,5 | 39,8 | 51,2 |
| 90 | 0 | 0 | 2,3 | 20,2 | 38,1 | 49,3 |
| 92 | 0 | 0 | 1,5 | 19 | 36,5 | 47,4 |
| 94 | 0 | 0 | ,7 | 17,8 | 34,9 | 45,6 |
| 96 | 0 | 0 | 0 | 16,7 | 33,4 | 43,9 |
| 98 | 0 | 0 | 0 | 15,6 | 32 | 42,2 |
| 100 | 0 | 0 | 0 | 14,5 | 30,6 | 40,6 |
| 102 | 0 | 0 | 0 | 13,5 | 29,3 | 39,1 |
| 104 | 0 | 0 | 0 | 12,6 | 28 | 37,7 |
| 106 | | 0 | 0 | 11,7 | 26,8 | 36,2 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 66 m |
| Jib Length | 84 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|-----|------|------|------|
| 82 | 0 | 0 | 4 | 23,7 | 43,4 | 55,8 |
| 84 | 0 | 0 | 3 | 22,2 | 41,5 | 53,5 |
| 86 | 0 | 0 | 2 | 20,8 | 39,6 | 51,3 |
| 88 | 0 | 0 | 1,1 | 19,5 | 37,8 | 49,3 |
| 90 | 0 | 0 | ,3 | 18,2 | 36,1 | 47,3 |
| 92 | 0 | 0 | 0 | 17 | 34,5 | 45,4 |
| 94 | 0 | 0 | 0 | 15,8 | 32,9 | 43,6 |
| 96 | 0 | 0 | 0 | 14,7 | 31,4 | 41,9 |
| 98 | 0 | 0 | 0 | 13,6 | 30 | 40,3 |
| 100 | 0 | 0 | 0 | 12,6 | 28,6 | 38,7 |
| 102 | | 0 | 0 | 11,6 | 27,3 | 37,2 |
| 104 | | 0 | 0 | 10,6 | 26,1 | 35,7 |
| 106 | | 0 | 0 | 9,7 | 24,8 | 34,3 |
| 108 | | 0 | 0 | 8,8 | 23,7 | 33 |
| 110 | | 0 | 0 | 8 | 22,5 | 31,6 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 66 m |
| Jib Length | 90 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|-----|------|------|------|
| 86 | 0 | 0 | ,6 | 19,4 | 38,1 | 49,9 |
| 88 | 0 | 0 | 0 | 18 | 36,4 | 47,8 |
| 90 | 0 | 0 | 0 | 16,8 | 34,7 | 45,9 |
| 92 | 0 | 0 | 0 | 15,5 | 33 | 44 |
| 94 | 0 | 0 | 0 | 14,4 | 31,5 | 42,2 |
| 96 | 0 | 0 | 0 | 13,3 | 30 | 40,5 |
| 98 | | 0 | 0 | 12,2 | 28,6 | 38,9 |
| 100 | | 0 | 0 | 11,2 | 27,3 | 37,3 |
| 102 | | 0 | 0 | 10,2 | 26 | 35,8 |
| 104 | | 0 | 0 | 9,3 | 24,7 | 34,4 |
| 106 | | 0 | 0 | 8,4 | 23,5 | 33 |
| 108 | | 0 | 0 | 7,5 | 22,4 | 31,6 |
| 110 | | 0 | 0 | 6,7 | 21,2 | 30,4 |
| 112 | | 0 | 0 | 5,9 | 20,2 | 29,1 |
| 114 | | 0 | 0 | 5,1 | 19,1 | 27,9 |
| 116 | | 0 | 0 | 4,3 | 18,1 | 26,8 |
| 118 | | 0 | 0 | 3,6 | 17,2 | 25,7 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 66 m |
| Jib Length | 96 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|-----|-----|-----|------|------|------|
| 90 | 0 | 0 | 14,8 | 32,8 | 44 |
| 92 | 0 | 0 | 13,6 | 31,2 | 42,2 |
| 94 | 0 | 0 | 12,5 | 29,6 | 40,4 |
| 96 | 0 | 0 | 11,4 | 28,2 | 38,7 |
| 98 | 0 | 0 | 10,3 | 26,8 | 37 |
| 100 | 0 | 0 | 9,3 | 25,4 | 35,5 |
| 102 | 0 | 0 | 8,3 | 24,1 | 34 |
| 104 | 0 | 0 | 7,4 | 22,9 | 32,5 |
| 106 | 0 | 0 | 6,5 | 21,6 | 31,1 |
| 108 | 0 | 0 | 5,6 | 20,5 | 29,8 |
| 110 | 0 | 0 | 4,8 | 19,4 | 28,5 |
| 112 | 0 | 0 | 4 | 18,3 | 27,3 |
| 114 | 0 | 0 | 3,2 | 17,3 | 26,1 |
| 116 | 0 | 0 | 2,4 | 16,3 | 24,9 |
| 118 | 0 | 0 | 1,7 | 15,3 | 23,8 |
| 120 | 0 | 0 | 1 | 14,4 | 22,7 |
| 122 | 0 | 0 | ,3 | 13,5 | 21,7 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 66 m |
| Jib Length | 102 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|------------|-----|-----|------|------|------|
| 94 | 0 | 0 | 11,9 | 29,1 | 39,8 |
| 96 | 0 | 0 | 10,8 | 27,6 | 38,1 |
| 98 | 0 | 0 | 9,7 | 26,2 | 36,5 |
| 100 | 0 | 0 | 8,7 | 24,8 | 34,9 |
| 102 | 0 | 0 | 7,7 | 23,5 | 33,4 |
| 104 | 0 | 0 | 6,8 | 22,3 | 32 |
| 106 | 0 | 0 | 5,9 | 21,1 | 30,6 |
| 108 | 0 | 0 | 5 | 19,9 | 29,2 |
| 110 | 0 | 0 | 4,1 | 18,8 | 27,9 |
| 112 | 0 | 0 | 3,3 | 17,7 | 26,7 |
| 114 | 0 | 0 | 2,5 | 16,7 | 25,5 |
| 116 | 0 | 0 | 1,8 | 15,7 | 24,3 |
| 118 | 0 | 0 | 1,1 | 14,7 | 23,2 |
| 120 | 0 | 0 | ,4 | 13,8 | 22,1 |
| 122 | 0 | 0 | 0 | 12,8 | 21,1 |
| 124 | 0 | 0 | 0 | 11,9 | 20 |
| 126 | 0 | 0 | 0 | 11,1 | 19 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 66 m |
| Jib Length | 108 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|-----|-----|-----|-----|------|------|
| 98 | 0 | 0 | 7,2 | 23,7 | 34 |
| 100 | 0 | 0 | 6,2 | 22,3 | 32,4 |
| 102 | 0 | 0 | 5,2 | 21 | 30,9 |
| 104 | 0 | 0 | 4,3 | 19,8 | 29,5 |
| 106 | 0 | 0 | 3,4 | 18,6 | 28,1 |
| 108 | 0 | 0 | 2,5 | 17,5 | 26,8 |
| 110 | 0 | 0 | 1,7 | 16,4 | 25,5 |
| 112 | 0 | 0 | ,9 | 15,3 | 24,3 |
| 114 | 0 | 0 | ,2 | 14,3 | 23,1 |
| 116 | 0 | 0 | 0 | 13,3 | 21,9 |
| 118 | 0 | 0 | 0 | 12,3 | 20,8 |
| 120 | 0 | 0 | 0 | 11,4 | 19,8 |
| 122 | | 0 | 0 | 10,5 | 18,7 |
| 124 | | 0 | 0 | 9,6 | 17,7 |
| 126 | | 0 | 0 | 8,8 | 16,8 |
| 128 | | 0 | 0 | 8 | 15,8 |
| 130 | | 0 | 0 | 7,2 | 14,9 |
| 132 | | 0 | 0 | 6,4 | 14 |
| 134 | | 0 | 0 | 5,7 | 13,1 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 72 m |
| Jib Length | 30 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|-----|------|------|------|-------|
| 54 | 0 | 0 | 7,1 | 37,6 | 68,1 | 98,6 | 117,6 |
| 55 | 0 | 0 | 6,4 | 36,3 | 66,2 | 96,2 | 114,8 |
| 56 | 0 | 0 | 5,8 | 35,1 | 64,5 | 93,8 | 112,2 |
| 57 | 0 | 0 | 5,2 | 34 | 62,8 | 91,6 | 109,6 |
| 58 | 0 | 0 | 4,5 | 32,8 | 61,1 | 89,4 | 107,1 |
| 59 | 0 | 0 | 3,9 | 31,7 | 59,5 | 87,3 | 104,7 |
| 60 | 0 | 0 | 3,4 | 30,7 | 58 | 85,3 | 102,3 |
| 62 | 0 | 0 | 2,2 | 28,6 | 55 | 81,4 | 97,9 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 72 m |
| Jib Length | 36 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

| Superlift Counterweight (t) Radius (m) | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|---|---|----|-----|------|------|------|-------|
| 58 | 0 | 0 | 3,2 | 31,6 | 60 | 88,4 | 106,1 |
| 59 | 0 | 0 | 2,7 | 30,6 | 58,4 | 86,3 | 103,7 |
| 60 | 0 | 0 | 2,2 | 29,5 | 56,9 | 84,3 | 101,4 |
| 62 | 0 | 0 | 1,1 | 27,6 | 54 | 80,5 | 97 |
| 64 | 0 | 0 | ,2 | 25,8 | 51,3 | 76,9 | 92,9 |
| 66 | 0 | 0 | 0 | 24 | 48,8 | 73,6 | 89,1 |

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 72 m |
| Jib Length | 42 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|-----|------|------|------|------|
| 62 | 0 | 0 | 0 | 26,1 | 52,6 | 79,2 | 95,7 |
| 64 | 0 | 0 | 0 | 24,3 | 50 | 75,6 | 91,7 |
| 66 | 0 | 0 | 0 | 22,7 | 47,5 | 72,3 | 87,8 |
| 68 | 0 | 0 | 0 | 21,1 | 45,2 | 69,2 | 84,3 |
| 70 | 0 | 0 | 0 | 19,6 | 43 | 66,3 | 80,9 |
| 72 | 0 | 0 | 0 | 18,2 | 40,9 | 63,6 | 77,7 |
| 74 | 0 | 0 | 0 | 16,9 | 38,9 | 61 | 74,7 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 72 m |
| Jib Length | 48 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|-----|------|------|------|------|
| 66 | 0 | 0 | 0 | 19,6 | 44,4 | 69,2 | 84,7 |
| 68 | 0 | 0 | 0 | 18 | 42,1 | 66,2 | 81,2 |
| 70 | 0 | 0 | 0 | 16,6 | 40 | 63,3 | 77,9 |
| 72 | 0 | 0 | 0 | 15,3 | 38 | 60,6 | 74,8 |
| 74 | | 0 | 0 | 14 | 36,1 | 58,1 | 71,9 |
| 76 | | 0 | 0 | 12,9 | 34,3 | 55,7 | 69,1 |
| 78 | | 0 | 0 | 11,7 | 32,6 | 53,5 | 66,5 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 72 m |
| Jib Length | 54 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|----|-----|------|------|------|------|
| 66 | 0 | 0 | 18,1 | 43 | 67,9 | 83,5 |
| 68 | 0 | 0 | 16,6 | 40,8 | 64,9 | 80 |
| 70 | 0 | 0 | 15,2 | 38,6 | 62 | 76,7 |
| 72 | 0 | 0 | 13,9 | 36,6 | 59,3 | 73,5 |
| 74 | 0 | 0 | 12,6 | 34,7 | 56,8 | 70,6 |
| 76 | 0 | 0 | 11,4 | 32,9 | 54,4 | 67,8 |
| 78 | 0 | 0 | 10,3 | 31,2 | 52,1 | 65,2 |
| 80 | 0 | 0 | 9,3 | 29,6 | 50 | 62,7 |
| 82 | 0 | 0 | 8,3 | 28,1 | 48 | 60,4 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 72 m |
| Jib Length | 60 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|----|-----|------|------|------|------|
| 70 | 0 | 0 | 14,6 | 38,2 | 61,8 | 76,5 |
| 72 | 0 | 0 | 13,2 | 36,1 | 59 | 73,4 |
| 74 | 0 | 0 | 11,9 | 34,2 | 56,5 | 70,4 |
| 76 | 0 | 0 | 10,7 | 32,4 | 54 | 67,6 |
| 78 | 0 | 0 | 9,6 | 30,7 | 51,7 | 64,9 |
| 80 | 0 | 0 | 8,5 | 29 | 49,5 | 62,4 |
| 82 | 0 | 0 | 7,5 | 27,5 | 47,5 | 60 |
| 84 | 0 | 0 | 6,5 | 26 | 45,5 | 57,7 |
| 86 | 0 | 0 | 5,6 | 24,6 | 43,6 | 55,5 |
| 88 | 0 | 0 | 4,7 | 23,3 | 41,8 | 53,5 |
| 90 | 0 | 0 | 3,8 | 22 | 40,1 | 51,5 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 72 m |
| Jib Length | 66 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|----|-----|-----|------|------|------|
| 74 | 0 | 0 | 9,8 | 32,2 | 54,7 | 68,7 |
| 76 | 0 | 0 | 8,6 | 30,4 | 52,2 | 65,8 |
| 78 | 0 | 0 | 7,4 | 28,7 | 49,9 | 63,2 |
| 80 | 0 | 0 | 6,3 | 27 | 47,7 | 60,6 |
| 82 | 0 | 0 | 5,3 | 25,5 | 45,6 | 58,2 |
| 84 | 0 | 0 | 4,3 | 24 | 43,6 | 55,9 |
| 86 | 0 | 0 | 3,4 | 22,6 | 41,7 | 53,7 |
| 88 | 0 | 0 | 2,5 | 21,2 | 39,9 | 51,6 |
| 90 | 0 | 0 | 1,7 | 19,9 | 38,2 | 49,6 |
| 92 | 0 | 0 | ,9 | 18,7 | 36,5 | 47,7 |
| 94 | 0 | 0 | ,1 | 17,5 | 35 | 45,9 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 72 m |
| Jib Length | 72 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|-----|------|------|------|
| 78 | 0 | 0 | 4,7 | 25,5 | 46,2 | 59,2 |
| 80 | 0 | 0 | 3,7 | 23,9 | 44,1 | 56,8 |
| 82 | 0 | 0 | 2,7 | 22,4 | 42,2 | 54,5 |
| 84 | 0 | 0 | 1,8 | 21 | 40,3 | 52,3 |
| 86 | 0 | 0 | ,9 | 19,7 | 38,5 | 50,2 |
| 88 | 0 | 0 | ,1 | 18,4 | 36,8 | 48,2 |
| 90 | 0 | 0 | 0 | 17,2 | 35,1 | 46,3 |
| 92 | 0 | 0 | 0 | 16 | 33,5 | 44,5 |
| 94 | 0 | 0 | 0 | 14,9 | 32,1 | 42,8 |
| 96 | 0 | 0 | 0 | 13,9 | 30,6 | 41,1 |
| 98 | 0 | 0 | 0 | 12,8 | 29,2 | 39,5 |
| 100 | | 0 | 0 | 11,9 | 27,9 | 38 |
| 102 | | 0 | 0 | 10,9 | 26,6 | 36,5 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 72 m |
| Jib Length | 78 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|-----|------|------|------|
| 82 | 0 | 0 | 1,4 | 21,1 | 40,8 | 53,1 |
| 84 | 0 | 0 | ,5 | 19,7 | 39 | 51 |
| 86 | 0 | 0 | 0 | 18,4 | 37,2 | 48,9 |
| 88 | 0 | 0 | 0 | 17,2 | 35,5 | 46,9 |
| 90 | 0 | 0 | 0 | 16 | 33,9 | 45,1 |
| 92 | 0 | 0 | 0 | 14,8 | 32,3 | 43,3 |
| 94 | 0 | 0 | 0 | 13,7 | 30,9 | 41,5 |
| 96 | 0 | 0 | 0 | 12,7 | 29,4 | 39,9 |
| 98 | | 0 | 0 | 11,7 | 28,1 | 38,3 |
| 100 | | 0 | 0 | 10,7 | 26,8 | 36,8 |
| 102 | | 0 | 0 | 9,8 | 25,5 | 35,4 |
| 104 | | 0 | 0 | 8,9 | 24,4 | 34 |
| 106 | | 0 | 0 | 8,1 | 23,2 | 32,7 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 72 m |
| Jib Length | 84 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|-----|------|------|------|
| 86 | 0 | 0 | 0 | 16,4 | 35,2 | 46,9 |
| 88 | 0 | 0 | 0 | 15,1 | 33,5 | 44,9 |
| 90 | 0 | 0 | 0 | 13,9 | 31,9 | 43,1 |
| 92 | | 0 | 0 | 12,8 | 30,3 | 41,3 |
| 94 | | 0 | 0 | 11,7 | 28,9 | 39,6 |
| 96 | | 0 | 0 | 10,7 | 27,4 | 37,9 |
| 98 | | 0 | 0 | 9,7 | 26,1 | 36,4 |
| 100 | | 0 | 0 | 8,7 | 24,8 | 34,9 |
| 102 | | 0 | 0 | 7,8 | 23,6 | 33,4 |
| 104 | | 0 | 0 | 6,9 | 22,4 | 32 |
| 106 | | 0 | 0 | 6,1 | 21,2 | 30,7 |
| 108 | | 0 | 0 | 5,3 | 20,1 | 29,4 |
| 110 | | 0 | 0 | 4,5 | 19,1 | 28,2 |
| 112 | | 0 | 0 | 3,7 | 18 | 27 |
| 114 | | 0 | 0 | 3 | 17 | 25,8 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 72 m |
| Jib Length | 90 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|------------|-----|-----|------|------|------|
| 90 | 0 | 0 | 12,4 | 30,4 | 41,6 |
| 92 | 0 | 0 | 11,3 | 28,9 | 39,8 |
| 94 | 0 | 0 | 10,3 | 27,4 | 38,1 |
| 96 | 0 | 0 | 9,2 | 26 | 36,5 |
| 98 | 0 | 0 | 8,2 | 24,7 | 34,9 |
| 100 | 0 | 0 | 7,3 | 23,4 | 33,4 |
| 102 | 0 | 0 | 6,4 | 22,2 | 32 |
| 104 | 0 | 0 | 5,5 | 21 | 30,6 |
| 106 | 0 | 0 | 4,7 | 19,9 | 29,3 |
| 108 | 0 | 0 | 3,9 | 18,8 | 28 |
| 110 | 0 | 0 | 3,1 | 17,7 | 26,8 |
| 112 | 0 | 0 | 2,4 | 16,7 | 25,7 |
| 114 | 0 | 0 | 1,7 | 15,7 | 24,5 |
| 116 | 0 | 0 | 1 | 14,8 | 23,4 |
| 118 | 0 | 0 | ,3 | 13,9 | 22,4 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 72 m |
| Jib Length | 96 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|-----|-----|-----|------|------|------|
| 90 | 0 | 0 | 10,5 | 28,5 | 39,7 |
| 92 | 0 | 0 | 9,4 | 27 | 37,9 |
| 94 | 0 | 0 | 8,3 | 25,5 | 36,2 |
| 96 | 0 | 0 | 7,3 | 24,1 | 34,6 |
| 98 | 0 | 0 | 6,3 | 22,8 | 33,1 |
| 100 | 0 | 0 | 5,4 | 21,5 | 31,6 |
| 102 | 0 | 0 | 4,5 | 20,3 | 30,1 |
| 104 | 0 | 0 | 3,6 | 19,1 | 28,8 |
| 106 | 0 | 0 | 2,8 | 18 | 27,5 |
| 108 | 0 | 0 | 2 | 16,9 | 26,2 |
| 110 | 0 | 0 | 1,2 | 15,8 | 25 |
| 112 | 0 | 0 | ,5 | 14,8 | 23,8 |
| 114 | 0 | 0 | 0 | 13,9 | 22,7 |
| 116 | 0 | 0 | 0 | 12,9 | 21,6 |
| 118 | 0 | 0 | 0 | 12 | 20,5 |
| 120 | 0 | 0 | 0 | 11,1 | 19,5 |
| 122 | | 0 | 0 | 10,3 | 18,5 |
| 124 | | 0 | 0 | 9,4 | 17,5 |
| 126 | | 0 | 0 | 8,6 | 16,6 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 72 m |
| Jib Length | 102 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|-----|-----|-----|-----|------|------|
| 94 | 0 | 0 | 7,7 | 24,9 | 35,7 |
| 96 | 0 | 0 | 6,7 | 23,5 | 34,1 |
| 98 | 0 | 0 | 5,7 | 22,2 | 32,5 |
| 100 | 0 | 0 | 4,8 | 20,9 | 31 |
| 102 | 0 | 0 | 3,9 | 19,7 | 29,6 |
| 104 | 0 | 0 | 3 | 18,5 | 28,2 |
| 106 | 0 | 0 | 2,2 | 17,4 | 26,9 |
| 108 | 0 | 0 | 1,4 | 16,3 | 25,6 |
| 110 | 0 | 0 | ,6 | 15,2 | 24,4 |
| 112 | 0 | 0 | 0 | 14,2 | 23,2 |
| 114 | 0 | 0 | 0 | 13,2 | 22,1 |
| 116 | 0 | 0 | 0 | 12,3 | 21 |
| 118 | 0 | 0 | 0 | 11,4 | 19,9 |
| 120 | | 0 | 0 | 10,5 | 18,9 |
| 122 | | 0 | 0 | 9,6 | 17,9 |
| 124 | | 0 | 0 | 8,8 | 16,9 |
| 126 | | 0 | 0 | 8 | 16 |
| 128 | | 0 | 0 | 7,2 | 15,1 |
| 130 | | 0 | 0 | 6,5 | 14,2 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 72 m |
| Jib Length | 108 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|-----|-----|-----|-----|------|------|
| 98 | 0 | 0 | 3,1 | 19,6 | 29,9 |
| 100 | 0 | 0 | 2,2 | 18,4 | 28,5 |
| 102 | 0 | 0 | 1,3 | 17,1 | 27 |
| 104 | 0 | 0 | ,5 | 16 | 25,7 |
| 106 | 0 | 0 | 0 | 14,9 | 24,4 |
| 108 | 0 | 0 | 0 | 13,8 | 23,1 |
| 110 | 0 | 0 | 0 | 12,8 | 21,9 |
| 112 | 0 | 0 | 0 | 11,8 | 20,7 |
| 114 | | 0 | 0 | 10,8 | 19,6 |
| 116 | | 0 | 0 | 9,9 | 18,5 |
| 118 | | 0 | 0 | 9 | 17,5 |
| 120 | | 0 | 0 | 8,1 | 16,5 |
| 122 | | 0 | 0 | 7,2 | 15,5 |
| 124 | | 0 | 0 | 6,4 | 14,5 |
| 126 | | 0 | 0 | 5,7 | 13,6 |
| 128 | | 0 | 0 | 4,9 | 12,7 |
| 130 | | 0 | 0 | 4,1 | 11,9 |
| 132 | | 0 | 0 | 3,4 | 11 |
| 134 | | 0 | 0 | 2,7 | 10,2 |
| 136 | | 0 | 0 | 2 | 9,4 |
| 138 | | 0 | 0 | 1,4 | 8,6 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 78 m |
| Jib Length | 30 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

| | | | | | | | |
|-----------------------------|---|----|-----|-----|-----|-----|-----|
| Superlift Counterweight (t) | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
| Radius (m) | | | | | | | |

| | | | | | | | |
|-----------|---|---|---|------|------|------|------|
| 58 | 0 | 0 | 0 | 26,7 | 55 | 83,3 | 101 |
| 59 | 0 | 0 | 0 | 25,8 | 53,5 | 81,3 | 98,7 |
| 60 | 0 | 0 | 0 | 24,8 | 52,1 | 79,4 | 96,5 |
| 62 | 0 | 0 | 0 | 23 | 49,4 | 75,8 | 92,3 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 78 m |
| Jib Length | 36 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|-----|------|------|------|------|
| 58 | 0 | 0 | 0 | 25,5 | 53,9 | 82,3 | 100 |
| 59 | 0 | 0 | 0 | 24,5 | 52,4 | 80,3 | 97,7 |
| 60 | 0 | 0 | 0 | 23,6 | 51 | 78,4 | 95,5 |
| 62 | 0 | 0 | 0 | 21,8 | 48,3 | 74,8 | 91,3 |
| 64 | 0 | 0 | 0 | 20,2 | 45,8 | 71,4 | 87,4 |
| 66 | 0 | 0 | 0 | 18,6 | 43,4 | 68,2 | 83,7 |
| 68 | 0 | 0 | 0 | 17,2 | 41,2 | 65,2 | 80,3 |
| 70 | 0 | 0 | 0 | 15,8 | 39,1 | 62,4 | 77 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 78 m |
| Jib Length | 42 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|-----|------|------|------|------|
| 62 | 0 | 0 | 0 | 20,3 | 46,9 | 73,4 | 90 |
| 64 | 0 | 0 | 0 | 18,7 | 44,4 | 70 | 86,1 |
| 66 | 0 | 0 | 0 | 17,2 | 42,1 | 66,9 | 82,4 |
| 68 | | 0 | 0 | 15,8 | 39,9 | 64 | 79 |
| 70 | | 0 | 0 | 14,5 | 37,8 | 61,2 | 75,8 |
| 72 | | 0 | 0 | 13,2 | 35,9 | 58,6 | 72,8 |
| 74 | | 0 | 0 | 12 | 34,1 | 56,1 | 69,9 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 78 m |
| Jib Length | 48 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|----|-----|------|------|------|------|
| 66 | 0 | 0 | 14 | 38,8 | 63,7 | 79,2 |
| 68 | 0 | 0 | 12,6 | 36,7 | 60,8 | 75,8 |
| 70 | 0 | 0 | 11,4 | 34,7 | 58,1 | 72,7 |
| 72 | 0 | 0 | 10,1 | 32,8 | 55,5 | 69,7 |
| 74 | 0 | 0 | 9 | 31,1 | 53,1 | 66,9 |
| 76 | 0 | 0 | 8 | 29,4 | 50,8 | 64,3 |
| 78 | 0 | 0 | 7 | 27,8 | 48,7 | 61,8 |
| 80 | 0 | 0 | 6 | 26,4 | 46,7 | 59,4 |
| 82 | 0 | 0 | 5,2 | 25 | 44,8 | 57,2 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 78 m |
| Jib Length | 54 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|----|-----|-----|------|------|------|
| 70 | 0 | 0 | 9,9 | 33,3 | 56,8 | 71,4 |
| 72 | 0 | 0 | 8,7 | 31,5 | 54,2 | 68,4 |
| 74 | 0 | 0 | 7,6 | 29,7 | 51,8 | 65,6 |
| 76 | 0 | 0 | 6,6 | 28 | 49,5 | 63 |
| 78 | 0 | 0 | 5,6 | 26,5 | 47,4 | 60,5 |
| 80 | 0 | 0 | 4,6 | 25 | 45,4 | 58,1 |
| 82 | 0 | 0 | 3,7 | 23,6 | 43,5 | 55,9 |
| 84 | 0 | 0 | 2,9 | 22,3 | 41,6 | 53,7 |
| 86 | 0 | 0 | 2,1 | 21 | 39,9 | 51,7 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 78 m |
| Jib Length | 60 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|----|-----|-----|------|------|------|
| 74 | 0 | 0 | 7 | 29,2 | 51,5 | 65,4 |
| 76 | 0 | 0 | 5,9 | 27,5 | 49,2 | 62,8 |
| 78 | 0 | 0 | 4,9 | 26 | 47 | 60,2 |
| 80 | 0 | 0 | 3,9 | 24,4 | 45 | 57,8 |
| 82 | 0 | 0 | 3 | 23 | 43 | 55,5 |
| 84 | 0 | 0 | 2,1 | 21,6 | 41,2 | 53,3 |
| 86 | 0 | 0 | 1,3 | 20,3 | 39,4 | 51,3 |
| 88 | 0 | 0 | ,5 | 19,1 | 37,7 | 49,3 |
| 90 | 0 | 0 | 0 | 17,9 | 36,1 | 47,4 |
| 92 | 0 | 0 | 0 | 16,8 | 34,5 | 45,6 |
| 94 | 0 | 0 | 0 | 15,7 | 33 | 43,9 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 78 m |
| Jib Length | 66 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|----|-----|-----|------|------|------|
| 78 | 0 | 0 | 2,7 | 23,9 | 45,2 | 58,4 |
| 80 | 0 | 0 | 1,7 | 22,4 | 43,1 | 56 |
| 82 | 0 | 0 | ,8 | 21 | 41,1 | 53,7 |
| 84 | 0 | 0 | 0 | 19,6 | 39,2 | 51,5 |
| 86 | 0 | 0 | 0 | 18,3 | 37,4 | 49,4 |
| 88 | 0 | 0 | 0 | 17 | 35,7 | 47,4 |
| 90 | 0 | 0 | 0 | 15,9 | 34,1 | 45,5 |
| 92 | 0 | 0 | 0 | 14,7 | 32,6 | 43,7 |
| 94 | 0 | 0 | 0 | 13,6 | 31,1 | 42 |
| 96 | | 0 | 0 | 12,6 | 29,6 | 40,3 |
| 98 | | 0 | 0 | 11,5 | 28,3 | 38,7 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 78 m |
| Jib Length | 72 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|-----|------|------|------|
| 82 | 0 | 0 | 0 | 18 | 37,7 | 50 |
| 84 | 0 | 0 | 0 | 16,6 | 35,9 | 47,9 |
| 86 | 0 | 0 | 0 | 15,4 | 34,2 | 45,9 |
| 88 | 0 | 0 | 0 | 14,2 | 32,6 | 44 |
| 90 | 0 | 0 | 0 | 13,1 | 31 | 42,2 |
| 92 | | 0 | 0 | 12 | 29,5 | 40,5 |
| 94 | | 0 | 0 | 11 | 28,1 | 38,8 |
| 96 | | 0 | 0 | 10 | 26,8 | 37,3 |
| 98 | | 0 | 0 | 9,1 | 25,5 | 35,8 |
| 100 | | 0 | 0 | 8,2 | 24,2 | 34,3 |
| 102 | | 0 | 0 | 7,3 | 23 | 32,9 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 78 m |
| Jib Length | 78 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|-----|------|------|------|
| 82 | 0 | 0 | 0 | 16,6 | 36,3 | 48,6 |
| 84 | 0 | 0 | 0 | 15,3 | 34,5 | 46,5 |
| 86 | 0 | 0 | 0 | 14,1 | 32,8 | 44,6 |
| 88 | | 0 | 0 | 12,9 | 31,2 | 42,7 |
| 90 | | 0 | 0 | 11,8 | 29,7 | 40,9 |
| 92 | | 0 | 0 | 10,8 | 28,3 | 39,2 |
| 94 | | 0 | 0 | 9,8 | 26,9 | 37,6 |
| 96 | | 0 | 0 | 8,8 | 25,5 | 36 |
| 98 | | 0 | 0 | 7,9 | 24,3 | 34,5 |
| 100 | | 0 | 0 | 7 | 23 | 33,1 |
| 102 | | 0 | 0 | 6,1 | 21,9 | 31,7 |
| 104 | | 0 | 0 | 5,3 | 20,8 | 30,4 |
| 106 | | 0 | 0 | 4,5 | 19,7 | 29,1 |
| 108 | | 0 | 0 | 3,8 | 18,6 | 27,9 |
| 110 | | 0 | 0 | 3 | 17,6 | 26,7 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 78 m |
| Jib Length | 84 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|------------|-----|-----|------|------|------|
| 86 | 0 | 0 | 12 | 30,8 | 42,5 |
| 88 | 0 | 0 | 10,8 | 29,2 | 40,7 |
| 90 | 0 | 0 | 9,7 | 27,7 | 38,9 |
| 92 | 0 | 0 | 8,7 | 26,2 | 37,2 |
| 94 | 0 | 0 | 7,7 | 24,9 | 35,6 |
| 96 | 0 | 0 | 6,7 | 23,5 | 34 |
| 98 | 0 | 0 | 5,8 | 22,2 | 32,5 |
| 100 | 0 | 0 | 4,9 | 21 | 31,1 |
| 102 | 0 | 0 | 4,1 | 19,9 | 29,7 |
| 104 | 0 | 0 | 3,3 | 18,8 | 28,4 |
| 106 | 0 | 0 | 2,5 | 17,7 | 27,1 |
| 108 | 0 | 0 | 1,8 | 16,6 | 25,9 |
| 110 | 0 | 0 | 1 | 15,6 | 24,8 |
| 112 | 0 | 0 | ,3 | 14,7 | 23,6 |
| 114 | 0 | 0 | 0 | 13,7 | 22,5 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 78 m |
| Jib Length | 90 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|-----|-----|-----|-----|------|------|
| 90 | 0 | 0 | 8,2 | 26,2 | 37,4 |
| 92 | 0 | 0 | 7,2 | 24,7 | 35,7 |
| 94 | 0 | 0 | 6,2 | 23,4 | 34,1 |
| 96 | 0 | 0 | 5,3 | 22 | 32,5 |
| 98 | 0 | 0 | 4,4 | 20,8 | 31,1 |
| 100 | 0 | 0 | 3,5 | 19,6 | 29,6 |
| 102 | 0 | 0 | 2,7 | 18,4 | 28,3 |
| 104 | 0 | 0 | 1,9 | 17,3 | 27 |
| 106 | 0 | 0 | 1,1 | 16,3 | 25,7 |
| 108 | 0 | 0 | ,4 | 15,2 | 24,5 |
| 110 | 0 | 0 | 0 | 14,2 | 23,4 |
| 112 | 0 | 0 | 0 | 13,3 | 22,2 |
| 114 | 0 | 0 | 0 | 12,4 | 21,2 |
| 116 | 0 | 0 | 0 | 11,5 | 20,1 |
| 118 | | 0 | 0 | 10,6 | 19,1 |
| 120 | | 0 | 0 | 9,8 | 18,2 |
| 122 | | 0 | 0 | 9 | 17,2 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 78 m |
| Jib Length | 96 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|-----|-----|-----|-----|------|------|
| 94 | 0 | 0 | 4,2 | 21,4 | 32,2 |
| 96 | 0 | 0 | 3,3 | 20,1 | 30,6 |
| 98 | 0 | 0 | 2,4 | 18,9 | 29,2 |
| 100 | 0 | 0 | 1,5 | 17,7 | 27,8 |
| 102 | 0 | 0 | ,7 | 16,5 | 26,4 |
| 104 | 0 | 0 | 0 | 15,4 | 25,1 |
| 106 | 0 | 0 | 0 | 14,4 | 23,8 |
| 108 | 0 | 0 | 0 | 13,3 | 22,6 |
| 110 | 0 | 0 | 0 | 12,4 | 21,5 |
| 112 | | 0 | 0 | 11,4 | 20,4 |
| 114 | | 0 | 0 | 10,5 | 19,3 |
| 116 | | 0 | 0 | 9,6 | 18,3 |
| 118 | | 0 | 0 | 8,8 | 17,2 |
| 120 | | 0 | 0 | 7,9 | 16,3 |
| 122 | | 0 | 0 | 7,1 | 15,4 |
| 124 | | 0 | 0 | 6,4 | 14,4 |
| 126 | | 0 | 0 | 5,6 | 13,6 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 78 m |
| Jib Length | 102 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|------------|-----|-----|-----|------|------|
| 98 | 0 | 0 | 1,8 | 18,3 | 28,6 |
| 100 | 0 | 0 | ,9 | 17,1 | 27,2 |
| 102 | 0 | 0 | ,1 | 15,9 | 25,8 |
| 104 | 0 | 0 | 0 | 14,8 | 24,5 |
| 106 | 0 | 0 | 0 | 13,8 | 23,3 |
| 108 | 0 | 0 | 0 | 12,7 | 22,1 |
| 110 | 0 | 0 | 0 | 11,8 | 20,9 |
| 112 | | 0 | 0 | 10,8 | 19,8 |
| 114 | | 0 | 0 | 9,9 | 18,7 |
| 116 | | 0 | 0 | 9 | 17,7 |
| 118 | | 0 | 0 | 8,1 | 16,7 |
| 120 | | 0 | 0 | 7,3 | 15,7 |
| 122 | | 0 | 0 | 6,5 | 14,7 |
| 124 | | 0 | 0 | 5,7 | 13,8 |
| 126 | | 0 | 0 | 5 | 12,9 |
| 128 | | 0 | 0 | 4,2 | 12,1 |
| 130 | | 0 | 0 | 3,5 | 11,2 |
| 132 | | 0 | 0 | 2,8 | 10,4 |
| 134 | | 0 | 0 | 2,1 | 9,6 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 78 m |
| Jib Length | 108 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 240 | 320 | 400 | 450 |
|-----|-----|-----|------|------|
| 102 | 0 | 0 | 13,3 | 23,2 |
| 104 | 0 | 0 | 12,2 | 21,9 |
| 106 | 0 | 0 | 11,2 | 20,7 |
| 108 | 0 | 0 | 10,2 | 19,5 |
| 110 | 0 | 0 | 9,2 | 18,4 |
| 112 | 0 | 0 | 8,3 | 17,3 |
| 114 | 0 | 0 | 7,4 | 16,2 |
| 116 | 0 | 0 | 6,5 | 15,2 |
| 118 | 0 | 0 | 5,7 | 14,2 |
| 120 | 0 | 0 | 4,8 | 13,2 |
| 122 | 0 | 0 | 4,1 | 12,3 |
| 124 | 0 | 0 | 3,3 | 11,4 |
| 126 | 0 | 0 | 2,5 | 10,5 |
| 128 | 0 | 0 | 1,8 | 9,7 |
| 130 | 0 | 0 | 1,1 | 8,9 |
| 132 | 0 | 0 | ,5 | 8,1 |
| 134 | 0 | 0 | 0 | 7,3 |
| 136 | 0 | 0 | 0 | 6,5 |
| 138 | | 0 | 0 | 5,8 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 84 m |
| Jib Length | 30 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 0 | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|---|----|-----|------|------|------|------|
| 58 | 0 | 0 | 0 | 19,9 | 48,2 | 76,5 | 94,2 |
| 59 | 0 | 0 | 0 | 19 | 46,8 | 74,6 | 92 |
| 60 | 0 | 0 | 0 | 18,1 | 45,5 | 72,8 | 89,9 |
| 62 | | 0 | 0 | 16,5 | 42,9 | 69,3 | 85,8 |
| 64 | | 0 | 0 | 15 | 40,6 | 66,1 | 82,1 |
| 66 | | 0 | 0 | 13,6 | 38,3 | 63,1 | 78,5 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 84 m |
| Jib Length | 36 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

| Superlift Counterweight (t) | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------------------------|----|-----|------|------|------|------|
| Radius (m) | | | | | | |
| 62 | 0 | 0 | 15,4 | 41,9 | 68,3 | 84,9 |
| 64 | 0 | 0 | 13,9 | 39,5 | 65,2 | 81,2 |
| 66 | 0 | 0 | 12,6 | 37,4 | 62,2 | 77,7 |
| 68 | 0 | 0 | 11,3 | 35,3 | 59,4 | 74,4 |
| 70 | 0 | 0 | 10,1 | 33,4 | 56,7 | 71,3 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 84 m |
| Jib Length | 42 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

| | | | | | | |
|-----------------------------|----|-----|-----|-----|-----|-----|
| Superlift Counterweight (t) | 80 | 160 | 240 | 320 | 400 | 450 |
| Radius (m) | | | | | | |

| | | | | | | |
|-----------|---|---|------|------|------|------|
| 66 | 0 | 0 | 11,1 | 35,9 | 60,8 | 76,3 |
| 68 | 0 | 0 | 9,8 | 33,9 | 58 | 73,1 |
| 70 | 0 | 0 | 8,7 | 32 | 55,4 | 70 |
| 72 | 0 | 0 | 7,6 | 30,3 | 53 | 67,1 |
| 74 | 0 | 0 | 6,5 | 28,6 | 50,6 | 64,4 |
| 76 | 0 | 0 | 5,6 | 27 | 48,5 | 61,9 |
| 78 | 0 | 0 | 4,6 | 25,5 | 46,4 | 59,4 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 84 m |
| Jib Length | 48 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|----|-----|-----|------|------|------|
| 70 | 0 | 0 | 5,4 | 28,8 | 52,2 | 66,8 |
| 72 | 0 | 0 | 4,4 | 27,1 | 49,8 | 64 |
| 74 | 0 | 0 | 3,4 | 25,5 | 47,5 | 61,3 |
| 76 | 0 | 0 | 2,5 | 23,9 | 45,4 | 58,8 |
| 78 | 0 | 0 | 1,6 | 22,5 | 43,4 | 56,4 |
| 80 | 0 | 0 | ,8 | 21,1 | 41,5 | 54,2 |
| 82 | 0 | 0 | 0 | 19,9 | 39,7 | 52,1 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 84 m |
| Jib Length | 54 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|----|-----|-----|------|------|------|
| 74 | 0 | 0 | 2 | 24,1 | 46,2 | 60 |
| 76 | 0 | 0 | 1,1 | 22,6 | 44,1 | 57,5 |
| 78 | 0 | 0 | ,2 | 21,1 | 42,1 | 55,2 |
| 80 | 0 | 0 | 0 | 19,8 | 40,2 | 52,9 |
| 82 | 0 | 0 | 0 | 18,5 | 38,4 | 50,8 |
| 84 | 0 | 0 | 0 | 17,3 | 36,7 | 48,8 |
| 86 | 0 | 0 | 0 | 16,1 | 35 | 46,9 |
| 88 | 0 | 0 | 0 | 15,1 | 33,5 | 45 |
| 90 | 0 | 0 | 0 | 14 | 32,1 | 43,3 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 84 m |
| Jib Length | 60 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

| Superlift Counterweight (t) Radius (m) | 80 | 160 | 240 | 320 | 400 | 450 |
|---|----|-----|-----|------|------|------|
| 78 | 0 | 0 | 0 | 20,7 | 41,8 | 54,9 |
| 80 | 0 | 0 | 0 | 19,3 | 39,8 | 52,7 |
| 82 | 0 | 0 | 0 | 18 | 38 | 50,5 |
| 84 | 0 | 0 | 0 | 16,7 | 36,2 | 48,4 |
| 86 | 0 | 0 | 0 | 15,6 | 34,6 | 46,5 |
| 88 | 0 | 0 | 0 | 14,4 | 33 | 44,6 |
| 90 | 0 | 0 | 0 | 13,3 | 31,5 | 42,8 |
| 92 | | 0 | 0 | 12,3 | 30 | 41,1 |
| 94 | | 0 | 0 | 11,3 | 28,7 | 39,5 |

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 84 m |
| Jib Length | 66 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|------------|----|-----|-----|------|------|------|
| 78 | 0 | 0 | 0 | 18,6 | 39,8 | 53,1 |
| 80 | 0 | 0 | 0 | 17,2 | 37,9 | 50,8 |
| 82 | 0 | 0 | 0 | 15,9 | 36 | 48,7 |
| 84 | 0 | 0 | 0 | 14,6 | 34,3 | 46,6 |
| 86 | | 0 | 0 | 13,5 | 32,6 | 44,6 |
| 88 | | 0 | 0 | 12,3 | 31 | 42,7 |
| 90 | | 0 | 0 | 11,2 | 29,5 | 41 |
| 92 | | 0 | 0 | 10,2 | 28,1 | 39,2 |
| 94 | | 0 | 0 | 9,2 | 26,7 | 37,6 |
| 96 | | 0 | 0 | 8,3 | 25,4 | 36 |
| 98 | | 0 | 0 | 7,3 | 24,1 | 34,5 |
| 100 | | 0 | 0 | 6,5 | 22,8 | 33,1 |
| 102 | | 0 | 0 | 5,6 | 21,6 | 31,6 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 84 m |
| Jib Length | 72 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|------------|-----|-----|------|------|------|
| 82 | 0 | 0 | 12,9 | 32,6 | 45 |
| 84 | 0 | 0 | 11,7 | 31 | 43 |
| 86 | 0 | 0 | 10,6 | 29,4 | 41,1 |
| 88 | 0 | 0 | 9,5 | 27,9 | 39,3 |
| 90 | 0 | 0 | 8,5 | 26,4 | 37,6 |
| 92 | 0 | 0 | 7,5 | 25,1 | 36 |
| 94 | 0 | 0 | 6,6 | 23,7 | 34,5 |
| 96 | 0 | 0 | 5,7 | 22,5 | 33 |
| 98 | 0 | 0 | 4,9 | 21,3 | 31,5 |
| 100 | 0 | 0 | 4 | 20,1 | 30,2 |
| 102 | 0 | 0 | 3,2 | 19 | 28,9 |
| 104 | 0 | 0 | 2,5 | 17,9 | 27,6 |
| 106 | 0 | 0 | 1,7 | 16,9 | 26,4 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 84 m |
| Jib Length | 78 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|------------|-----|-----|-----|------|------|
| 86 | 0 | 0 | 9,2 | 28 | 39,7 |
| 88 | 0 | 0 | 8,2 | 26,5 | 38 |
| 90 | 0 | 0 | 7,2 | 25,1 | 36,3 |
| 92 | 0 | 0 | 6,2 | 23,7 | 34,7 |
| 94 | 0 | 0 | 5,3 | 22,4 | 33,1 |
| 96 | 0 | 0 | 4,4 | 21,2 | 31,7 |
| 98 | 0 | 0 | 3,6 | 20 | 30,3 |
| 100 | 0 | 0 | 2,8 | 18,9 | 28,9 |
| 102 | 0 | 0 | 2 | 17,8 | 27,6 |
| 104 | 0 | 0 | 1,3 | 16,7 | 26,4 |
| 106 | 0 | 0 | ,6 | 15,7 | 25,2 |
| 108 | 0 | 0 | 0 | 14,7 | 24 |
| 110 | 0 | 0 | 0 | 13,8 | 22,9 |
| 112 | 0 | 0 | 0 | 12,9 | 21,9 |
| 114 | 0 | 0 | 0 | 12 | 20,8 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 84 m |
| Jib Length | 84 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|-----|-----|-----|-----|------|------|
| 90 | 0 | 0 | 5,1 | 23 | 34,2 |
| 92 | 0 | 0 | 4,1 | 21,7 | 32,6 |
| 94 | 0 | 0 | 3,2 | 20,4 | 31,1 |
| 96 | 0 | 0 | 2,3 | 19,1 | 29,6 |
| 98 | 0 | 0 | 1,5 | 18 | 28,2 |
| 100 | 0 | 0 | ,7 | 16,8 | 26,9 |
| 102 | 0 | 0 | 0 | 15,7 | 25,6 |
| 104 | 0 | 0 | 0 | 14,7 | 24,4 |
| 106 | 0 | 0 | 0 | 13,7 | 23,2 |
| 108 | 0 | 0 | 0 | 12,7 | 22 |
| 110 | 0 | 0 | 0 | 11,8 | 20,9 |
| 112 | | 0 | 0 | 10,9 | 19,9 |
| 114 | | 0 | 0 | 10 | 18,8 |
| 116 | | 0 | 0 | 9,2 | 17,9 |
| 118 | | 0 | 0 | 8,4 | 16,9 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 84 m |
| Jib Length | 90 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|-----|-----|-----|-----|------|------|
| 94 | 0 | 0 | 1,7 | 18,8 | 29,6 |
| 96 | 0 | 0 | ,8 | 17,6 | 28,1 |
| 98 | 0 | 0 | 0 | 16,5 | 26,7 |
| 100 | 0 | 0 | 0 | 15,3 | 25,4 |
| 102 | 0 | 0 | 0 | 14,3 | 24,1 |
| 104 | 0 | 0 | 0 | 13,2 | 22,9 |
| 106 | 0 | 0 | 0 | 12,2 | 21,7 |
| 108 | | 0 | 0 | 11,3 | 20,6 |
| 110 | | 0 | 0 | 10,4 | 19,5 |
| 112 | | 0 | 0 | 9,5 | 18,5 |
| 114 | | 0 | 0 | 8,6 | 17,4 |
| 116 | | 0 | 0 | 7,8 | 16,5 |
| 118 | | 0 | 0 | 7 | 15,5 |
| 120 | | 0 | 0 | 6,3 | 14,6 |
| 122 | | 0 | 0 | 5,5 | 13,7 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 84 m |
| Jib Length | 96 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|------------|-----|-----|-----|------|------|
| 98 | 0 | 0 | 0 | 14,5 | 24,8 |
| 100 | 0 | 0 | 0 | 13,4 | 23,5 |
| 102 | 0 | 0 | 0 | 12,3 | 22,2 |
| 104 | | 0 | 0 | 11,3 | 21 |
| 106 | | 0 | 0 | 10,3 | 19,8 |
| 108 | | 0 | 0 | 9,4 | 18,7 |
| 110 | | 0 | 0 | 8,5 | 17,6 |
| 112 | | 0 | 0 | 7,6 | 16,5 |
| 114 | | 0 | 0 | 6,7 | 15,5 |
| 116 | | 0 | 0 | 5,9 | 14,6 |
| 118 | | 0 | 0 | 5,1 | 13,6 |
| 120 | | 0 | 0 | 4,4 | 12,7 |
| 122 | | 0 | 0 | 3,6 | 11,8 |
| 124 | | 0 | 0 | 2,9 | 11 |
| 126 | | 0 | 0 | 2,2 | 10,2 |
| 128 | | 0 | 0 | 1,5 | 9,4 |
| 130 | | 0 | 0 | ,9 | 8,6 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 84 m |
| Jib Length | 102 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 240 | 320 | 400 | 450 |
|-----|-----|-----|------|------|
| 102 | 0 | 0 | 11,7 | 21,6 |
| 104 | 0 | 0 | 10,7 | 20,4 |
| 106 | 0 | 0 | 9,7 | 19,2 |
| 108 | 0 | 0 | 8,8 | 18,1 |
| 110 | 0 | 0 | 7,8 | 17 |
| 112 | 0 | 0 | 7 | 16 |
| 114 | 0 | 0 | 6,1 | 14,9 |
| 116 | 0 | 0 | 5,3 | 14 |
| 118 | 0 | 0 | 4,5 | 13 |
| 120 | 0 | 0 | 3,7 | 12,1 |
| 122 | 0 | 0 | 3 | 11,2 |
| 124 | 0 | 0 | 2,3 | 10,4 |
| 126 | 0 | 0 | 1,6 | 9,6 |
| 128 | 0 | 0 | ,9 | 8,8 |
| 130 | 0 | 0 | ,2 | 8 |
| 132 | 0 | 0 | 0 | 7,2 |
| 134 | 0 | 0 | 0 | 6,5 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 84 m |
| Jib Length | 108 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | | | |
|-----|-----|-----|-----|
| 240 | 320 | 400 | 450 |
|-----|-----|-----|-----|

| | | | | |
|-----|---|---|-----|------|
| 102 | 0 | 0 | 9,1 | 19 |
| 104 | 0 | 0 | 8,1 | 17,8 |
| 106 | 0 | 0 | 7,1 | 16,6 |
| 108 | 0 | 0 | 6,2 | 15,5 |
| 110 | 0 | 0 | 5,2 | 14,4 |
| 112 | 0 | 0 | 4,4 | 13,4 |
| 114 | 0 | 0 | 3,5 | 12,4 |
| 116 | 0 | 0 | 2,8 | 11,4 |
| 118 | 0 | 0 | 2 | 10,5 |
| 120 | 0 | 0 | 1,2 | 9,6 |
| 122 | 0 | 0 | ,5 | 8,7 |
| 124 | 0 | 0 | 0 | 7,9 |
| 126 | 0 | 0 | 0 | 7,1 |
| 128 | 0 | 0 | 0 | 6,3 |
| 130 | | 0 | 0 | 5,5 |
| 132 | | 0 | 0 | 4,8 |
| 134 | | 0 | 0 | 4,1 |
| 136 | | 0 | 0 | 3,4 |
| 138 | | 0 | 0 | 2,7 |
| 140 | | 0 | 0 | 2 |
| 142 | | 0 | 0 | 1,4 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 90 m |
| Jib Length | 30 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

| Superlift Counterweight (t) Radius (m) | 80 | 160 | 240 | 320 | 400 | 450 |
|---|----|-----|------|------|------|------|
| 62 | 0 | 0 | 10,2 | 36,6 | 63 | 79,5 |
| 64 | 0 | 0 | 8,9 | 34,5 | 60 | 76 |
| 66 | 0 | 0 | 7,7 | 32,4 | 57,2 | 72,6 |
| 68 | 0 | 0 | 6,5 | 30,5 | 54,5 | 69,5 |
| 70 | 0 | 0 | 5,3 | 28,6 | 51,9 | 66,5 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 90 m |
| Jib Length | 36 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

| | | | | | | |
|-----------------------------|----|-----|-----|-----|-----|-----|
| Superlift Counterweight (t) | 80 | 160 | 240 | 320 | 400 | 450 |
| Radius (m) | | | | | | |

| | | | | | | |
|-----------|---|---|-----|------|------|------|
| 66 | 0 | 0 | 6,6 | 31,4 | 56,2 | 71,7 |
| 68 | 0 | 0 | 5,5 | 29,5 | 53,6 | 68,6 |
| 70 | 0 | 0 | 4,4 | 27,8 | 51,1 | 65,7 |
| 72 | 0 | 0 | 3,4 | 26,1 | 48,8 | 62,9 |
| 74 | 0 | 0 | 2,5 | 24,5 | 46,5 | 60,3 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 90 m |
| Jib Length | 42 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

| | | | | | | |
|-----------------------------|----|-----|-----|-----|-----|-----|
| Superlift Counterweight (t) | 80 | 160 | 240 | 320 | 400 | 450 |
| Radius (m) | | | | | | |

| | | | | | | |
|-----------|---|---|-----|------|------|------|
| 70 | 0 | 0 | 3 | 26,4 | 49,7 | 64,3 |
| 72 | 0 | 0 | 2 | 24,7 | 47,4 | 61,6 |
| 74 | 0 | 0 | 1,1 | 23,2 | 45,3 | 59 |
| 76 | 0 | 0 | ,3 | 21,8 | 43,2 | 56,6 |
| 78 | 0 | 0 | 0 | 20,4 | 41,3 | 54,3 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 90 m |
| Jib Length | 48 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|----|-----|-----|------|------|------|
| 70 | 0 | 0 | 0 | 23 | 46,4 | 61 |
| 72 | 0 | 0 | 0 | 21,5 | 44,2 | 58,3 |
| 74 | 0 | 0 | 0 | 20 | 42 | 55,8 |
| 76 | 0 | 0 | 0 | 18,6 | 40 | 53,5 |
| 78 | 0 | 0 | 0 | 17,3 | 38,2 | 51,2 |
| 80 | 0 | 0 | 0 | 16 | 36,4 | 49,1 |
| 82 | 0 | 0 | 0 | 14,9 | 34,7 | 47,1 |
| 84 | 0 | 0 | 0 | 13,8 | 33,1 | 45,2 |
| 86 | | 0 | 0 | 12,7 | 31,6 | 43,4 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 90 m |
| Jib Length | 54 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|----|-----|-----|------|------|------|
| 74 | 0 | 0 | 0 | 18,6 | 40,7 | 54,5 |
| 76 | 0 | 0 | 0 | 17,2 | 38,7 | 52,2 |
| 78 | 0 | 0 | 0 | 15,9 | 36,8 | 49,9 |
| 80 | 0 | 0 | 0 | 14,7 | 35,1 | 47,8 |
| 82 | | 0 | 0 | 13,5 | 33,4 | 45,8 |
| 84 | | 0 | 0 | 12,4 | 31,8 | 43,9 |
| 86 | | 0 | 0 | 11,4 | 30,3 | 42,1 |
| 88 | | 0 | 0 | 10,4 | 28,8 | 40,4 |
| 90 | | 0 | 0 | 9,4 | 27,5 | 38,8 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 90 m |
| Jib Length | 60 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|-----------|-----|-----|------|------|------|
| 78 | 0 | 0 | 15,5 | 36,6 | 49,8 |
| 80 | 0 | 0 | 14,2 | 34,8 | 47,6 |
| 82 | 0 | 0 | 13 | 33 | 45,6 |
| 84 | 0 | 0 | 11,9 | 31,4 | 43,6 |
| 86 | 0 | 0 | 10,8 | 29,9 | 41,8 |
| 88 | 0 | 0 | 9,8 | 28,4 | 40 |
| 90 | 0 | 0 | 8,8 | 27 | 38,3 |
| 92 | 0 | 0 | 7,9 | 25,6 | 36,8 |
| 94 | 0 | 0 | 7 | 24,4 | 35,2 |
| 96 | 0 | 0 | 6,2 | 23,1 | 33,8 |
| 98 | 0 | 0 | 5,3 | 21,9 | 32,3 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 90 m |
| Jib Length | 66 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|------------|-----|-----|------|------|------|
| 82 | 0 | 0 | 10,9 | 31,1 | 43,7 |
| 84 | 0 | 0 | 9,8 | 29,5 | 41,7 |
| 86 | 0 | 0 | 8,7 | 27,9 | 39,9 |
| 88 | 0 | 0 | 7,7 | 26,4 | 38,1 |
| 90 | 0 | 0 | 6,7 | 25 | 36,4 |
| 92 | 0 | 0 | 5,8 | 23,7 | 34,8 |
| 94 | 0 | 0 | 4,9 | 22,4 | 33,3 |
| 96 | 0 | 0 | 4 | 21,1 | 31,8 |
| 98 | 0 | 0 | 3,2 | 19,9 | 30,4 |
| 100 | 0 | 0 | 2,4 | 18,8 | 29 |
| 102 | 0 | 0 | 1,6 | 17,7 | 27,7 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 90 m |
| Jib Length | 72 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|------------|-----|-----|-----|------|------|
| 86 | 0 | 0 | 5,9 | 24,7 | 36,4 |
| 88 | 0 | 0 | 4,9 | 23,3 | 34,7 |
| 90 | 0 | 0 | 4 | 21,9 | 33,1 |
| 92 | 0 | 0 | 3,1 | 20,6 | 31,6 |
| 94 | 0 | 0 | 2,3 | 19,4 | 30,1 |
| 96 | 0 | 0 | 1,5 | 18,2 | 28,7 |
| 98 | 0 | 0 | ,7 | 17,1 | 27,4 |
| 100 | 0 | 0 | 0 | 16 | 26,1 |
| 102 | 0 | 0 | 0 | 15 | 24,9 |
| 104 | 0 | 0 | 0 | 14 | 23,7 |
| 106 | 0 | 0 | 0 | 13,1 | 22,5 |
| 108 | 0 | 0 | 0 | 12,1 | 21,4 |
| 110 | | 0 | 0 | 11,2 | 20,4 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 90 m |
| Jib Length | 78 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|------------|-----|-----|-----|------|------|
| 90 | 0 | 0 | 2,6 | 20,5 | 31,7 |
| 92 | 0 | 0 | 1,7 | 19,3 | 30,2 |
| 94 | 0 | 0 | ,9 | 18,1 | 28,8 |
| 96 | 0 | 0 | ,1 | 16,9 | 27,4 |
| 98 | 0 | 0 | 0 | 15,8 | 26,1 |
| 100 | 0 | 0 | 0 | 14,8 | 24,8 |
| 102 | 0 | 0 | 0 | 13,7 | 23,6 |
| 104 | 0 | 0 | 0 | 12,8 | 22,4 |
| 106 | 0 | 0 | 0 | 11,8 | 21,3 |
| 108 | | 0 | 0 | 10,9 | 20,2 |
| 110 | | 0 | 0 | 10,1 | 19,2 |
| 112 | | 0 | 0 | 9,2 | 18,2 |
| 114 | | 0 | 0 | 8,4 | 17,2 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 90 m |
| Jib Length | 84 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|------------|-----|-----|-----|------|------|
| 94 | 0 | 0 | 0 | 16 | 26,7 |
| 96 | 0 | 0 | 0 | 14,8 | 25,3 |
| 98 | 0 | 0 | 0 | 13,7 | 24 |
| 100 | 0 | 0 | 0 | 12,7 | 22,8 |
| 102 | | 0 | 0 | 11,7 | 21,5 |
| 104 | | 0 | 0 | 10,7 | 20,4 |
| 106 | | 0 | 0 | 9,8 | 19,3 |
| 108 | | 0 | 0 | 8,9 | 18,2 |
| 110 | | 0 | 0 | 8 | 17,2 |
| 112 | | 0 | 0 | 7,2 | 16,2 |
| 114 | | 0 | 0 | 6,4 | 15,2 |
| 116 | | 0 | 0 | 5,6 | 14,3 |
| 118 | | 0 | 0 | 4,9 | 13,4 |
| 120 | | 0 | 0 | 4,2 | 12,5 |
| 122 | | 0 | 0 | 3,5 | 11,7 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 90 m |
| Jib Length | 90 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

 Superlift Counterweight (t)
 Radius (m)

| | 240 | 320 | 400 | 450 |
|------------|-----|-----|------|------|
| 94 | 0 | 0 | 14,4 | 25,1 |
| 96 | 0 | 0 | 13,3 | 23,8 |
| 98 | 0 | 0 | 12,2 | 22,5 |
| 100 | 0 | 0 | 11,2 | 21,2 |
| 102 | 0 | 0 | 10,2 | 20 |
| 104 | 0 | 0 | 9,2 | 18,9 |
| 106 | 0 | 0 | 8,3 | 17,8 |
| 108 | 0 | 0 | 7,4 | 16,7 |
| 110 | 0 | 0 | 6,6 | 15,7 |
| 112 | 0 | 0 | 5,8 | 14,7 |
| 114 | 0 | 0 | 5 | 13,8 |
| 116 | 0 | 0 | 4,2 | 12,9 |
| 118 | 0 | 0 | 3,5 | 12 |
| 120 | 0 | 0 | 2,8 | 11,1 |
| 122 | 0 | 0 | 2,1 | 10,3 |
| 124 | 0 | 0 | 1,4 | 9,5 |
| 126 | 0 | 0 | ,8 | 8,7 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 90 m |
| Jib Length | 96 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

 Superlift Counterweight (t)
 Radius (m)

| | | | |
|-----|-----|-----|-----|
| 240 | 320 | 400 | 450 |
|-----|-----|-----|-----|

| | | | | |
|------------|---|---|------|------|
| 98 | 0 | 0 | 10,2 | 20,5 |
| 100 | 0 | 0 | 9,2 | 19,3 |
| 102 | 0 | 0 | 8,2 | 18,1 |
| 104 | 0 | 0 | 7,3 | 16,9 |
| 106 | 0 | 0 | 6,3 | 15,8 |
| 108 | 0 | 0 | 5,5 | 14,8 |
| 110 | 0 | 0 | 4,6 | 13,8 |
| 112 | 0 | 0 | 3,8 | 12,8 |
| 114 | 0 | 0 | 3 | 11,9 |
| 116 | 0 | 0 | 2,3 | 10,9 |
| 118 | 0 | 0 | 1,5 | 10,1 |
| 120 | 0 | 0 | ,9 | 9,2 |
| 122 | 0 | 0 | ,2 | 8,4 |
| 124 | 0 | 0 | 0 | 7,6 |
| 126 | 0 | 0 | 0 | 6,8 |
| 128 | 0 | 0 | 0 | 6,1 |
| 130 | | 0 | 0 | 5,3 |
| 132 | | 0 | 0 | 4,6 |
| 134 | | 0 | 0 | 4 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 90 m |
| Jib Length | 102 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 240 | 320 | 400 | 450 |
|-----|-----|-----|-----|------|
| 102 | 0 | 0 | 7,6 | 17,5 |
| 104 | 0 | 0 | 6,7 | 16,4 |
| 106 | 0 | 0 | 5,7 | 15,3 |
| 108 | 0 | 0 | 4,9 | 14,2 |
| 110 | 0 | 0 | 4 | 13,2 |
| 112 | 0 | 0 | 3,2 | 12,2 |
| 114 | 0 | 0 | 2,4 | 11,3 |
| 116 | 0 | 0 | 1,7 | 10,4 |
| 118 | 0 | 0 | ,9 | 9,5 |
| 120 | 0 | 0 | ,2 | 8,6 |
| 122 | 0 | 0 | 0 | 7,8 |
| 124 | 0 | 0 | 0 | 7 |
| 126 | 0 | 0 | 0 | 6,2 |
| 128 | | 0 | 0 | 5,5 |
| 130 | | 0 | 0 | 4,7 |
| 132 | | 0 | 0 | 4 |
| 134 | | 0 | 0 | 3,3 |
| 136 | | 0 | 0 | 2,7 |
| 138 | | 0 | 0 | 2 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 90 m |
| Jib Length | 108 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

 Superlift Counterweight (t)
 Radius (m)

| | | | |
|-----|-----|-----|-----|
| 240 | 320 | 400 | 450 |
|-----|-----|-----|-----|

| | | | | |
|-----|---|---|-----|------|
| 106 | 0 | 0 | 3 | 12,6 |
| 108 | 0 | 0 | 2,2 | 11,5 |
| 110 | 0 | 0 | 1,4 | 10,5 |
| 112 | 0 | 0 | ,6 | 9,6 |
| 114 | 0 | 0 | 0 | 8,6 |
| 116 | 0 | 0 | 0 | 7,7 |
| 118 | 0 | 0 | 0 | 6,9 |
| 120 | 0 | 0 | 0 | 6 |
| 122 | | 0 | 0 | 5,2 |
| 124 | | 0 | 0 | 4,4 |
| 126 | | 0 | 0 | 3,7 |
| 128 | | 0 | 0 | 3 |
| 130 | | 0 | 0 | 2,2 |
| 132 | | 0 | 0 | 1,5 |
| 134 | | 0 | 0 | ,9 |
| 136 | | 0 | 0 | ,2 |
| 138 | | 0 | 0 | 0 |
| 140 | | 0 | 0 | 0 |
| 142 | | 0 | 0 | 0 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 96 m |
| Jib Length | 30 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

| Superlift Counterweight (t) Radius (m) | 80 | 160 | 240 | 320 | 400 | 450 |
|---|----|-----|-----|------|------|------|
| 62 | 0 | 0 | 3,2 | 29,6 | 56 | 72,5 |
| 64 | 0 | 0 | 2 | 27,6 | 53,2 | 69,2 |
| 66 | 0 | 0 | 1 | 25,8 | 50,5 | 66 |
| 68 | 0 | 0 | ,1 | 24 | 48 | 63 |
| 70 | 0 | 0 | 0 | 22,4 | 45,7 | 60,2 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 96 m |
| Jib Length | 36 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|----|-----|-----|------|------|------|
| 66 | 0 | 0 | 0 | 24,7 | 49,6 | 65,1 |
| 68 | 0 | 0 | 0 | 23 | 47,1 | 62,2 |
| 70 | 0 | 0 | 0 | 21,5 | 44,8 | 59,4 |
| 72 | 0 | 0 | 0 | 20 | 42,7 | 56,8 |
| 74 | 0 | 0 | 0 | 18,6 | 40,6 | 54,4 |
| 76 | 0 | 0 | 0 | 17,2 | 38,7 | 52,1 |
| 78 | 0 | 0 | 0 | 15,9 | 36,8 | 49,9 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 96 m |
| Jib Length | 42 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 80 | 160 | 240 | 320 | 400 | 450 |
|-----------|----|-----|-----|------|------|------|
| 70 | 0 | 0 | 0 | 20 | 43,4 | 58 |
| 72 | 0 | 0 | 0 | 18,6 | 41,3 | 55,5 |
| 74 | 0 | 0 | 0 | 17,2 | 39,3 | 53,1 |
| 76 | 0 | 0 | 0 | 15,9 | 37,4 | 50,8 |
| 78 | 0 | 0 | 0 | 14,7 | 35,6 | 48,6 |
| 80 | | 0 | 0 | 13,5 | 33,9 | 46,6 |
| 82 | | 0 | 0 | 12,4 | 32,3 | 44,7 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 96 m |
| Jib Length | 48 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

 Superlift Counterweight (t)
 Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|-----------|-----|-----|------|------|------|
| 74 | 0 | 0 | 13,9 | 36 | 49,7 |
| 76 | 0 | 0 | 12,6 | 34,1 | 47,5 |
| 78 | 0 | 0 | 11,5 | 32,3 | 45,4 |
| 80 | 0 | 0 | 10,4 | 30,7 | 43,4 |
| 82 | 0 | 0 | 9,3 | 29,1 | 41,5 |
| 84 | 0 | 0 | 8,3 | 27,7 | 39,8 |
| 86 | 0 | 0 | 7,4 | 26,3 | 38,1 |
| 88 | 0 | 0 | 6,5 | 25 | 36,5 |
| 90 | 0 | 0 | 5,7 | 23,7 | 35 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 96 m |
| Jib Length | 54 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|-----------|-----|-----|------|------|------|
| 78 | 0 | 0 | 10,1 | 31,1 | 44,2 |
| 80 | 0 | 0 | 9 | 29,4 | 42,2 |
| 82 | 0 | 0 | 8 | 27,9 | 40,3 |
| 84 | 0 | 0 | 7 | 26,4 | 38,5 |
| 86 | 0 | 0 | 6,1 | 25 | 36,8 |
| 88 | 0 | 0 | 5,2 | 23,6 | 35,2 |
| 90 | 0 | 0 | 4,3 | 22,4 | 33,7 |
| 92 | 0 | 0 | 3,5 | 21,2 | 32,2 |
| 94 | 0 | 0 | 2,8 | 20,1 | 30,8 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 96 m |
| Jib Length | 60 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

 Superlift Counterweight (t)
 Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|-----------|-----|-----|-----|------|------|
| 82 | 0 | 0 | 7,5 | 27,6 | 40,1 |
| 84 | 0 | 0 | 6,5 | 26,1 | 38,3 |
| 86 | 0 | 0 | 5,6 | 24,6 | 36,5 |
| 88 | 0 | 0 | 4,7 | 23,3 | 34,9 |
| 90 | 0 | 0 | 3,8 | 22 | 33,3 |
| 92 | 0 | 0 | 3 | 20,8 | 31,9 |
| 94 | 0 | 0 | 2,2 | 19,6 | 30,4 |
| 96 | 0 | 0 | 1,5 | 18,4 | 29,1 |
| 98 | 0 | 0 | ,7 | 17,4 | 27,8 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

| |
|-------------------|
| SWSL-PLMIN |
|-------------------|

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 96 m |
| Jib Length | 66 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|------------|-----|-----|-----|------|------|
| 86 | 0 | 0 | 3,5 | 22,6 | 34,6 |
| 88 | 0 | 0 | 2,6 | 21,3 | 33 |
| 90 | 0 | 0 | 1,7 | 20 | 31,4 |
| 92 | 0 | 0 | ,9 | 18,8 | 29,9 |
| 94 | 0 | 0 | ,1 | 17,6 | 28,5 |
| 96 | 0 | 0 | 0 | 16,4 | 27,1 |
| 98 | 0 | 0 | 0 | 15,3 | 25,8 |
| 100 | 0 | 0 | 0 | 14,3 | 24,5 |
| 102 | 0 | 0 | 0 | 13,3 | 23,3 |
| 104 | 0 | 0 | 0 | 12,3 | 22,1 |
| 106 | | 0 | 0 | 11,4 | 21 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 96 m |
| Jib Length | 72 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|------------|-----|-----|-----|------|------|
| 90 | 0 | 0 | 0 | 16,9 | 28,1 |
| 92 | 0 | 0 | 0 | 15,8 | 26,7 |
| 94 | 0 | 0 | 0 | 14,6 | 25,4 |
| 96 | 0 | 0 | 0 | 13,6 | 24 |
| 98 | 0 | 0 | 0 | 12,5 | 22,8 |
| 100 | | 0 | 0 | 11,5 | 21,6 |
| 102 | | 0 | 0 | 10,6 | 20,5 |
| 104 | | 0 | 0 | 9,7 | 19,3 |
| 106 | | 0 | 0 | 8,8 | 18,3 |
| 108 | | 0 | 0 | 8 | 17,3 |
| 110 | | 0 | 0 | 7,1 | 16,3 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 96 m |
| Jib Length | 78 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 160 | 240 | 320 | 400 | 450 |
|------------|-----|-----|-----|------|------|
| 90 | 0 | 0 | 0 | 15,5 | 26,7 |
| 92 | 0 | 0 | 0 | 14,3 | 25,3 |
| 94 | 0 | 0 | 0 | 13,2 | 23,9 |
| 96 | | 0 | 0 | 12,2 | 22,6 |
| 98 | | 0 | 0 | 11,2 | 21,4 |
| 100 | | 0 | 0 | 10,2 | 20,2 |
| 102 | | 0 | 0 | 9,3 | 19,1 |
| 104 | | 0 | 0 | 8,4 | 18 |
| 106 | | 0 | 0 | 7,5 | 17 |
| 108 | | 0 | 0 | 6,7 | 16 |
| 110 | | 0 | 0 | 5,9 | 15 |
| 112 | | 0 | 0 | 5,1 | 14,1 |
| 114 | | 0 | 0 | 4,4 | 13,2 |
| 116 | | 0 | 0 | 3,7 | 12,3 |
| 118 | | 0 | 0 | 3 | 11,5 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 96 m |
| Jib Length | 84 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 240 | 320 | 400 | 450 |
|------------|-----|-----|------|------|
| 94 | 0 | 0 | 11,1 | 21,8 |
| 96 | 0 | 0 | 10,1 | 20,5 |
| 98 | 0 | 0 | 9,1 | 19,3 |
| 100 | 0 | 0 | 8,1 | 18,2 |
| 102 | 0 | 0 | 7,2 | 17 |
| 104 | 0 | 0 | 6,3 | 16 |
| 106 | 0 | 0 | 5,4 | 14,9 |
| 108 | 0 | 0 | 4,6 | 13,9 |
| 110 | 0 | 0 | 3,8 | 13 |
| 112 | 0 | 0 | 3,1 | 12,1 |
| 114 | 0 | 0 | 2,4 | 11,2 |
| 116 | 0 | 0 | 1,7 | 10,3 |
| 118 | 0 | 0 | 1 | 9,5 |
| 120 | 0 | 0 | ,3 | 8,7 |
| 122 | 0 | 0 | 0 | 7,9 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 96 m |
| Jib Length | 90 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 240 | 320 | 400 | 450 |
|-----|-----|-----|-----|------|
| 98 | 0 | 0 | 7,5 | 17,8 |
| 100 | 0 | 0 | 6,5 | 16,6 |
| 102 | 0 | 0 | 5,6 | 15,5 |
| 104 | 0 | 0 | 4,8 | 14,4 |
| 106 | 0 | 0 | 3,9 | 13,4 |
| 108 | 0 | 0 | 3,1 | 12,4 |
| 110 | 0 | 0 | 2,3 | 11,5 |
| 112 | 0 | 0 | 1,6 | 10,6 |
| 114 | 0 | 0 | ,9 | 9,7 |
| 116 | 0 | 0 | ,2 | 8,9 |
| 118 | 0 | 0 | 0 | 8 |
| 120 | 0 | 0 | 0 | 7,2 |
| 122 | 0 | 0 | 0 | 6,5 |
| 124 | | 0 | 0 | 5,8 |
| 126 | | 0 | 0 | 5,1 |
| 128 | | 0 | 0 | 4,4 |
| 130 | | 0 | 0 | 3,7 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 96 m |
| Jib Length | 96 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 240 | 320 | 400 | 450 |
|-----|-----|-----|-----|------|
| 102 | 0 | 0 | 3,7 | 13,5 |
| 104 | 0 | 0 | 2,8 | 12,5 |
| 106 | 0 | 0 | 2 | 11,5 |
| 108 | 0 | 0 | 1,2 | 10,5 |
| 110 | 0 | 0 | ,4 | 9,5 |
| 112 | 0 | 0 | 0 | 8,6 |
| 114 | 0 | 0 | 0 | 7,8 |
| 116 | 0 | 0 | 0 | 6,9 |
| 118 | 0 | 0 | 0 | 6,1 |
| 120 | | 0 | 0 | 5,3 |
| 122 | | 0 | 0 | 4,6 |
| 124 | | 0 | 0 | 3,8 |
| 126 | | 0 | 0 | 3,1 |
| 128 | | 0 | 0 | 2,4 |
| 130 | | 0 | 0 | 1,8 |
| 132 | | 0 | 0 | 1,1 |
| 134 | | 0 | 0 | ,5 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 96 m |
| Jib Length | 102 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

Superlift Counterweight (t)
Radius (m)

| | 240 | 320 | 400 | 450 |
|-----|-----|-----|-----|------|
| 106 | 0 | 0 | 1,3 | 10,9 |
| 108 | 0 | 0 | ,6 | 9,9 |
| 110 | 0 | 0 | 0 | 8,9 |
| 112 | 0 | 0 | 0 | 8,1 |
| 114 | 0 | 0 | 0 | 7,2 |
| 116 | 0 | 0 | 0 | 6,3 |
| 118 | | 0 | 0 | 5,5 |
| 120 | | 0 | 0 | 4,7 |
| 122 | | 0 | 0 | 4 |
| 124 | | 0 | 0 | 3,2 |
| 126 | | 0 | 0 | 2,5 |
| 128 | | 0 | 0 | 1,8 |
| 130 | | 0 | 0 | 1,2 |
| 132 | | 0 | 0 | ,5 |
| 134 | | 0 | 0 | 0 |
| 136 | | 0 | 0 | 0 |
| 138 | | 0 | 0 | 0 |
| 140 | | 0 | 0 | 0 |
| 142 | | 0 | 0 | 0 |

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

| | |
|-------------------------|---------|
| Slew Range | 0-360 ° |
| Main Boom Length | 96 m |
| Jib Length | 108 m |
| SL-Mast Length | 40,5 m |
| Angle Main Boom | 65 ° |
| Track Width | 9,6 m |
| Counterweight | 250 t |
| Central Ballast | 80 t |
| SL-Mast Radius | 18,5 m |
| Superlift Radius | 18 m |

 Superlift Counterweight (t)
 Radius (m)

| | | |
|-----|-----|-----|
| 320 | 400 | 450 |
|-----|-----|-----|

| | | | |
|-----|---|---|-----|
| 110 | 0 | 0 | 6,2 |
| 112 | 0 | 0 | 5,4 |
| 114 | 0 | 0 | 4,5 |
| 116 | 0 | 0 | 3,7 |
| 118 | 0 | 0 | 2,9 |
| 120 | 0 | 0 | 2,1 |
| 122 | 0 | 0 | 1,4 |
| 124 | 0 | 0 | ,6 |
| 126 | 0 | 0 | 0 |
| 128 | 0 | 0 | 0 |
| 130 | 0 | 0 | 0 |
| 132 | 0 | 0 | 0 |
| 134 | 0 | 0 | 0 |
| 136 | 0 | 0 | 0 |
| 138 | 0 | 0 | 0 |
| 140 | 0 | 0 | 0 |
| 142 | 0 | 0 | 0 |
| 144 | | 0 | 0 |
| 146 | | 0 | 0 |

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!