

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	30 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

64	97
65	95
66	93,1

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	48 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
78	0	0	13,8	34,5	55,3	68,3
80	0	0	12,7	33	53,2	65,8
82	0	0	11,8	31,5	51,2	63,5

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
90	0	0	4,9	22,9	41	52,3
92	0	0	4,1	21,7	39,4	50,4
94	0	0	3,3	20,6	37,8	48,6

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
94	0	,7	18,1	35,5	46,3
96	0	0	17	34	44,6
98	0	0	15,9	32,5	42,9

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					

98	0	0	13,3	29,7	39,9
100	0	0	12,4	28,4	38,3
102	0	0	11,4	27,1	36,9
104	0	0	10,5	25,9	35,5
106	0	0	9,6	24,7	34,1

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	160	240	320	400	450
102	0	0	10,2	25,9	35,7
104	0	0	9,4	24,7	34,3
106	0	0	8,5	23,6	33
108	0	0	7,7	22,5	31,7
110	0	0	6,9	21,4	30,5

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	160	240	320	400	450
110	0	0	4,7	19,2	28,3
112	0	0	4	18,2	27,1
114	0	0	3,2	17,2	26
116	0	0	2,5	16,3	24,9
118	0	0	1,9	15,4	23,8

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
114	0	1,9	15,9	24,6
116	0	1,2	14,9	23,5
118	0	,5	14,1	22,5
120	0	0	13,2	21,5
122	0	0	12,4	20,5

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
118	0	0	11,9	20,4
120	0	0	11,1	19,4
122	0	0	10,2	18,4
124	0	0	9,4	17,5
126	0	0	8,6	16,6
128	0	0	7,9	15,7
130	0	0	7,1	14,8

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
122	0	0	9,4	17,6
124	0	0	8,6	16,7
126	0	0	7,8	15,8
128	0	0	7,1	14,9
130	0	0	6,3	14
132	0	0	5,6	13,1
134	0	0	4,9	12,3

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	48 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

 Superlift Counterweight (t)
 Radius (m)

	240	320	400	450
130	0	0	3,9	11,6
132	0	0	3,2	10,8
134	0	0	2,5	9,9
136	0	0	1,8	9,2
138		0	1,2	8,4

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
78	0	0	10,6	31,4	52,2	65,2
80	0	0	9,7	29,9	50,2	62,8
82	0	0	8,7	28,5	48,2	60,5

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	48 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
82	0	0	5,7	25,5	45,2	57,5
84	0	0	4,9	24,2	43,4	55,5
86	0	0	4,2	23	41,8	53,5

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
94	0	0	15,3	32,6	43,4
96	0	0	14,3	31,2	41,8
98	0	0	13,4	29,9	40,3

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
98	0	0	10,9	27,5	37,9
100	0	0	9,9	26,2	36,4
102	0	0	9	25	35

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	160	240	320	400	450
102	0	0	6,5	22,2	32
104	0	0	5,7	21,1	30,7
106	0	0	4,9	20	29,5
108	0	0	4,2	19	28,2
110	0	0	3,5	18	27,1

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
110	0	2,3	16,8	25,9
112	0	1,6	15,9	24,8
114	0	1	15	23,7

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
--	-----	-----	-----	-----

114	0	0	12,7	21,5
116	0	0	11,9	20,5
118	0	0	11	19,5
120	0	0	10,2	18,5
122	0	0	9,4	17,6

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
118	0	0	9,6	18,1
120	0	0	8,8	17,1
122	0	0	8,1	16,2
124	0	0	7,3	15,4
126	0	0	6,6	14,5

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
122	0	0	5,9	14,1
124	0	0	5,2	13,2
126	0	0	4,5	12,4
128	0	0	3,8	11,6
130	0	0	3,1	10,8
132	0	0	2,4	10
134	0	0	1,8	9,2

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
126	0	0	3,6	11,6
128	0	0	2,9	10,7
130	0	0	2,2	9,9
132	0	0	1,6	9,2
134		0	,9	8,4
136		0	,3	7,7
138		0	0	6,9

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	54 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

 Superlift Counterweight (t)
 Radius (m)

	320	400	450
--	-----	-----	-----

134	0	0	5,9
136	0	0	5,2
138	0	0	4,5
140	0	0	3,8
142	0	0	3,2

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
82	0	2,2	21,9	41,7	54
84	0	1,5	20,7	40	52
86	0	,8	19,6	38,4	50,1

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	48 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
86	0	0	16,5	35,3	47
88	0	0	15,5	33,8	45,3
90	0	0	14,5	32,5	43,7

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
94	0	0	10,9	28,1	38,8
96	0	0	10,1	26,9	37,4
98	0	0	9,3	25,8	36

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
98	0	0	7,7	24,3	34,6
100	0	0	6,9	23,1	33,3
102	0	0	6,2	22	32

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
102	0	0	3,6	19,5	29,5
104	0	0	2,8	18,5	28,3
106	0	0	2,1	17,5	27

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
106	0	0	14,7	24,2
108	0	0	13,8	23,1
110	0	0	12,9	22
112	0	0	12,1	21
114	0	0	11,2	20

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
114	0	0	10	18,7
116	0	0	9,2	17,8
118	0	0	8,4	16,9

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
118	0	0	6,2	14,6
120	0	0	5,4	13,7
122	0	0	4,7	12,9
124	0	0	4	12,1
126	0	0	3,4	11,3

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
122	0	0	3,3	11,5
124	0	0	2,6	10,7
126	0	0	2	9,9
128	0	0	1,4	9,1
130		0	,8	8,4

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

320	400	450
-----	-----	-----

126	0	0	7,7
128	0	0	7
130	0	0	6,2
132	0	0	5,5
134	0	0	4,9
136	0	0	4,2
138	0	0	3,5

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

320	400	450
-----	-----	-----

130	0	0	5,4
132	0	0	4,7
134	0	0	4
136	0	0	3,3
138	0	0	2,7
140	0	0	2
142	0	0	1,4

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	60 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

320	400	450
-----	-----	-----

138	0	0	,2
140	0	0	0
142	0	0	0
144	0	0	0
146	0	0	0
148	0	0	0
150		0	0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
86	0	0	13,6	32,4	44,2
88	0	0	12,6	31	42,5
90	0	0	11,7	29,7	40,9

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	48 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
90	0	0	8,6	26,5	37,7
92	0	0	7,8	25,3	36,3
94	0	0	7	24,2	34,9

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
98	0	0	3,8	20,2	30,5
100	0	0	3,1	19,2	29,3
102	0	0	2,5	18,3	28,2

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
102	0	,9	16,8	26,8
104	0	,3	15,9	25,6
106	0	0	14,9	24,5

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)				
106	0	0	12,4	22
108	0	0	11,5	20,9
110	0	0	10,7	19,9

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
110	0	0	8	17,1
112	0	0	7,2	16,1
114	0	0	6,5	15,2
116	0	0	5,8	14,4
118	0	0	5,1	13,5

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
118	0	0	3,8	12,2
120	0	0	3,1	11,4
122	0	0	2,5	10,7

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

122	0	,2	8,4
124	0	0	7,6
126	0	0	6,9
128	0	0	6,2
130	0	0	5,5

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

126	0	0	5,4
128	0	0	4,8
130	0	0	4,1
132	0	0	3,5
134	0	0	2,8

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
 "Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

320	400	450
-----	-----	-----

130	0	0	1,9
132	0	0	1,2
134	0	0	,6
136	0	0	0
138	0	0	0
140	0	0	0
142	0	0	0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

 Superlift Counterweight (t)
 Radius (m)

320	400	450
-----	-----	-----

138	0	0	0
140	0	0	0
142	0	0	0
144	0	0	0
146		0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	66 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	400	450
Radius (m)		

142	0	0
144	0	0
146	0	0
148	0	0
150	0	0
154	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
90	0	0	5,1	23	34,2
92	0	0	4,3	21,9	32,9
94	0	0	3,7	20,8	31,5

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	102	104	106	
	0	0	0	
	12,2	11,4	10,6	
	22	21,1	20,1	

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)				
106	0	0	9,1	18,7
108	0	0	8,4	17,7
110	0	0	7,6	16,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	240	320	400	450
110	0	0	5	14,3
112	0	0	4,3	13,4
114	0	0	3,6	12,5
116	0	0	2,9	11,7
118	0	0	2,2	10,8

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

114	0	1	9,8
116	0	,4	9
118	0	0	8,2
120	0	0	7,5
122	0	0	6,8

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
 "Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	320	400	450	
Radius (m)	122	124	126	
	0	0	0	
	5,5	4,8	4,2	

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

126	0	0	1,8
128	0	0	1,2
130	0	0	,6
132	0	0	,1
134	0	0	0

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)			

130	0	0	0
132	0	0	0
134	0	0	0
136	0	0	0
138	0	0	0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	400	450	
Radius (m)			

134	0	0	
136	0	0	
138	0	0	
140	0	0	
142	0	0	
144	0	0	
146	0	0	

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	400	450	
Radius (m)			

142	0	0	
144	0	0	
146	0	0	
148	0	0	
150	0	0	

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	72 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	400	450
Radius (m)		

146	0	0
148	0	0
150	0	0
154	0	0
158	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)				
94	0	0	14,5	25,3
96	0	0	13,6	24,1
98	0	0	12,8	23,1

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	106	108	110	
	0	0	0	0
	4,8	4,2	3,6	14,3
	13,5	12,7		

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)				
110	0	0	2,1	11,3
112	0	0	1,5	10,5
114	0	0	,9	9,8

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)			

114	0	0	7,2
116	0	0	6,5
118	0	0	5,7
120	0	0	5
122	0	0	4,3

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)	122	124	126
	0	0	0
	1,8	1,2	,6

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)			
126	0	0	0
128	0	0	0
130	0	0	0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	400	450	
Radius (m)			

130	0	0	
132	0	0	
134	0	0	
136	0	0	
138	0	0	

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

400	450
-----	-----

134	0	0
136	0	0
138	0	0
140	0	0
142	0	0

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	400	450
Radius (m)		

138	0	0
140	0	0
142	0	0
144	0	0
146	0	0
148	0	0
150	0	0

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	400	450
Radius (m)		

146	0	0
148	0	0
150	0	0
154		0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	78 m
Jib Length	108 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

 Superlift Counterweight (t)
 Radius (m)

150	0
154	0
158	0
162	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)				
98	0	0	6	16,3
100	0	0	5,3	15,4
102	0	0	4,6	14,5

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)			
110	0	0	6,5
112	0	0	5,8
114	0	0	5,2

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
114	0	0	3,8
116	0	0	3,2
118	0	0	2,6

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

	320	400	450
--	-----	-----	-----

118	0	0	0
120	0	0	0
122	0	0	0
124	0	0	0
126	0	0	0

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	400	450	
Radius (m)			

126	0	0	
128	0	0	
130	0	0	

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	400	450
Radius (m)		

130	0	0
132	0	0
134	0	0
136	0	0
138	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

400	450
-----	-----

134	0	0
136	0	0
138	0	0
140	0	0
142	0	0

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	400	450
Radius (m)		

138	0	0
140	0	0
142	0	0
144	0	0
146	0	0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	96 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

142	0
144	0
146	0
148	0
150	0
154	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	84 m
Jib Length	102 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

150	0
154	0
158	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	42 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

320	400	450
-----	-----	-----

102	0	0	8,1
104	0	0	7,4
106	0	0	6,7

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)			
114	0	0	0
116	0	0	0
118	0	0	0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)			
118	0	0	0
120	0	0	0
122	0	0	0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"
Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	400	450	
Radius (m)			

122	0	0	
124	0	0	
126	0	0	
128	0	0	
130	0	0	

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	400	450
Radius (m)		

130	0	0
132	0	0
134	0	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN

"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	400	450
Radius (m)		

134	0	0
136	0	0
138	0	0
140	0	0
142	0	0

() PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	84 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

138	0
140	0
142	0
144	0
146	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	90 m
Jib Length	90 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

142	0
144	0
146	0
148	0
150	0
154	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	36 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)	102	104	106
	0	0	0
	2,8	2,2	1,6

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	54 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	400	450	
Radius (m)			

118	0	0	
120	0	0	
122	0	0	

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	60 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	400	450	
Radius (m)			

122	0	0	
124	0	0	
126	0	0	

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	66 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)	400	450	
Radius (m)			

126	0	0	
128	0	0	
130	0	0	
132	0	0	
134	0	0	

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	72 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
 Radius (m)

134	0
136	0
138	0

() PLMIN-loads are greater than max. perm. capacities
 Attention: This is no Capacity Chart!!!

CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

SWSL-PLMIN
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

Slew Range	0-360 °
Main Boom Length	96 m
Jib Length	78 m
SL-Mast Length	40,5 m
Angle Main Boom	45 °
Track Width	9,6 m
Counterweight	170 t
Central Ballast	0 t
SL-Mast Radius	18,5 m
Superlift Radius	18 m

Superlift Counterweight (t)
Radius (m)

138	0
140	0
142	0
144	0
146	0

() PLMIN-loads are greater than max. perm. capacities
Attention: This is no Capacity Chart!!!