

# CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	48 m
<b>Jib Length</b>	30 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)   
Radius (m)

64	97
65	95
66	93,1

( ) PLMIN-loads are greater than max. perm. capacities  
Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	48 m
<b>Jib Length</b>	48 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
<b>78</b>	0	0	13,8	34,5	55,3	68,3
<b>80</b>	0	0	12,7	33	53,2	65,8
<b>82</b>	0	0	11,8	31,5	51,2	63,5

( ) PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	48 m
<b>Jib Length</b>	60 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
<b>90</b>	0	0	4,9	22,9	41	52,3
<b>92</b>	0	0	4,1	21,7	39,4	50,4
<b>94</b>	0	0	3,3	20,6	37,8	48,6

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	48 m
<b>Jib Length</b>	66 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
<b>94</b>	0	0	,7	18,1	35,5	46,3
<b>96</b>	0	0	0	17	34	44,6
<b>98</b>	0	0	0	15,9	32,5	42,9

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**
**"Standard-Vario-SL"**
**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	48 m
<b>Jib Length</b>	72 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					

<b>98</b>	0	0	13,3	29,7	39,9
<b>100</b>	0	0	12,4	28,4	38,3
<b>102</b>	0	0	11,4	27,1	36,9
<b>104</b>	0	0	10,5	25,9	35,5
<b>106</b>	0	0	9,6	24,7	34,1

**() PLMIN-loads are greater than max. perm. capacities**
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	48 m
<b>Jib Length</b>	78 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					

<b>102</b>	0	0	10,2	25,9	35,7
<b>104</b>	0	0	9,4	24,7	34,3
<b>106</b>	0	0	8,5	23,6	33
<b>108</b>	0	0	7,7	22,5	31,7
<b>110</b>	0	0	6,9	21,4	30,5

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	48 m
<b>Jib Length</b>	84 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	160	240	320	400	450
<b>110</b>	0	0	4,7	19,2	28,3
<b>112</b>	0	0	4	18,2	27,1
<b>114</b>	0	0	3,2	17,2	26
<b>116</b>	0	0	2,5	16,3	24,9
<b>118</b>	0	0	1,9	15,4	23,8

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	48 m
<b>Jib Length</b>	90 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					

<b>114</b>	0	0	1,9	15,9	24,6
<b>116</b>	0	0	1,2	14,9	23,5
<b>118</b>	0	0	,5	14,1	22,5
<b>120</b>	0	0	0	13,2	21,5
<b>122</b>	0	0	0	12,4	20,5

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**



**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	48 m
<b>Jib Length</b>	96 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	240	320	400	450
<b>118</b>	0	0	11,9	20,4
<b>120</b>	0	0	11,1	19,4
<b>122</b>	0	0	10,2	18,4
<b>124</b>	0	0	9,4	17,5
<b>126</b>	0	0	8,6	16,6
<b>128</b>	0	0	7,9	15,7
<b>130</b>	0	0	7,1	14,8

( ) PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	48 m
<b>Jib Length</b>	102 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	240	320	400	450
<b>122</b>	0	0	9,4	17,6
<b>124</b>	0	0	8,6	16,7
<b>126</b>	0	0	7,8	15,8
<b>128</b>	0	0	7,1	14,9
<b>130</b>	0	0	6,3	14
<b>132</b>	0	0	5,6	13,1
<b>134</b>	0	0	4,9	12,3

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	48 m
<b>Jib Length</b>	108 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	240	320	400	450
<b>130</b>	0	0	3,9	11,6
<b>132</b>	0	0	3,2	10,8
<b>134</b>	0	0	2,5	9,9
<b>136</b>	0	0	1,8	9,2
<b>138</b>	0	0	1,2	8,4

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	54 m
<b>Jib Length</b>	42 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
<b>78</b>	0	0	10,6	31,4	52,2	65,2
<b>80</b>	0	0	9,7	29,9	50,2	62,8
<b>82</b>	0	0	8,7	28,5	48,2	60,5

( ) PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	54 m
<b>Jib Length</b>	48 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
<b>82</b>	0	0	5,7	25,5	45,2	57,5
<b>84</b>	0	0	4,9	24,2	43,4	55,5
<b>86</b>	0	0	4,2	23	41,8	53,5

() PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	54 m
<b>Jib Length</b>	60 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
<b>94</b>	0	0	0	15,3	32,6	43,4
<b>96</b>	0	0	0	14,3	31,2	41,8
<b>98</b>	0	0	0	13,4	29,9	40,3

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	54 m
<b>Jib Length</b>	66 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
<b>98</b>	0	0	10,9	27,5	37,9
<b>100</b>	0	0	9,9	26,2	36,4
<b>102</b>	0	0	9	25	35

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**
**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	54 m
<b>Jib Length</b>	72 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					

<b>102</b>	0	0	6,5	22,2	32
<b>104</b>	0	0	5,7	21,1	30,7
<b>106</b>	0	0	4,9	20	29,5
<b>108</b>	0	0	4,2	19	28,2
<b>110</b>	0	0	3,5	18	27,1

( ) PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!



**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	54 m
<b>Jib Length</b>	78 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
<b>110</b>	0	0	2,3	16,8	25,9
<b>112</b>	0	0	1,6	15,9	24,8
<b>114</b>	0	0	1	15	23,7

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	54 m
<b>Jib Length</b>	84 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	160	240	320	400	450
<b>114</b>	0	0	0	12,7	21,5
<b>116</b>	0	0	0	11,9	20,5
<b>118</b>		0	0	11	19,5
<b>120</b>		0	0	10,2	18,5
<b>122</b>		0	0	9,4	17,6

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	54 m
<b>Jib Length</b>	90 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	240	320	400	450
<b>118</b>	0	0	9,6	18,1
<b>120</b>	0	0	8,8	17,1
<b>122</b>	0	0	8,1	16,2
<b>124</b>	0	0	7,3	15,4
<b>126</b>	0	0	6,6	14,5

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	54 m
<b>Jib Length</b>	96 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	240	320	400	450
<b>122</b>	0	0	5,9	14,1
<b>124</b>	0	0	5,2	13,2
<b>126</b>	0	0	4,5	12,4
<b>128</b>	0	0	3,8	11,6
<b>130</b>	0	0	3,1	10,8
<b>132</b>	0	0	2,4	10
<b>134</b>	0	0	1,8	9,2

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	54 m
<b>Jib Length</b>	102 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	240	320	400	450
<b>126</b>	0	0	3,6	11,6
<b>128</b>	0	0	2,9	10,7
<b>130</b>	0	0	2,2	9,9
<b>132</b>	0	0	1,6	9,2
<b>134</b>	0	0	,9	8,4
<b>136</b>	0	0	,3	7,7
<b>138</b>	0	0	0	6,9

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	54 m
<b>Jib Length</b>	108 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)			

<b>134</b>	0	0	5,9
<b>136</b>	0	0	5,2
<b>138</b>	0	0	4,5
<b>140</b>	0	0	3,8
<b>142</b>	0	0	3,2

( ) PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	60 m
<b>Jib Length</b>	42 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
<b>82</b>	0	0	2,2	21,9	41,7	54
<b>84</b>	0	0	1,5	20,7	40	52
<b>86</b>	0	0	,8	19,6	38,4	50,1

() PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	60 m
<b>Jib Length</b>	48 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	80	160	240	320	400	450
Radius (m)						
<b>86</b>	0	0	0	16,5	35,3	47
<b>88</b>	0	0	0	15,5	33,8	45,3
<b>90</b>	0	0	0	14,5	32,5	43,7

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**



**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	60 m
<b>Jib Length</b>	54 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
<b>94</b>	0	0	10,9	28,1	38,8
<b>96</b>	0	0	10,1	26,9	37,4
<b>98</b>	0	0	9,3	25,8	36

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	60 m
<b>Jib Length</b>	60 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
<b>98</b>	0	0	7,7	24,3	34,6
<b>100</b>	0	0	6,9	23,1	33,3
<b>102</b>	0	0	6,2	22	32

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	60 m
<b>Jib Length</b>	66 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
<b>102</b>	0	0	3,6	19,5	29,5
<b>104</b>	0	0	2,8	18,5	28,3
<b>106</b>	0	0	2,1	17,5	27

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**
**"Standard-Vario-SL"**
**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	60 m
<b>Jib Length</b>	72 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					

<b>106</b>	0	0	0	14,7	24,2
<b>108</b>	0	0	0	13,8	23,1
<b>110</b>	0	0	0	12,9	22
<b>112</b>	0	0	0	12,1	21
<b>114</b>		0	0	11,2	20

**() PLMIN-loads are greater than max. perm. capacities**
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	60 m
<b>Jib Length</b>	78 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	114	116	118	
	0	0	10	18,7
	0	0	9,2	17,8
	0	0	8,4	16,9

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	60 m
<b>Jib Length</b>	84 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	240	320	400	450
<b>118</b>	0	0	6,2	14,6
<b>120</b>	0	0	5,4	13,7
<b>122</b>	0	0	4,7	12,9
<b>124</b>	0	0	4	12,1
<b>126</b>	0	0	3,4	11,3

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	60 m
<b>Jib Length</b>	90 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	240	320	400	450
<b>122</b>	0	0	3,3	11,5
<b>124</b>	0	0	2,6	10,7
<b>126</b>	0	0	2	9,9
<b>128</b>	0	0	1,4	9,1
<b>130</b>	0	0	,8	8,4

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	60 m
<b>Jib Length</b>	96 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	240	320	400	450
<b>126</b>	0	0	0	7,7
<b>128</b>	0	0	0	7
<b>130</b>	0	0	0	6,2
<b>132</b>		0	0	5,5
<b>134</b>		0	0	4,9
<b>136</b>		0	0	4,2
<b>138</b>		0	0	3,5

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**



**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	60 m
<b>Jib Length</b>	102 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	320	400	450
--	-----	-----	-----

<b>130</b>	0	0	5,4
<b>132</b>	0	0	4,7
<b>134</b>	0	0	4
<b>136</b>	0	0	3,3
<b>138</b>	0	0	2,7
<b>140</b>	0	0	2
<b>142</b>	0	0	1,4

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	60 m
<b>Jib Length</b>	108 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

320	400	450
-----	-----	-----

138	0	0	,2
140	0	0	0
142	0	0	0
144	0	0	0
146	0	0	0
148	0	0	0
150	0	0	0

( ) PLMIN-loads are greater than max. perm. capacities

Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	66 m
<b>Jib Length</b>	42 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
<b>86</b>	0	0	13,6	32,4	44,2
<b>88</b>	0	0	12,6	31	42,5
<b>90</b>	0	0	11,7	29,7	40,9

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	66 m
<b>Jib Length</b>	48 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
<b>90</b>	0	0	8,6	26,5	37,7
<b>92</b>	0	0	7,8	25,3	36,3
<b>94</b>	0	0	7	24,2	34,9

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	66 m
<b>Jib Length</b>	54 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
<b>98</b>	0	0	3,8	20,2	30,5
<b>100</b>	0	0	3,1	19,2	29,3
<b>102</b>	0	0	2,5	18,3	28,2

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	66 m
<b>Jib Length</b>	60 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
<b>102</b>	0	0	,9	16,8	26,8
<b>104</b>	0	0	,3	15,9	25,6
<b>106</b>	0	0	0	14,9	24,5

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**
**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	66 m
<b>Jib Length</b>	66 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)				
<b>106</b>	0	0	12,4	22
<b>108</b>	0	0	11,5	20,9
<b>110</b>	0	0	10,7	19,9

( ) PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	66 m
<b>Jib Length</b>	72 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	240	320	400	450
<b>110</b>	0	0	8	17,1
<b>112</b>	0	0	7,2	16,1
<b>114</b>	0	0	6,5	15,2
<b>116</b>	0	0	5,8	14,4
<b>118</b>	0	0	5,1	13,5

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**



**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	66 m
<b>Jib Length</b>	78 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	240	320	400	450
<b>118</b>	0	0	3,8	12,2
<b>120</b>	0	0	3,1	11,4
<b>122</b>	0	0	2,5	10,7

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	66 m
<b>Jib Length</b>	84 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	240	320	400	450
<b>122</b>	0	0	,2	8,4
<b>124</b>	0	0	0	7,6
<b>126</b>	0	0	0	6,9
<b>128</b>	0	0	0	6,2
<b>130</b>		0	0	5,5

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	66 m
<b>Jib Length</b>	90 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)			

<b>126</b>	0	0	5,4
<b>128</b>	0	0	4,8
<b>130</b>	0	0	4,1
<b>132</b>	0	0	3,5
<b>134</b>	0	0	2,8

( ) PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
 "Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	66 m
<b>Jib Length</b>	96 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

320	400	450
-----	-----	-----

<b>130</b>	0	0	1,9
<b>132</b>	0	0	1,2
<b>134</b>	0	0	,6
<b>136</b>	0	0	0
<b>138</b>	0	0	0
<b>140</b>	0	0	0
<b>142</b>	0	0	0

( ) PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	66 m
<b>Jib Length</b>	102 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)			
<b>138</b>	0	0	0
<b>140</b>	0	0	0
<b>142</b>	0	0	0
<b>144</b>	0	0	0
<b>146</b>	0	0	0

( ) PLMIN-loads are greater than max. perm. capacities  
Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	66 m
<b>Jib Length</b>	108 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	400	450
Radius (m)		

142	0	0
144	0	0
146	0	0
148	0	0
150	0	0
154	0	0

( ) PLMIN-loads are greater than max. perm. capacities  
Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	72 m
<b>Jib Length</b>	42 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
<b>90</b>	0	0	5,1	23	34,2
<b>92</b>	0	0	4,3	21,9	32,9
<b>94</b>	0	0	3,7	20,8	31,5

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	72 m
<b>Jib Length</b>	54 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	102	104	106	
	0	0	0	
	12,2	11,4	10,6	
	22	21,1	20,1	

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**



**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	72 m
<b>Jib Length</b>	60 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)				
<b>106</b>	0	0	9,1	18,7
<b>108</b>	0	0	8,4	17,7
<b>110</b>	0	0	7,6	16,8

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	72 m
<b>Jib Length</b>	66 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	240	320	400	450
<b>110</b>	0	0	5	14,3
<b>112</b>	0	0	4,3	13,4
<b>114</b>	0	0	3,6	12,5
<b>116</b>	0	0	2,9	11,7
<b>118</b>	0	0	2,2	10,8

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	72 m
<b>Jib Length</b>	72 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	240	320	400	450
<b>114</b>	0	0	1	9,8
<b>116</b>	0	0	,4	9
<b>118</b>	0	0	0	8,2
<b>120</b>	0	0	0	7,5
<b>122</b>	0	0	0	6,8

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
 "Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	72 m
<b>Jib Length</b>	78 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)	122	124	126
	0	0	0
	5,5	4,8	4,2

( ) PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
 "Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	72 m
<b>Jib Length</b>	84 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	320	400	450	
Radius (m)				

<b>126</b>	0	0	1,8
<b>128</b>	0	0	1,2
<b>130</b>	0	0	,6
<b>132</b>	0	0	,1
<b>134</b>	0	0	0

( ) PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	72 m
<b>Jib Length</b>	90 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)			

<b>130</b>	0	0	0
<b>132</b>	0	0	0
<b>134</b>	0	0	0
<b>136</b>	0	0	0
<b>138</b>	0	0	0

( ) PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	72 m
<b>Jib Length</b>	96 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

320	400	450
-----	-----	-----

<b>134</b>	0	0	0
<b>136</b>	0	0	0
<b>138</b>	0	0	0
<b>140</b>		0	0
<b>142</b>		0	0
<b>144</b>		0	0
<b>146</b>		0	0

( ) PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	72 m
<b>Jib Length</b>	102 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	400	450	
Radius (m)			

<b>142</b>	0	0	
<b>144</b>	0	0	
<b>146</b>	0	0	
<b>148</b>	0	0	
<b>150</b>	0	0	

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**



**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	72 m
<b>Jib Length</b>	108 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	400	450
Radius (m)		

<b>146</b>	0	0
<b>148</b>	0	0
<b>150</b>	0	0
<b>154</b>	0	0
<b>158</b>	0	0

() PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	78 m
<b>Jib Length</b>	42 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	160	240	320	400	450
Radius (m)					
<b>94</b>	0	0	0	14,5	25,3
<b>96</b>	0	0	0	13,6	24,1
<b>98</b>	0	0	0	12,8	23,1

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	78 m
<b>Jib Length</b>	54 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	106	108	110	
	0	0	4,8	14,3
	0	0	4,2	13,5
	0	0	3,6	12,7

( ) PLMIN-loads are greater than max. perm. capacities  
Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	78 m
<b>Jib Length</b>	60 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	110	112	114	
	0	0	2,1	11,3
	0	0	1,5	10,5
	0	0	,9	9,8

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	78 m
<b>Jib Length</b>	66 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	240	320	400	450
<b>114</b>	0	0	0	7,2
<b>116</b>	0	0	0	6,5
<b>118</b>		0	0	5,7
<b>120</b>		0	0	5
<b>122</b>		0	0	4,3

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	78 m
<b>Jib Length</b>	72 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	320	400	450
--	-----	-----	-----

<b>122</b>	0	0	1,8
<b>124</b>	0	0	1,2
<b>126</b>	0	0	,6

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	78 m
<b>Jib Length</b>	78 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)			
126	0	0	0
128	0	0	0
130	0	0	0

( ) PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	78 m
<b>Jib Length</b>	84 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)			

<b>130</b>	0	0	0
<b>132</b>	0	0	0
<b>134</b>	0	0	0
<b>136</b>	0	0	0
<b>138</b>		0	0

() PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!



**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	78 m
<b>Jib Length</b>	90 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	400	450
--	-----	-----

<b>134</b>	0	0
<b>136</b>	0	0
<b>138</b>	0	0
<b>140</b>	0	0
<b>142</b>	0	0

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	78 m
<b>Jib Length</b>	96 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	400	450
Radius (m)		

<b>138</b>	0	0
<b>140</b>	0	0
<b>142</b>	0	0
<b>144</b>	0	0
<b>146</b>	0	0
<b>148</b>	0	0
<b>150</b>	0	0

( ) PLMIN-loads are greater than max. perm. capacities  
Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	78 m
<b>Jib Length</b>	102 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

400	450
-----	-----

146	0	0
148	0	0
150	0	0
154	0	0

**( ) PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

# CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	78 m
<b>Jib Length</b>	108 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)   
Radius (m)

150	0
154	0
158	0
162	0

() PLMIN-loads are greater than max. perm. capacities  
Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	84 m
<b>Jib Length</b>	42 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	98	100	102	
	0	0	6	16,3
	0	0	5,3	15,4
	0	0	4,6	14,5

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	84 m
<b>Jib Length</b>	54 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	320	400	450
--	-----	-----	-----

<b>110</b>	0	0	6,5
<b>112</b>	0	0	5,8
<b>114</b>	0	0	5,2

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	84 m
<b>Jib Length</b>	60 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)			
114	0	0	3,8
116	0	0	3,2
118	0	0	2,6

( ) PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	84 m
<b>Jib Length</b>	66 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)			

<b>118</b>	0	0	0
<b>120</b>	0	0	0
<b>122</b>	0	0	0
<b>124</b>	0	0	0
<b>126</b>	0	0	0

( ) PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!



**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	84 m
<b>Jib Length</b>	72 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)			
126	0	0	0
128	0	0	0
130	0	0	0

( ) PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	84 m
<b>Jib Length</b>	78 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	400	450	
Radius (m)			

<b>130</b>	0	0	
<b>132</b>	0	0	
<b>134</b>	0	0	
<b>136</b>	0	0	
<b>138</b>	0	0	

( ) PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	84 m
<b>Jib Length</b>	84 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	400	450
Radius (m)		

<b>134</b>	0	0
<b>136</b>	0	0
<b>138</b>	0	0
<b>140</b>	0	0
<b>142</b>	0	0

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	84 m
<b>Jib Length</b>	90 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

400	450
-----	-----

<b>138</b>	0	0
<b>140</b>	0	0
<b>142</b>	0	0
<b>144</b>	0	0
<b>146</b>	0	0

**() PLMIN-loads are greater than max. perm. capacities**

**Attention: This is no Capacity Chart!!!**

# CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	84 m
<b>Jib Length</b>	96 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)   
Radius (m)

142	0
144	0
146	0
148	0
150	0
154	0

( ) PLMIN-loads are greater than max. perm. capacities  
Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	84 m
<b>Jib Length</b>	102 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)   
Radius (m)

150	0
154	0
158	0

( ) PLMIN-loads are greater than max. perm. capacities  
Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	90 m
<b>Jib Length</b>	42 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	240	320	400	450
Radius (m)	102	104	106	
	0	0	0	8,1
	0	0	0	7,4
	0	0	0	6,7

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
 "Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	90 m
<b>Jib Length</b>	54 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	320	400	450
Radius (m)			
<b>114</b>	0	0	0
<b>116</b>	0	0	0
<b>118</b>	0	0	0

( ) PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!



**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	90 m
<b>Jib Length</b>	60 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	320	400	450
<b>118</b>	0	0	0
<b>120</b>	0	0	0
<b>122</b>	0	0	0

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	90 m
<b>Jib Length</b>	66 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	400	450	
Radius (m)			

<b>122</b>	0	0	
<b>124</b>	0	0	
<b>126</b>	0	0	
<b>128</b>	0	0	
<b>130</b>	0	0	

() PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
 "Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	90 m
<b>Jib Length</b>	72 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	400	450	
Radius (m)			

<b>130</b>	0	0	
<b>132</b>	0	0	
<b>134</b>	0	0	

( ) PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	90 m
<b>Jib Length</b>	78 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	400	450
Radius (m)		

<b>134</b>	0	0
<b>136</b>	0	0
<b>138</b>	0	0
<b>140</b>	0	0
<b>142</b>	0	0

( ) PLMIN-loads are greater than max. perm. capacities  
Attention: This is no Capacity Chart!!!

# CC6800

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	90 m
<b>Jib Length</b>	84 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)   
Radius (m)

138	0
140	0
142	0
144	0
146	0

() PLMIN-loads are greater than max. perm. capacities  
Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**
**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	90 m
<b>Jib Length</b>	90 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

 Superlift Counterweight (t)  
 Radius (m)

450
-----

142	0
144	0
146	0
148	0
150	0
154	0

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**

**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	96 m
<b>Jib Length</b>	36 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)  
Radius (m)

	320	400	450
--	-----	-----	-----

<b>102</b>	0	0	2,8
<b>104</b>	0	0	2,2
<b>106</b>	0	0	1,6

**() PLMIN-loads are greater than max. perm. capacities**  
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	96 m
<b>Jib Length</b>	54 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	400	450
Radius (m)		

<b>118</b>	0	0
<b>120</b>	0	0
<b>122</b>	0	0

( ) PLMIN-loads are greater than max. perm. capacities  
Attention: This is no Capacity Chart!!!



**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
**"Standard-Vario-SL"**

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	96 m
<b>Jib Length</b>	60 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	400	450	
Radius (m)			

<b>122</b>	0	0	
<b>124</b>	0	0	
<b>126</b>	0	0	

( ) PLMIN-loads are greater than max. perm. capacities  
 Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	96 m
<b>Jib Length</b>	66 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)	400	450
Radius (m)		

<b>126</b>	0	0
<b>128</b>	0	0
<b>130</b>	0	0
<b>132</b>	0	0
<b>134</b>	0	0

**() PLMIN-loads are greater than max. perm. capacities**  
Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	96 m
<b>Jib Length</b>	72 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)   
Radius (m)

<b>134</b>	0
<b>136</b>	0
<b>138</b>	0

( ) PLMIN-loads are greater than max. perm. capacities  
Attention: This is no Capacity Chart!!!

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

<b>SWSL-PLMIN</b>
-------------------

**"Standard-Vario-SL"**
**Attention: This is no Capacity Chart!!!**

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	96 m
<b>Jib Length</b>	78 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

 Superlift Counterweight (t)  
 Radius (m)

450
-----

138	0
140	0
142	0
144	0
146	0

**() PLMIN-loads are greater than max. perm. capacities**
**Attention: This is no Capacity Chart!!!**

**CC6800**

Required loads, that do lift up the SL-counterweight on tray from ground.

**SWSL-PLMIN**  
"Standard-Vario-SL"

Attention: This is no Capacity Chart!!!

<b>Slew Range</b>	0-360 °
<b>Main Boom Length</b>	96 m
<b>Jib Length</b>	84 m
<b>SL-Mast Length</b>	40,5 m
<b>Angle Main Boom</b>	45 °
<b>Track Width</b>	9,6 m
<b>Counterweight</b>	250 t
<b>Central Ballast</b>	80 t
<b>SL-Mast Radius</b>	18,5 m
<b>Superlift Radius</b>	18 m

Superlift Counterweight (t)   
Radius (m)

142	0
144	0
146	0

( ) PLMIN-loads are greater than max. perm. capacities  
Attention: This is no Capacity Chart!!!